

| STANDARD RATINGS | | | | | | | | | | | | | |
|------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|-------|------|------|
| Vrms | 1100 | | 750 | | 900 | 700 | | | | 500 | 550 | 500 | |
| MFD at 1KHz | 1.2 | 1.4 | 3.0 | 3.3 | 4.0 | 5.6 | 6.3 | 8.5 | 10 | 21 | 27 | 33 | 37 |
| Current Irms | 600 | 600 | 800 | 800 | 700 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 |
| Power Kvar | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 |
| Frequency KHz | 55-96 | 46-83 | 47-68 | 43-62 | 25-39 | 29-57 | 26-51 | 19-38 | 16-32 | 15 | 10-12 | 10 | 9 |
| Terminal Style | ST | ST | ST | ST | ST | ST | ST | ST | ST | ST | ST | ST | ST |
| ØD | 80 | 80 | 80 | 80 | 102 | 80 | 80 | 88 | 95 | 80 | 102 | 102 | 102 |



KEY FEATURES

- Maximum Frequency 100 KHz
- Operating Temperature range -25°C to +85°C
- Low ESL & ESR
- Low loss Polypropylene dielectric
- Water flow rate 10 LPM
- Cooling: Conduction Cooled

DIMENSIONS (mm)

