

**Series DE - High Voltage Pulse Discharge Capacitors**



Double-Ended Plastic Case  
High Voltage Capacitors, 5 kV to 50 kV  
Inductance less than 100 nH

Don't see the capacitor you're looking for? We have thousands of designs in our database. Please contact us.

Part Number	Cap Rating ( $\mu$ F)	Voltage Rating (kV)	Max Peak Current (kA)	Max RMS Current (A)	Design Life (20% VR)	Operating Temp Range (°C)	Approx. Inductance (nH)
31697	0.040	36	25	25	$1 \times 10^5$	-30 to +65	40
31677	0.045	40	25	25	$3 \times 10^7$	-30 to +65	80
31393	0.060	40	25	25	$1 \times 10^5$	-10 to +40	90
31662	0.090	40	25	25	$1 \times 10^5$	-10 to +40	80
31981	0.100	40	25	25	$1 \times 10^5$	-10 to +40	60
37218	0.010	45	10	65	$3 \times 10^5$	-30 to +65	60
31583	0.015	45	25	25	$4 \times 10^5$	-30 to +65	60
37093	0.020	45	25	30	$4 \times 10^5$	-30 to +65	50
31607	0.030	45	25	30	$2 \times 10^5$	-10 to +40	50
37600	2.000	5	25	25	$1 \times 10^5$	-30 to +65	20
37696	0.250	10	25	40	$3 \times 10^5$	-30 to +65	20
37636	0.500	10	25	25	$1 \times 10^5$	-30 to +65	20
37612	0.050	25	25	25	$1 \times 10^5$	-30 to +65	20
37618	0.050	30	25	25	$1 \times 10^5$	-30 to +65	20
37623	0.030	36	25	25	$1 \times 10^5$	-30 to +65	20
37628	0.015	40	25	25	$1 \times 10^5$	-30 to +65	20
37635	0.007	50	25	25	$1 \times 10^5$	-30 to +65	20
37633	0.010	50	25	25	$1 \times 10^5$	-30 to +65	20
37634	0.0125	50	25	25	$1 \times 10^5$	-30 to +65	20

**Double-Ended High Voltage Capacitors (continued)**

Part Number	Cap Rating ( $\mu\text{F}$ )	Case Dimensions H x W x L (Millimeters)	Case Dimensions H x W x L (Inches)	Approx. Weight (kgs)	Approx. Weight (lbs)	Outline Drawing
31687	0.040	102 x 153 x 142	4.0 x 6.0 x 5.6	2.8	6.1	B1
31677	0.045	102 x 153 x 244	4.0 x 6.0 x 9.6	4.2	9.3	B1
31393	0.060	102 x 153 x 244	4.0 x 6.0 x 9.6	5.0	11.0	B1
31662	0.090	102 x 153 x 330	4.0 x 6.0 x 13.0	6.5	14.4	B1
31981	0.100	102 x 153 x 267	4.0 x 6.0 x 10.5	5.5	12.0	B1
37218	0.010	102 x 153 x 218	4.0 x 6.0 x 8.5	4.0	8.8	B1
31583	0.015	102 x 153 x 218	4.0 x 6.0 x 8.5	4.6	10.2	B1
37093	0.020	102 x 153 x 229	4.0 x 6.0 x 9.0	5.0	11.0	B1
31507	0.030	102 x 153 x 218	4.0 x 6.0 x 8.5	4.4	9.7	B1
37600	2.000	58 x 150 x 77	2.3 x 5.9 x 3.0	0.9	2.0	B2
37686	0.250	58 x 150 x 133	2.3 x 5.9 x 5.25	1.6	3.4	B2
37636	0.500	58 x 150 x 102	2.3 x 5.9 x 4.0	1.3	2.9	B2
37612	0.050	58 x 150 x 77	2.3 x 5.9 x 3.0	0.9	2.0	B2
37618	0.050	58 x 150 x 102	2.3 x 5.9 x 4.0	1.1	2.5	B2
37623	0.030	58 x 150 x 102	2.3 x 5.9 x 4.0	1.2	2.6	B2
37628	0.015	58 x 150 x 77	2.3 x 5.9 x 3.0	0.9	2.0	B2
37635	0.007	58 x 150 x 127	2.3 x 5.9 x 5.0	1.4	3.1	B2
37633	0.010	58 x 150 x 102	2.3 x 5.9 x 4.0	1.1	2.5	B2
37634	0.0125	58 x 150 x 102	2.3 x 5.9 x 4.0	1.1	2.5	B2

Specifications are subject to change without prior notice.