

## Series DP - General Purpose Pulse Capacitors



High Voltage Pulse Discharge Capacitors  
Lasers, Flash Lamps, Other Pulse Circuits Moderate to Long Life

Don't see the capacitor you're looking for? We have thousands of designs in our database. Please [contact us](#).

Part Number	Cap Rating (μF)	Voltage Rating (kV)	Max Peak Current (kA)	Max RMS Current (A)	Design Life (20% VR)	Operating Temp Range (°C)	Approx. Inductance (nH)
30542	50	2.0	25	25	$5 \times 10^7$	-30 to +65	100
30543	100	2.0	25	25	$6 \times 10^8$	-30 to +65	120
39504	185	3.0	25	25	$5 \times 10^4$	-10 to +40	160
30545	10	3.5	25	25	$1 \times 10^6$	-30 to +65	50
30549	50	3.5	25	25	$1 \times 10^6$	-30 to +65	120
30550	10	5.0	25	25	$4 \times 10^5$	-30 to +65	90
30552	50	5.0	25	25	$2 \times 10^5$	-30 to +65	170
30665	20	7.5	25	25	$1 \times 10^5$	-30 to +65	90
39741	2	15.0	25	25	$2.5 \times 10^5$	-30 to +65	110

**Drawn Metal Can High Voltage Capacitors (continued)**

Part Number	Cap Rating (μF)	Case Dimensions H x W x L (Millimeters)	Case Dimensions H x W x L (Inches)	Approx. Weight (kgs)	Approx. Weight (lbs)	Outline Drawing
30542	50	73 x 116 x 197	2.88 x 4.56 x 7.75	2.3	5.0	D1
30543	100	96 x 116 x 197	3.75 x 4.56 x 7.75	3.5	7.6	D1
39504	185	96 x 116 x 267	3.75 x 4.56 x 10.5	5.0	11.0	D1
30545	10	49 x 74 x 175	1.91 x 2.91 x 6.88	0.8	1.7	D2
30549	50	96 x 116 x 184	3.75 x 4.56 x 7.25	2.7	6.0	D1
30550	10	50 x 93 x 184	1.96 x 3.66 x 7.25	1.1	2.4	D2
30552	50	96 x 116 x 267	3.75 x 4.56 x 10.5	4.0	8.7	D1
30665	20	96 x 116 x 267	3.75 x 4.56 x 10.5	4.5	10.0	D1
39741	2	81 x 86 x 175	3.19 x 3.75 x 6.88	1.9	4.2	D1

Specifications are subject to change without prior notice.

Mounting brackets available from **FIGLEY STAMPING COMPANY**

