

2.4-2.5 GHZ SOLID-STATE HIGH-POWER MICROWAVE GENERATOR

PTS Series

Frequency Range

- Frequency range: full 2.4–2.5 GHz ISM band
- Frequency resolution: 1 kHz
- Absolute frequency accuracy: +/- 2.5 ppm
- Frequency stability: +/- 0.5 ppm
- Phase adjustment: 0–360°, 1° resolution
- Operating modes: fixed single frequency, full/partial band sweep, or optimized frequency hopping
- Frequency sweep step speed: 1 Hz to 10 kHz adjustable
- Frequency change response time: <1 msec

Microwave Power

- Power output: based on NXP's MRF24300N

Model	Maximum Power	Minimum Across Band
PTS-4	5 kW	4 kW
PTS-8	10 kW	8 kW
PTS-16	20 kW	16 kW

- Power set resolution: 1 Watt at full power
- Harmonic suppression: >40 dBc
- Forward and reflected power (S11 and S21) real-time display
- Power control accuracy: 0.1%
- Power measurement accuracy: forward power 0.1%, reflected power 0.5%
- Maximum mismatch for full power output: 6 dB return loss = 3:1 VSWR
- Integral isolators protect against load mismatch
- Proportional power fold back under excessive load mismatch
- Automatic load-tuning
- Automatic return loss mapping across the band
- Power switching speed: <1 msec

Modulation

- Modes: CW, pulse width modulation, or user-defined waveform
- PWM pulse mode: 10 kHz maximum pulse rate, 0–100% duty cycle
- Exciter output and RF input connectors permit multiple generators to be phase-coherent



Control System

- Windows-based interactive user control software
- USB 2.0 interface to Windows PC
- Manual or automatic operation
- Built-in test features
- LabView™ instrument driver available

Wired Control Interface

- Digital outputs (0–24 V sinking): ready, RF-on, fault
- Digital inputs (5–24 V sinking): RF-on/off, emergency stop loop, arc detect
- Arc detect input to RF power-off delay time: <10 µsec
- Analog output (4–20 mA): RF power output
- Analog input: (4–20 mA): RF power control

2.4-2.5 GHZ SOLID-STATE HIGH-POWER MICROWAVE GENERATOR

PTS Series

External Connectors

- RF output: WR-340 waveguide (individual 7/16 DIN connections optional)
- External RF input: SMA, 0 dBm nominal
- External exciter output: SMA, 0 dBm nominal
- External control: 16-pin rectangular connector with screw terminal connections

Power

- AC mains power input: 180-264 / 342-528 VAC three-phase, 50/60 Hz
 - Maximum current per phase:
 - 4-blade: 50 A / 30 A
 - 8-blade: 95 A / 65 A
 - 16-blade: 190 A / 130 A
 - Inrush current: 2.5 x maximum current
- Power supply: high-efficiency 32 VDC switch mode
- Line-to-RF power conversion efficiency: >50% at maximum power
- Transient over-voltage: 15% greater than voltage rating max
- EN60950-1, IEC60950-1, CE

Environmental

- Cooling
 - Hybrid air/water option:
 - Ambient environmental temperature: 0°–40° C
 - Max inlet water temperature: 40° C
 - 4-blade: 2 GPM min
 - 8-blade: 4 GPM min
 - 16-blade: 8 GPM min
 - Water cooled option:
 - Ambient environmental temperature: 0°–50° C
 - Max inlet water temperature: 40° C
 - 4-blade: 3 GPM min
 - 8-blade: 5.5 GPM min
 - 16-blade: 11 GPM min
- Humidity: non-condensing
- Electromagnetic susceptibility: designed to meet EN61000-4; -2, -3, -4, -5, -6, -8

Dimensions and Weight

- Dimensions: 56.5"-58.25" H x 48" L x 26.4" W (height is adjustable with levelling feet)
- Weight: 800-1200 lb (dependent on system configuration)



PrecisePower Control Screen

PrecisePower™



800.348.5580 | 630.208.2200 | RELPOWER.COM

©2017 National Electronics. National Electronics and its affiliates reserve the right to make changes to the product(s), specifications or other information contained herein without notice. National Electronics assumes no responsibility for any errors which may appear in this document. No part of this document may be copied or reproduced in any form or by any means without the prior written consent of National Electronics.