

GORE Cross Reference, DC-26.5GHz model

Frequency	Gore Cable Type	Center conductor	Junkosha Cable Type	Center conductor	MWX Features
18GHz	0H	stranded	MWX221	Stranded	Low loss, Flexible
	0X	Solid	MWX221		Flexible, Low loss
	0S	stranded	MWX221		Low loss, Flexible
	0U	stranded	MWX021		Available till 26.5GHz
	0Q	Solid	MWX315		Flexible, Low loss
	0P	stranded	MWX315		Low loss, Flexible
	0M	Solid	MWX315		Flexible, Low loss
26.5GHz	0W	Solid	MWX221		Flexible, Low loss
	0R	stranded	MWX221		Low loss, Flexible
	0T	stranded	MWX021		Flexible

GORE Cross Reference, 40-120GHz model, for 5G testing

Frequency	Gore Cable Type	Center conductor	Junkosha Cable Type	Center conductor	MWX Features
40GHz	OK	Solid	MWX241	Stranded	Flexible
	OD	Solid	MWX051	Solid	Flexible
50GHz	ON	Solid	MWX051	Solid	Flexible
	OZ	Solid	MWX251	Stranded	Low Loss, Flexible
67GHz	OF	Solid	MWX061	Solid	Flexible
			MWX261	Solid	Low loss, Flexible
110GHz	CX	Solid	MWX001	Solid	Low loss
			MWX002	Solid	Available till 120GHz

MWX0 have Phase stability in both Bending and Temperature changes

MWX0 have better phase stability than MWX2

MWX2 have phase stability in Bending only but more mechanically flexible

MWX2 have lower loss than MWX0

MWX2 have lower price range than MWX0