

Increase Confidence in Measurements Using MAURY MICROWAVE 7mm CALIBRATION, VALIDATION & INTERCONNECT SOLUTIONS

7mm VNA calibration kits



7mm calibration verification kits



8770CK40 – fixed load SOLT kit (polynomial definitions)



8770CK41 – fixed load SOLT kit (polynomial definitions) with adapters



8770CK60 – characterized verification kit

Calibration-Grade / Metrology Adapters



Model: 7909C1
Frequency Range: 18 GHz
Configuration: NMD2.4mm female to 7mm



Model: 2633C1
Frequency Range: 18 GHz
Configuration: NMD3.5mm female to 7mm



Model: 7922A1
Frequency Range: 18 GHz
Configuration: 2.4mm female to 7mm



Model: 7922B1
Frequency Range: 18 GHz
Configuration: 2.4mm male to 7mm



Model: 8725A
Frequency Range: 18 GHz
Configuration: 2.92mm female to 7mm



Model: 8725B
Frequency Range: 18 GHz
Configuration: 2.92mm male to 7mm



Model: 8022S1
Frequency Range: 18 GHz
Configuration: 3.5mm female to 7mm



Model: 8022T1
Frequency Range: 18 GHz
Configuration: 3.5mm male to 7mm



Model: 2606C
Frequency Range: 18 GHz
Configuration: 7mm to Type N female



Model: 2606D
Frequency Range: 18 GHz
Configuration: 7mm to Type N male



Model: 2622A1
Frequency Range: 18 GHz
Configuration: 7mm to TNC female



Model: 2622B
Frequency Range: 18 GHz
Configuration: 7mm to TNC male



Model: 2625A
Frequency Range: 18 GHz
Configuration: 7mm to SMA female



Model: 2625B
Frequency Range: 18 GHz
Configuration: 7mm to SMA male

Connector Gages



Torque Wrenches



A028F – 7mm digital connector gage kit



A028D – 7mm analog connector gage kit



TW-12 – 0.75 hex torque wrench with 12 in/lb torque

Maury Microwave

MAURY MICROWAVE / 1F-004 / Rev 2021.11/A

Distribution
Partner

**Richardson
Electronics**
POWER & MICROWAVE
TECHNOLOGIES



800.348.5580
630.208.2200



rellpower.com
rellpower@rell.com