





NON-MAGNETIC COMPONENTS



- High-Q Capacitors
- High Power Custom Assemblies
 - Variable Capacitors
- Thin Film Components
- Single Layer Capacitors

Non-magnetic component material choice is essential when developing projects where even the smallest trace of magnetism is not suitable for medical applications such as Magnetic Resonance Imaging (MRI) and Nuclear Magnetic Resonance (NMR) scanners, hi-Rel medical systems, test and diagnostic equipment, and laboratory analysis systems.

Non-magnetic components are also used in other sectors of the electronics industry, including the military, telecommunication, and aerospace industries.





Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

0505C/P (0.055" x 0.055")

Product Features

- High Q
- High Power
- Low ESR/ESL
- Low Noise
- High Self-Resonance
- Ultra Stable Performance
- Capacitance Range:
0.1pF to 1000pF
- Working Voltage: 150V
- Extended Voltage: 300V


Product Applications

Typical Functional Applications:

- Tuning • Bypass • Coupling
- Feedback • D.C. Blocking
- Impedance Matching


Typical Circuit Applications:

- UHF/Microwave RF Power Amplifiers
- Mixers • Oscillators • Filter Networks
- Low Noise Amplifiers • Timing Circuits and Delay Lines



Marking shown for illustration purposes only.
Actual marking may differ.


Part Numbering



Capacitor Dimensions

Unit: inch (millimeter)

Length	Width	Thickness	Overlap
Lc	Wc	Tc	B
0.055 + 0.015 to -0.010 (1.40 + 0.38 to -0.25)	0.055 ± .010 (1.40 ± 0.25)	0.057 (1.45 max)	0.020 (0.51 max)



Temperature Coefficient

- C:** -55° to 125°C 0± 30ppm/°C;
>125°C to 200°C 0± 60ppm/°C
- P:** ±90 ±20ppm/°C



Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

0505C/P (0.055" x 0.055")

≠ 0505C/P Capacitance Values

- NP0=C; P90=P
- **Maximum Capacitance: 0505P=100pF; 0505C=1000pF**
- * - Available in NP0 only.

Special capacitances, tolerances and WVDC are available. Please contact PPI.



Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC	
			Std.	Ext.				Std.	Ext.				Std.	Ext.				Std.	Ext.
0.1	0R1	A,B, C,D	150V	250V or 300V	2.4	2R4	A,B, C,D	150V	250V or 300V	20	200	F,G, J,K	150V	250V or 300V	160	161*	F,G, J,K	150V	200V
0.2	0R2				2.7	2R7				22	220				180	181*			
0.3	0R3				3.0	3R0				24	240				200	201*			
0.4	0R4				3.3	3R3				27	270				220	221*			
0.5	0R5				3.6	3R6				30	300				240	241*			
0.6	0R6				3.9	3R9				33	330				270	271*			
0.7	0R7				4.3	4R3				36	360				300	301*			
0.8	0R8				4.7	4R7				39	390				330	331*			
0.9	0R9				5.1	5R1				43	430				360	361*			
1.0	1R0				5.6	5R6				47	470				390	391*			
1.1	1R1				6.2	6R2				51	510				430	431*			
1.2	1R2				6.8	6R8				56	560				470	471*			
1.3	1R3				7.5	7R5				62	620				510	511*			
1.4	1R4				8.2	8R2				68	680				560	561*			
1.5	1R5				9.1	9R1				75	750				620	621*			
1.6	1R6	10	100	82	820	680	681*												
1.7	1R7	11	110	91	910	750	751*												
1.8	1R8	12	120	100	101	820	821*												
1.9	1R9	13	130	110	111*	910	911*												
2.0	2R0	15	150	120	121*	1000	102*												
2.1	2R1	16	160	130	131*														
2.2	2R2	18	180	150	151*														

*Available in NP0 only



Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

0505C/P (0.055" x 0.055")

≠ Capacitance Tolerance Codes

Code	A	B	C	D	F	G	J	K
Tol.	±0.05pF	±0.1pF	±0.25pF	±0.5pF	±1%	±2%	±5%	±10%

≠ Termination Types

Termination Code	Termination
W	100% Sn Solder over Nickel Plating 
L	90% Sn10%Pb Tin/Lead Solder over Nickel Plating
P (Non-Magnetic) 	100%Sn Solder over Copper Plating 

Note: "Non-Magnetic" means no magnetic materials.

≠ Voltage Codes

Voltage	Code
50V	500
100V	101
150V	151
200V	201
250V	251
300V	301





Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

0505C/P (0.055" x 0.055")

≠ Electrical Specifications

Quality Factor (Q)	Greater than 10,000 at 1 MHz
Insulation Resistance (IR)	10 ⁵ MegaOhms min. @ +25°C rated WVDC 10 ⁴ MegaOhms min. @ +125°C rated WVDC
Rated Voltage	See Rated Voltage Table
Dielectric Withstanding Voltage (WVDC)	250% of Rated Voltage of 5 seconds
Operating Temperature Range	-55°C to 200°C
Temperature Coefficient (TC)	C: -55°C to 125°C 0±30ppm/°C; >125°C to 200°C 0±60ppm/°C P: +90±20ppm/°C
Capacitance Drift	±0.02% or ±0.02pF, whichever is greater
Piezoelectric Effects	None
Termination Type	See Termination Type Table

Capacitors are designed and manufactured to meet the requirements of MIL-PRF-55681 and MIL-PRF-123.

≠ Environmental Specifications

	Specification	Test Parameters
Thermal Shock	DWV: The initial Value IR: Shall not be less than 30% of the initial value. Capacitance Change:	MIL-STD-202, Method 107, Condition A. At the maximum rated temperature (-55°C and 200°C) stay 30 minutes, the time of removing shall not be more than 3 minutes. Perform five cycles.
Moisture Resistance	No more than 0.5% or 0.5pF, whichever is greater.	MIL-STD-202, Method 106
Humidity (Steady State)	DWV: The initial Value IR: The initial value. Capacitance Change: No more than 0.5% or 0.5pF, whichever is greater.	MIL-STD-202, Method 103, Condition A With 1.5Volts DC applied while subjected to an environment of 85°C with 85% relative humidity for 240 hours minimum.
Life	IR: Shall not be less than 30% of the initial value. Capacitance Change: No more than 2.0% or 0.5pF, whichever is greater.	MIL-STD-202, Method 108. For 2000 hours, at 200°C. Rated Voltage DC applies.
Terminal Strength	Force: 10lbs typical, 5lbs. Minimum. Duration Time: 5 to 10 seconds	MIL-STD-202, Method 211A, Test Condition A. Applied a force and maintained for a period of 5 to 10 seconds. The force shall be in the direction of the axes of the terminations.




≠ FPR -- First Parallel Resonance (FPRs)

≠ Definitions and Measurement Conditions

The **First Parallel Resonance, FPR**, is defined as the lowest frequency at which a suckout or notch appears in $|S_{21}|$.


It is generally independent of substrate thickness or dielectric constant, but does depend on capacitor orientation. A horizontal orientation means the capacitor electrode planes are parallel to the plane of the substrate; a vertical orientation means the electrode planes are perpendicular to the substrate.



≠ FSR -- First Series Resonance (FSRs)

≠ Definitions and Measurement Conditions

The **First Series Resonance, FSR**, is defined as the lowest frequency at which the imaginary part of the input impedance, $\text{Im}[Z_{in}]$, equals zero. Should $\text{Im}[Z_{in}]$ or the real part of the input impedance, $\text{Re}[Z_{in}]$, not be monotonic with frequency at frequencies lower than those at which $\text{Im}[Z_{in}] = 0$, the FSR shall be considered as undefined (represented as a gap in the plot). FSR is dependent on internal capacitor structure; substrate thickness and dielectric constant; capacitor orientation, as defined alongside the FPR plot; and mounting pad dimensions.



The measurement conditions are: substrate – Rogers RO4350; substrate dielectric constant = 3.66; horizontal mount substrate thickness (mils) = 25; gap in microstrip trace (mils) = 15; horizontal mount microstrip trace width (mils) = 55. Reference planes at sample edges.

All data has been derived from electrical models created by Modelithics, Inc., a specialty vendor contracted by PPI. The models are derived from measurements on a large number of parts disposed on several different substrates.



Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors


0505C/P (0.055" x 0.055")

≠ ESR vs. Frequency

0505C/P ESR vs Frequency



0505C ESR vs Frequency





Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

0505C/P (0.055" x 0.055")

≠ Q vs. Frequency

0505C/P Q vs Frequency




0505C Q vs Frequency



≠ Current Rating vs. Capacitance

0505C/P Current Rating vs Capacitance




The current depends on voltage limited:

$$I = \frac{\sqrt{2}}{2} I_{peak} = \frac{\sqrt{2}}{2} \times \frac{V_{rated}}{X_c} = \sqrt{2} \pi f C V_{rated}$$

The current depends on power dissipation limited:

$$I = \sqrt{\frac{P_{dissipation}}{ESR}}$$

0505C Current Rating vs Capacitance




Note: If the thermal resistance of mounting surface is 40°C/W, then a power dissipation of 1.5 W will result in the current limited we can calculate the current limited:

$$I = \sqrt{\frac{P_{dissipation}}{ESR}}$$

≠ Capacitor Application Program

Passive Plus, Inc.'s brand new **online Capacitor Application Program (C.A.P.)** helps Engineers and Designers select capacitors according to parameters such as cap value and frequency. C.A.P. allows engineers to insert capacitor requirements (Cap value, Frequency), producing Scattering Matrices (S2P) Charts while providing options (Case Size, Terminations, Mounting), and parameters (ESR, Q, Impedance) along with Datasheets. Once engineers have determined their capacitor requirements, C.A.P. also includes online Requests For Quotes (RFQs) and/or sample requests.



≠ Modelithics Vendor Program

PPI offers design engineers a Free 90-Day Trial license for the Modelithics PPI Component Library. This program provides engineers access to extremely accurate scalable simulation models for Passive Plus capacitors with advanced features that enable a more precise and rapid design process.

Microwave Global Models include every part value in a series and permit users to input substrate thickness, dielectric constant, and loss tangent, as well as mounting pad layout dimensions. Selected models also include capacitor orientation – vertical or horizontal – as an input. Engineers can request FREE use of the models, by either visiting the [Passive Plus Resources page \(http://passiveplus.com/addldocs_resources.php\)](http://passiveplus.com/addldocs_resources.php).




≡ Recommended Land Pattern Dimensions

When mounting the capacitor to substrate, it's important to carefully consider that the amount of solder (size of fillet) used has a direct effect upon the capacitor once it's mounted.

- 1) The greater the amount of solder, the greater the stress to the elements. This may cause the substrate to break or crack.
- 2) In the situation where two or more devices are mounted onto a common land, be sure to separate the device into exclusive pads by using soldering resist.


≡ Horizontal Mounting (mm)

A	B	C
0.5-0.7	0.7-0.9	1.2-1.4



≡ Vertical Mounting* (mm)


A	B	C
0.5-0.7	0.7-0.9	1.0-1.2




*Only available below 430pF

≡ Tape & Reel Specifications (mm)

Horizontal Orientation



Vertical Orientation



Orientation	W	P0	P1	T	F	Qty Min	Qty/reel	Tape Material
Horizontal	8.00	4.00	4.00	0.22	3.50	500	3000	Plastic
Vertical	12.00	4.00	4.00	0.30	5.50	300	2000	Plastic

A₀ B₀ K₀

- Determined by component size. Typical clearance between the cavity and the component is:
.05 (.002) min to .50 (.020) max for 8mm tape and .50 (.002) min to .65 (.026) max for 12mm tape.
- The component cannot rotate more than 20° within the determined cavity.



Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

0505C/P (0.055" x 0.055")

≠ Engineering Design Kits

PPI offers Design Kits for engineers who are building and testing prototypes. Each kit contains 16 values; 10 pieces per value.



Kits are offered in Magnetic or Non-Magnetic Terminations. Kits are 100% RoHS compliant.

Kit Number		Value Range	Values	
MAGNETIC	NON-MAGNETIC			
DKD0505C01	DKD0505C05	0.1 - 2.0pF	0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0, 1.2, 1.5, 1.6, 1.8, 2.0pF	✓ RoHS
DKD0505P01	DKD0505P05			
DKD0505C02	DKD0505C06	1 - 10pF	1.0, 1.2, 1.5, 1.8, 2.0, 2.2, 2.4, 2.7, 3.0, 3.3, 3.9, 4.7, 5.6, 6.8, 8.2, 10pF	✓ RoHS
DKD0505P02	DKD0505P06			
DKD0505C03	DKD0505C07	10 - 100pF	10, 12, 15, 18, 20, 22, 24, 27, 30, 33, 39, 47, 56, 68, 82, 100pF	✓ RoHS
DKD0505P03	DKD0505P07			
DKD0505C04	DKD0505C08	100 - 1000pF	100, 120, 150, 180, 200, 220, 240, 270, 300, 330, 390, 470, 560, 680, 820, 1000pF	✓ RoHS

PPI
Passive Plus Inc.
RF & Microwave Components

DKD0505C01

0505C Series 0.1 — 2.0pF
Size: 0.055" x 0.055"
TC = NP0 WVDC = 150V

Hi-Q Low ESR Capacitor Design Kit

www.passiveplus.com

PPI
Passive Plus Inc.
RF & Microwave Components

DKD0505C02

0505C Series 1.0 — 10pF
Size: 0.055" x 0.055"
TC = NP0 WVDC = 150V

Hi-Q Low ESR Capacitor Design Kit

www.passiveplus.com

PPI
Passive Plus Inc.
RF & Microwave Components

DKD0505C03

0505C Series 10 — 100pF
Size: 0.055" x 0.055"
TC = NP0 WVDC = 150V

Hi-Q Low ESR Capacitor Design Kit

www.passiveplus.com

PPI
Passive Plus Inc.
RF & Microwave Components

DKD0505C04

0505C Series 100 — 1000pF
Size: 0.055" x 0.055"
TC = NP0 WVDC = 150V

Hi-Q Low ESR Capacitor Design Kit

www.nassivenlus.com

PPI
Passive Plus Inc.
RF & Microwave Components

DKD0505P01

0505P Series 0.1 — 2.0pF
Size: 0.055" x 0.055"
TC = P90 WVDC = 150V

Hi-Q Low ESR Capacitor Design Kit

www.passiveplus.com

PPI
Passive Plus Inc.
RF & Microwave Components

DKD0505P02

0505P Series 1.0 — 10pF
Size: 0.055" x 0.055"
TC = P90 WVDC = 150V

Hi-Q Low ESR Capacitor Design Kit

www.passiveplus.com

PPI
Passive Plus Inc.
RF & Microwave Components

DKD0505P03

0505P Series 10 — 100pF
Size: 0.055" x 0.055"
TC = P90 WVDC = 150V

Hi-Q Low ESR Capacitor Design Kit

www.passiveplus.com



Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

1111C/P (0.110" x 0.110")

≠ Product Features

- High Q
- High Power
- Low ESR/ESL
- Low Noise
- High Self-Resonance
- Ultra Stable Performance
- Capacitance Range:
0.1pF to 10000pF
- Working Voltage: 500V
- Extended Voltage: 1500V

≠ Product Applications

Typical Functional Applications

- Tuning • Bypass • Coupling
- Feedback • D.C. Blocking
- Impedance Matching


Typical Circuit Applications

- UHF/Microwave RF Power Amplifiers
- Mixers • Oscillators • Filter Networks
- Low Noise Amplifiers • Timing Circuits
and Delay Lines



Marking shown for illustration purposes only.
Actual marking may differ.

≠ Part Numbering



≠ Capacitance Tolerance Codes

Code	A	B	C	D	F	G	J	K
Tol.	±0.05pF	±0.1pF	±0.25pF	±0.5pF	±1%	±2%	±5%	±10%

≠ Voltage Codes

Voltage	Code
50V	500
100V	101
200V	201
300V	301
500V	501
600V	601
1000V	102
1500V	152



Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

1111C/P (0.110" x 0.110")

≠ 1111C/P Capacitance Values

- NP0=C; P90=P
- **Maximum Capacitance: 1111P=1000pF; 1111C=10000pF**
- * - Available in NP0 only.

Special capacitances, tolerances and WVDC are available. Please contact PPI.



Marking shown for illustration purposes only.
Actual marking may differ.

Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC	
			Std.	Ext.				Std.	Ext.				Std.	Ext.				Std.	Ext.
0.1	OR1	A,B	500V	1000V or 1500V	3.3	3R3	A,B C,D	500V	1000V or 1500V	36	360	F,G, J,K	500V	1000V or 1500V	390	391	F,G, J,K	200V	600V
0.2	OR2				3.6	3R6				39	390				430	431			
0.3	OR3				3.9	3R9				43	430				470	471			
0.4	OR4				4.3	4R3				47	470				510	511			
0.5	OR5	A,B, C,D	500V	1000V or 1500V	4.7	4R7	F,G, J,K	500V	1000V or 1500V	51	510	F,G, J,K	300V	1000V	560	561	F,G, J,K	100V	200V
0.6	OR6				5.1	5R1				56	560				620	621			
0.7	OR7				5.6	5R6				62	620				680	681			
0.8	OR8				6.2	6R2				68	680				750	751			
0.9	OR9				6.8	6R8				75	750				820	821			
1.0	1R0				7.5	7R5				82	820				910	911			
1.1	1R1				8.2	8R2				91	910				1000	102			
1.2	1R2				9.1	9R1				100	101				1100	112*			
1.3	1R3				10	100				110	111				1200	122*			
1.4	1R4				11	110				120	121				1500	152*			
1.5	1R5	12	120	130	131	1800	182*												
1.6	1R6	13	130	150	151	2200	222*												
1.7	1R7	15	150	160	161	2700	272*												
1.8	1R8	16	160	180	181	3000	302*												
1.9	1R9	18	180	200	201	3300	332*												
2.0	2R0	20	200	220	221	4700	472*												
2.1	2R1	22	220	240	241	5100	512*												
2.2	2R2	24	240	270	271	5600	562*												
2.4	2R4	27	270	300	301	10000	103*												
2.7	2R7	30	300	330	331														
3.0	3R0	33	330	360	361														


*Available in NP0 only




Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

1111C/P (0.110" x 0.110")

≠ Terminations Types and Codes



Chip Termination:
Codes: **W, L, P**



Microstrip Termination:
Codes: **MS, MN**

Magnetic Terminations

Termination Code	Termination
W	100% Sn Solder over Nickel Plating
L	90% Sn10%Pb Tin/Lead Solder over Nickel Plating
MS	100% Silver

⊗ Non-Magnetic Terminations ⊗

P	100%Sn Solder over Copper Plating
MN	100% Silver

≠ Capacitor Dimensions Unit: inch (millimeter)

Magnetic Terminations								
Code	Term.	Capacitor Dimensions				Lead Dimensions		
		Length	Width	Thickness	Overlap	Length	Width	Thickness
		Lc	Wc	Tc	B	LL	WL	TL

W/L	Chip	0.110 + 0.020 to -0.010 (2.79 +0.51 to -0.25)	0.110 ± 0.010 (2.79 ±0.25)	0.10 (2.54 max)	0.024 (0.60max)	-	-	-
-----	------	---	-------------------------------	--------------------	--------------------	---	---	---

MS	Microstrip	0.135 ± 0.015 (3.43 ± 0.38)	0.110 ± 0.010 (2.79 ±0.25)	0.10 (2.54 max)	-	0.250 (6.35) min	0.093 ±0.005 (2.36 ± 0.13)	0.004 ± 0.001 (0.10 ± 0.13)
----	------------	--------------------------------	-------------------------------	--------------------	---	---------------------	-------------------------------	--------------------------------

⊗ Non-Magnetic Terminations ⊗

Code	Term.	Length	Width	Thickness	Overlap	Length	Width	Thickness
		Lc	Wc	Tc	B	LL	WL	TL

P	Chip	0.110 + 0.020 to -0.010 (2.79 +0.51 to -0.25)	0.110 ± 0.010 (2.79 ±0.25)	0.10 (2.54 max)	0.024 (0.60max)	-	-	-
---	------	---	-------------------------------	--------------------	--------------------	---	---	---

MN	Microstrip Non-Magnetic	0.135 ± 0.015 (3.43 ± 0.38)	0.110 ± 0.010 (2.79 ±0.25)	0.10 (2.54 max)	-	0.250 (6.35) min	0.093 ±0.005 (2.36 ± 0.13)	0.004 ± 0.001 (0.10 ± 0.13)
----	----------------------------	--------------------------------	-------------------------------	--------------------	---	---------------------	-------------------------------	--------------------------------

Note: "Non-Magnetic" means no magnetic materials.



⚡ Electrical Specifications

Quality Factor (Q)	Greater than 10,000 at 1 MHz
Insulation Resistance (IR)	0.1pF to 470pF: 10 ⁶ Megaohms min. @ +25°C rated WVDC
	10 ⁵ Megaohms min. @ +125°C rated WVDC
	510pF to 1000pF: 10 ⁵ Megaohms min. @ +25°C rated WVDC 10 ⁴ Megaohms min. @ +125°C rated WVDC
Rated Voltage	See Rated Voltage Table
Dielectric Withstanding Voltage (WVDC)	250% of Rated Voltage of 5 seconds, Rated Voltage ≤ 500VDC
	150% of Voltage for 5 seconds, 500VDC < Rated Voltage ≤ 1250 VDC
	120% of Voltage for 5 seconds, Rated Voltage > 1250 VDC
Operating Temperature Range	-55°C to 200°C
Temperature Coefficient (TC)	C: -55°C to 125°C 0±30ppm/°C;
	>125°C to 200°C 0±60ppm/°C
	P: +90±20ppm/°C
Capacitance Drift	±0.02% or ±0.02pF, whichever is greater
Piezoelectric Effects	None
Termination Type	See Termination Type Table

⚡ Environmental Specifications

	Specification	Test Parameters
Thermal Shock	DWV: The initial Value IR: Shall not be less than 30% of the initial value. Capacitance Change:	MIL-STD-202, Method 107, Condition A. At the maximum rated temperature (-55°C and 200°C) stay 30 minutes, the time of removing shall not be more than 3 minutes. Perform five cycles.
Moisture Resistance	No more than 0.5% or 0.5pF, whichever is greater.	MIL-STD-202, Method 106
Humidity (Steady State)	DWV: The initial Value IR: The initial value. Capacitance Change: No more than 0.3% or 0.3pF, whichever is greater.	MIL-STD-202, Method 103, Condition A With 1.5Volts DC applied while subjected to an environment of 85°C with 85% relative humidity for 240 hours minimum.
Life	IR: Shall not be less than 30% of the initial value. Capacitance Change: No more than 2.0% or 0.5pF, whichever is greater.	MIL-STD-202, Method 108. For 2000 hours, at 200°C. 200% of Voltage for Capacitors, Rated Voltage ≤ 500VDC; 120% of Voltage for Capacitors, 500VDC < Rated Voltage ≤ 1250VDC; 100% for Voltage for Capacitors, Rated Voltage > 1250VDC
Terminal Strength	Force: 10lbs typical, 5lbs. Minimum. Duration Time: 5 to 10 seconds	MIL-STD-202, Method 211A, Test Condition A. Applied a force and maintained for a period of 5 to 10 seconds. The force shall be in the direction of the axes of the terminations.

Capacitors are designed and manufactured to meet the requirements of MIL-PRF-55681 and MIL-PRF-123.




≠ FPR -- First Parallel Resonance (FPRs)

≠ Definitions and Measurement Conditions

The **First Parallel Resonance, FPR**, is defined as the lowest frequency at which a suckout or notch appears in $|S_{21}|$.

It is generally independent of substrate thickness or dielectric constant, but does depend on capacitor orientation. A horizontal orientation means the capacitor electrode planes are parallel to the plane of the substrate; a vertical orientation means the electrode planes are perpendicular to the substrate.



≠ FSR -- First Series Resonance (FSRs)

≠ Definitions and Measurement Conditions

The **First Series Resonance, FSR**, is defined as the lowest frequency at which the imaginary part of the input impedance, $\text{Im}[Z_{in}]$, equals zero. Should $\text{Im}[Z_{in}]$ or the real part of the input impedance, $\text{Re}[Z_{in}]$, not be monotonic with frequency at frequencies lower than those at which $\text{Im}[Z_{in}] = 0$, the FSR shall be considered as undefined (represented as a gap in the plot). FSR is dependent on internal capacitor structure; substrate thickness and dielectric constant; capacitor orientation, as defined alongside the FPR plot; and mounting pad dimensions.



The measurement conditions are: substrate – Rogers RO4350; substrate dielectric constant = 3.66; horizontal mount substrate thickness (mils) = 50; gap in microstrip trace (mils) = 72; horizontal mount microstrip trace width (mils) = 110. Reference planes at sample edges.

All data has been derived from electrical models created by Modelithics, Inc., a specialty vendor contracted by PPI. The models are derived from measurements on a large number of parts disposed on several different substrates.




Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors


1111C/P (0.110" x 0.110")

≠ ESR vs. Frequency

1111C/P ESR vs Frequency



1111C ESR vs Frequency





Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

1111C/P (0.110" x 0.110")

≠ Q vs. Capacitance

1111C/P Q vs Frequency




1111C Q vs Frequency




≠ Current Rating vs. Capacitance

1111C/P Current Rating vs Capacitance



1111C Current Rating vs Capacitance



The current depends on voltage limited:

$$I = \frac{\sqrt{2}}{2} I_{peak} = \frac{\sqrt{2}}{2} \times \frac{V_{rated}}{X_c} = \sqrt{2} \pi f C V_{rated}$$

The current depends on power dissipation limited:

$$I = \sqrt{\frac{P_{dissipation}}{ESR}}$$

Note: If the thermal resistance of mounting surface is 20°C/W, then a power dissipation of 3 W will result in the current limited we can calculate the current limited:

$$I = \sqrt{\frac{P_{dissipation}}{ESR}}$$




Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

1111C/P (0.110" x 0.110")

≡ Capacitor Application Program

Passive Plus, Inc.'s brand new **online Capacitor Application Program (C.A.P.)** helps Engineers and Designers select capacitors according to parameters such as cap value and frequency. C.A.P. allows engineers to insert capacitors requirements (Cap value, Frequency), producing Scattering Matrices (S2P) Charts while providing options (Case Size, Terminations, Mounting), and parameters (ESR, Q, Impedance) along with Datasheets. Once engineers have determined their capacitor requirements, C.A.P. also includes online Requests For Quotes (RFQs) and/or sample requests.



≡ Modelithics Vendor Program

PPI offers design engineers a Free 90-Day Trial license for the Modelithics PPI Component Library. This program provides engineers access to extremely accurate scalable simulation models for Passive Plus capacitors with advanced features that enable a more precise and rapid design process.

Microwave Global Models include every part value in a series and permit users to input substrate thickness, dielectric constant, and loss tangent, as well as mounting pad layout dimensions. Selected models also include capacitor orientation – vertical or horizontal – as an input. Engineers can request FREE use of the models, by either visiting the [Passive Plus Resources page](http://passiveplus.com/addldocs_resources.php) (http://passiveplus.com/addldocs_resources.php).



≠ Recommended Land Pattern Dimensions

When mounting the capacitor to substrate, it's important to carefully consider that the amount of solder (size of fillet) used has a direct effect upon the capacitor once it's mounted.


- 1) The greater the amount of solder, the greater the stress to the elements. This may cause the substrate to break or crack.
- 2) In the situation where two or more devices are mounted onto a common land, be sure to separate the device into exclusive pads by using soldering resist.

≠ Horizontal Mounting (mm)

A	B	C
1.9	1.7	2.9


≠ Vertical Mounting (mm)

A	B	C
1.9	1.7	2.5




≠ Tape & Reel Specifications (mm)

Horizontal Orientation



Vertical Orientation



Orientation	W	P0	P1	T	F	Qty Min	Qty/reel	Tape Material
Horizontal	8.00	4.00	4.00	0.22	3.50	500	2000	Plastic
Vertical	12.00	4.00	4.00	0.40	5.50	500	1500	Plastic
Vertical	8.00	4.00	4.00	0.22	3.50	500	1500	Plastic

A₀ B₀ K₀

- Determined by component size. Typical clearance between the cavity and the component is:
.05 (.002) min to .50 (.020) max for 8mm tape and .50 (.002) min to .65 (.026) max for 12mm tape.
- The component cannot rotate more than 20° within the determined cavity.

Dimensions: mm



Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

1111C/P (0.110" x 0.110")

Engineering Design Kits

PPI offers Design Kits for engineers who are building and testing prototypes. Each kit contains 16 values; 10 pieces per value.



Kits are offered in Magnetic or Non-Magnetic Terminations. Kits are 100% RoHS compliant.

Kit Number		Value Range	Values	
MAGNETIC	NON-MAGNETIC			
DKD1111C01 DKD1111P01	DKD1111C05 DKD1111P05	1.0 - 10pF	1.0, 1.2, 1.5, 1.8, 2.0, 2.2, 2.4, 2.7, 3.0, 3.3, 3.9, 4.7, 5.6, 6.8, 8.2, 10pF	✓ RoHS
DKD1111C02 DKD1111P02	DKD1111C06 DKD1111P06	10 - 100pF	10, 12, 15, 18, 20, 22, 24, 27, 30, 33, 39, 47, 56, 68, 82, 100pF	✓ RoHS
DKD1111C03 DKD1111P03	DKD1111C07 DKD1111P07	100 - 1000pF	100, 120, 150, 180, 200, 220, 240, 270, 300, 330, 390, 470, 560, 680, 820, 1000pF	✓ RoHS
DKD1111C04 DKD1111P04	DKD1111C08 DKD1111P08	1000 - 10000pF	1000, 1100, 1200, 1500, 1800, 2000, 2200, 2700, 3000, 3300, 3900, 4700, 5100, 5600, 10000pF	✓ RoHS

PPI
Passive Plus Inc.
RF & Microwave Components

DKD1111C01

1111C Series 1.0 — 10pF
Size: 0.110" x 0.110"
TC = NP0 WVDC = 500V

Hi-Q Low ESR Capacitor Design Kit

PPI
Passive Plus Inc.
RF & Microwave Components

DKD1111C02

1111C Series 10 — 100pF
Size: 0.110" x 0.110"
TC = NP0 WVDC = 500V

Hi-Q Low ESR Capacitor Design Kit

PPI
Passive Plus Inc.
RF & Microwave Components

DKD1111C03

1111C Series 100 — 1000pF
Size: 0.110" x 0.110"
TC = NP0 WVDC = 500V

Hi-Q Low ESR Capacitor Design Kit

PPI
Passive Plus Inc.
RF & Microwave Components

DKD1111C04

1111C Series 1000 — 10000pF
Size: 0.110" x 0.110"
TC = NP0 WVDC = 100V

Hi-Q Low ESR Capacitor Design Kit

PPI
Passive Plus Inc.
RF & Microwave Components

DKD1111P01

1111P Series 1.0 — 10pF
Size: 0.110" x 0.110"
TC = P90 WVDC = 500V

Hi-Q Low ESR Capacitor Design Kit

www.passiveplus.com

PPI
Passive Plus Inc.
RF & Microwave Components

DKD1111P02

1111P Series 10 — 100pF
Size: 0.110" x 0.110"
TC = P90 WVDC = 500V

Hi-Q Low ESR Capacitor Design Kit

www.passiveplus.com

PPI
Passive Plus Inc.
RF & Microwave Components

DKD1111P03

1111P Series 100 — 1000pF
Size: 0.110" x 0.110"
TC = P90 WVDC = 500V

Hi-Q Low ESR Capacitor Design Kit

www.passiveplus.com

PPI
Passive Plus Inc.
RF & Microwave Components

DKD1111P04

1111P Series 1000 — 10000pF
Size: 0.110" x 0.110"
TC = P90 WVDC = 100V

Hi-Q Low ESR Capacitor Design Kit

www.passiveplus.com



Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

2225C/P (0.220" x 0.250")

Product Features

- High Q
- High RF Current/Voltage
- Ultra Stable Performance
- Capacitance Range:
0.5pF to 2700pF
- Working Voltage: 2500V
- Extended Voltage: 3600V

Product Applications

Typical Functional Applications:

- Tuning • Bypass • Coupling
- D.C. Blocking • Impedance Matching


Typical Circuit Applications

- UHF/Microwave RF Power Amplifiers
- Antenna Tuning • Plasma Chambers
- Medical Equipment



Marking shown for illustration purposes only.
Actual marking may differ.

Part Numbering



Capacitance Tolerance Codes

Code	A	B	C	D	F	G	J	K
Tol.	±0.05pF	±0.1pF	±0.25pF	±0.5pF	±1%	±2%	±5%	±10%

Voltage Codes

Voltage	Code
500V	501
1000V	102
1500V	152
2000V	202
2500V	252
3000V	302
3600V	362




Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

2225C/P (0.220" x 0.250")

≠ 2225C/P Capacitance Values

- NP0=C; P90=P

Special capacitances, tolerances and WVDC are available. Please contact PPI.




Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC	
			Std.	Ext.				Std.	Ext.				Std.	Ext.				Std.	Ext.
0.5	0R5				4.3	4R3				43	430				430	431	F,G, J,K	1500V	2000V
0.6	0R6				4.7	4R7				47	470				470	471			
0.7	0R7				5.1	5R1				51	510				510	511			
0.8	0R8				5.6	5R6				56	560				560	561			
0.9	0R9				6.2	6R2	B,C, D	2500V	3600V	62	620	F,G, J,K	2500V	3600V	620	621			
1.0	1R0				6.8	6R8				68	680				680	681			
1.1	1R1				7.5	7R5				75	750				750	751	F,G, J,K	1000V	1500V
1.2	1R2				8.2	8R2				82	820				820	821			
1.3	1R3				9.1	9R1				91	910				910	911			
1.4	1R4				10	100				100	101				1000	102			
1.5	1R5				11	110				110	111				1100	112			
1.6	1R6	B,C, D	2500V	3600V	12	120				120	121				1200	122			
1.7	1R7				13	130				130	131				1500	152			
1.8	1R8				15	150				150	151				1800	182	F,G, J,K	500V	N/A
1.9	1R9				16	160				160	161	F,G, J,K	2500V	3000V	2200	222			
2.0	2R0				18	180				180	181				2700	272			
2.1	2R1				20	200	F,G, J,K	2500V	3600V	200	201								
2.2	2R2				22	220				220	221								
2.4	2R4				24	240				240	241								
2.7	2R7				27	270				270	271								
3.0	3R0				30	300				300	301								
3.3	3R3				33	330				330	331	F,G, J,K	1500V	2000V					
3.6	3R6				36	360				360	361								
3.9	3R9				39	390				390	391								




Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

2225C/P (0.220" x 0.250")


≠ Termination Types and Codes




Chip Termination:
Codes: W, L, P




Microstrip Termination:
Codes: MS, MN




Axial Ribbon Termination:
Code: AR, AN



Radial Wire Termination:
Codes: RW, RN



Radial Ribbon Termination:
Code: RR, FN



Axial Wire Termination:
Codes: AW, BN

Termination Code	Magnetic Termination	Termination Code	Non-Magnetic Termination
W	100% Sn Solder over Nickel Plating	P	100%Sn Solder over Copper Plating
L	90% Sn10%Pb Tin/Lead Solder over Nickel Plating	MN	
MS		AN	
AR		FN	Silver-Plated Copper
RR	Silver-Plated Copper	RN	
RW		BN	
AW			

Note: "Non-Magnetic" means no magnetic materials.



≠ Termination Types For Termination Types images, see previous page

Unit: inch (millimeter)

Magnetic Terminations								
Capacitor Dimensions					Lead Dimensions			
Code	Term.	Length Lc	Width Wc	Thickness Tc	Overlap B	Length LL	Width WL	Thickness TL
W/L	Chip	0.225 -0.010+0.25 (5.72 -0.25+ 0.64)	0.250 ± 0.015 (6.35 ± 0.38)	0.165 (4.19) max	0.020~0.047 (0.50~1.20) max	---	---	---
MS	Microstrip					0.500 (12.70) min	0.240 ±0.005 (6.1 ± 0.13)	0.008 ±0.001 (0.2 ±0.025)
AR	Axial Ribbon							
RR	Radial Ribbon	0.245 ± 0.025 (6.22 ± 0.64)	0.250 ±0.015 (6.35 ± 0.38)	0.150 (3.81) max		0.354 (9.00) min	0.118 ±0.005 (3.0 ±0.13)	0.012 ±0.001 (0.3 ±0.025)
RW	Radio Wire					0.709 (18.00) min	Dia. = 0.031 ±0.004 (0.80 ±0.10)	
AW	Axial Wire					0.906 (23.00) min		
⊗ Non-Magnetic Terminations ⊗								
Capacitor Dimensions					Lead Dimensions			
Code	Term.	Length Lc	Width Wc	Thickness Tc	Overlap B	Length LL	Width WL	Thickness TL
P	Chip	0.225 -0.010+0.25 (5.72 -0.25+ 0.64)	0.250 ± 0.015 (6.35 ± 0.38)	0.165 (4.19) max	0.020~0.047 (0.50~1.20) max			
MN	Microstrip					0.500 (12.70) min	0.240 ±0.005 (6.1 ± 0.13)	0.008 ±0.001 (0.2 ±0.025)
AN	Axial Ribbon							
FN	Radial Ribbon	0.245 ± 0.025 (6.22 ± 0.64)	0.250 ±0.015 (6.35 ± 0.38)	0.150 (3.81) max		0.354 (9.00) min	0.118 ±0.005 (3.0 ±0.13)	0.012 ±0.001 (0.3 ±0.025)
RN	Radial Wire					0.709 (18.00) min	Dia. = 0.031 ±0.004 (0.80 ±0.10)	
BN	Axial Wire					0.906 (23.00) min		

Note: Non-Magnetic means no magnetic materials. All leads are attached with high temperature solder and parts are RoHS Compliant.



⚡ Electrical Specifications

Quality Factor (Q)	Greater than 10,000 at 1 MHz
Insulation Resistance (IR)	Test Voltage: 500V 10 ⁵ Megaohms min. @ +25°C rated WVDC 10 ⁴ Megaohms min. @ +125°C rated WVDC
Rated Voltage	See Rated Voltage Table
Dielectric Withstanding Voltage (WVDC)	250% of Rated Voltage of 5 seconds, Rated Voltage ≤ 500VDC 150% of Voltage for 5 seconds, 500VDC < Rated Voltage ≤ 1250 VDC 120% of Voltage for 5 seconds, Rated Voltage > 1250 VDC
Operating Temperature Range	-55°C to 200°C
Temperature Coefficient (TC)	C: -55°C to 125°C 0±30ppm/°C; >125°C to 200°C 0±60ppm/°C P: -55°C to 200°C +90±20ppm/°C
Capacitance Drift	±0.02% or ±0.02pF, whichever is greater
Piezoelectric Effects	None
Termination Type	See Termination Type Table

Capacitors are designed and manufactured to meet the requirements of MIL-PRF-55681 and MIL-PRF-123.

⚡ Environmental Specifications

	Specification	Test Parameters
Thermal Shock	DWV: The initial Value IR: Shall not be less than 30% of the initial value. Capacitance Change:	MIL-STD-202, Method 107, Condition A. At the maximum rated temperature (-55°C and 200°C) stay 30 minutes, the time of removing shall not be more than 3 minutes. Perform five cycles.
Moisture Resistance	No more than 0.5% or 0.5pF, whichever is greater.	MIL-STD-202, Method 106
Humidity (Steady State)	DWV: The initial Value IR: The initial value. Capacitance Change: No more than 0.3% or 0.3pF, whichever is greater.	MIL-STD-202, Method 103, Condition A With 1.5Volts DC applied while subjected to an environment of 85°C with 85% relative humidity for 240 hours minimum.
Life	IR: Shall not be less than 30% of the initial value. Capacitance Change: No more than 2.0% or 0.5pF, whichever is greater.	MIL-STD-202, Method 108. For 2000 hours, at 200°C. 200% of Voltage for Capacitors, Rated Voltage ≤ 500VDC; 120% of Voltage for Capacitors, 500VDC < Rated Voltage ≤ 1250VDC; 100% for Voltage for Capacitors, Rated Voltage > 1250VDC
Terminal Strength	Force: 20lbs typical, 10lbs. Minimum. Duration Time: 5 to 10 seconds	MIL-STD-202, Method 211A, Test Condition A. Applied a force and maintained for a period of 5 to 10 seconds. The force shall be in the direction of the axes of the terminations.




Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

2225C/P (0.220" x 0.250")

≠ Series Resonance vs. Capacitance

Series Resonance vs. Capacitance






Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

2225C/P (0.220" x 0.250")


≠ ESR vs. Frequency

2225C/P ESR vs Frequency




≠ Q vs. Capacitance

Q vs Capacitance



≠ Current Rating vs. Capacitance

2225C/P Current Rating vs Capacitance



The current depends on voltage limited:
$$I = \frac{\sqrt{2}}{2} I_{peak} = \frac{\sqrt{2}}{2} \times \frac{V_{rated}}{X_c} = \sqrt{2\pi f C} V_{rated}$$

The current depends on power dissipation limited:
$$I = \sqrt{\frac{P_{dissipation}}{ESR}}$$

Note: If the thermal resistance of mounting surface is 15°C/W, then a power dissipation of 4W will result in the current limited.

We can calculate the current limited.




Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

2225C/P (0.220" x 0.250")

≠ Capacitor Application Program


Passive Plus, Inc.'s brand new **online Capacitor Application Program (C.A.P.)** helps Engineers and Designers select capacitors according to parameters such as cap value and frequency. C.A.P. allows engineers to insert capacitors requirements (Cap value, Frequency), producing Scattering Matrices (S2P) Charts while providing options (Case Size, Terminations, Mounting), and parameters (ESR, Q, Impedance) along with Datasheets. Once engineers have determined their capacitor requirements, C.A.P. also includes online Requests For Quotes (RFQs) and/or sample requests.



≠ Custom Assemblies

Passive Plus offers Capacitor Assemblies for high power requirements. Typical assemblies are configured in series and/or parallel combinations, producing higher voltage/current handling capabilities, extended capacitance range and tighter tolerances.

To get started, simply send us either a mechanical drawing or circuit conditions and we can recommend a solution. All components are 100% up-screened for Partial Discharge and Sonoscanned. All assemblies include a 100hr Military burn in.




≠ Recommended Land Pattern Dimensions

When mounting the capacitor to substrate, it's important to carefully consider that the amount of solder (size of fillet) used has a direct effect upon the capacitor once it's mounted.

- 1) The greater the amount of solder, the greater the stress to the elements. This may cause the substrate to break or crack.
- 2) In the situation where two or more devices are mounted onto a common land, be sure to separate the device into exclusive pads by using soldering resist.


≠ Horizontal Mounting (mm)

A	B	C
3.9	2.5	7.0




≠ Vertical Mounting (mm)

A	B	C
3.9	2.5	4.0



≠ Tape & Reel Specifications (mm)

Horizontal Orientation



Case Size	Orientation	Measurement Unit	W	P0	P1	T	F	Minimum Qty per Reel	Std Qty per Reel	Tape Material
2225CP	H	in.	0.630	0.157	0.472	0.012	0.295	500	500	Plastic
		mm	16.00	4.00	12.00	0.30	7.50			
	V	in.	0.630	0.157	0.315	0.020	0.295	500	500	Plastic
		mm	16.00	4.00	8.00	0.50	7.50			

A₀ B₀ K₀

- Determined by component size. Typical clearance between the cavity and the component is:
.05 (.002) min to .50 (.020) max for 8mm tape and .50 (.002) min to .65 (.026) max for 12mm tape.
- The component cannot rotate more than 20° within the determined cavity.



Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

3838C/P (0.380" x 0.380")

≠ Product Features

- High Q
- High RF Current/Voltage
- Ultra Stable Performance
- Capacitance Range:
0.5pF to 5100pF
- Working Voltage: 3600V
- Extended Voltage: 7200V

≠ Product Applications

Typical Functional Applications:

- Tuning • Bypass • Coupling
- D.C. Blocking • Impedance Matching


Typical Circuit Applications

- HF/ RF Power Amplifiers • Antenna Tuning • Plasma Chambers • Medical Equipment • Transmitters



Marking shown for illustration purposes only.
Actual marking may differ.

≠ Part Numbering



≠ Capacitance Tolerance Codes

Code	A	B	C	D	F	G	J	K
Tol.	±0.05pF	±0.1pF	±0.25pF	±0.5pF	±1%	±2%	±5%	±10%

≠ Voltage Codes

Voltage	Code
500V	501
1000V	102
2500V	252
3600V	362
7200V	722




Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

3838C/P (0.380" x 0.380")


≠ 3838C/P Capacitance Values

Special capacitances, tolerances and WVDC are available. Please contact PPI.




Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC
			Std.	Ext.				Std.	Ext.				Std.	Ext.				
0.5	OR5	B,C, D	3600V	7200V	4.7	4R7	B,C, D	3600V	7200V	51	510	F,G, J,K	3600V	7200V	560	561	F,G, J,K	2500V
0.6	OR6				5.1	5R1				56	560				620	621		
0.7	OR7				5.6	5R6				62	620				680	681		
0.8	OR8				6.2	6R2				68	680				750	751		
0.9	OR9				6.8	6R8				75	750				820	821	F,G, J,K	1000V
1.0	1R0				7.5	7R5				82	820				910	911		
1.1	1R1				8.2	8R2				91	910				1000	102		
1.2	1R2				9.1	9R1				100	101				1100	112		
1.3	1R3				10	100				110	111				1200	122		
1.4	1R4				11	110				120	121				1500	152		
1.5	1R5	12	120	130	131	1800	182	F,G, J,K	500V									
1.6	1R6	13	130	150	151	2200	222											
1.7	1R7	15	150	160	161	2400	242											
1.8	1R8	16	160	180	181	2700	272											
1.9	1R9	18	180	200	201	3000	302											
2.0	2R0	20	200	220	221	3300	332											
2.1	2R1	22	220	240	241	3600	362											
2.2	2R2	24	240	270	271	3900	392											
2.4	2R4	27	270	300	301	4300	432											
2.7	2R7	30	300	330	331	4700	472											
3.0	3R0	33	330	360	361	5100	512											
3.3	3R3	36	360	390	391													
3.6	3R6	39	390	430	431	F,G, J,K	2500V	N/A										
3.9	3R9	43	430	470	471													
4.3	4R3	47	470	510	511													


≠ Termination Types and Codes




Chip Termination:
Codes: **W, L, P**




Microstrip Termination:
Codes: **MS, MN**




Axial Ribbon Termination:
Code: **AR, AN**



Radial Wire Termination:
Codes: **RW, RN**



Radial Ribbon Termination:
Code: **RR, FN**



Axial Wire Termination:
Codes: **AW, BN**

Termination Code	Magnetic Termination
W 	100% Sn Solder over Nickel Plating
L	90% Sn10%Pb Tin/Lead Solder over Nickel Plating
MS 	
AR 	
RR 	Silver-Plated Copper
RW 	
AW 	

Termination Code	Non-Magnetic Terminations
P 	100%Sn Solder over Copper Plating
MN 	
AN 	
FN 	Silver-Plated Copper
RN 	
BN 	

Note: "Non-Magnetic" means no magnetic materials.



Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

3838C/P (0.380" x 0.380")

≠ Termination Types For Termination Types images, see previous page

Unit: inch (millimeter)

Magnetic Terminations								
Code	Term.	Capacitor Dimensions				Lead Dimensions		
		Length Lc	Width Wc	Thickness Tc	Overlap B	Length LL	Width WL	Thickness TL
W	Chip	0.380 -0.010+0.015 (9.65 - 0.25+0.38)	0.380 ±0.010 (9.65±0.25)	0.170 (4.32) max	0.024~0.059 (0.60~1.50)			
MS	Microstrip					0.728 (18.50) min	0.350 ± 0.020 (8.89±0.50)	0.008±0.001 (0.20±0.025)
AR	Axial Ribbon	0.380	0.380				0.315±0.010 (8.00±0.25)	
RR	Radial Ribbon	-0.010.+0.015	±0.010	0.177 (4.50) max		0.354 (9.00) min	0.118 ± 0.010 (3.0 ± 0.25)	0.012 ± 0.001 (0.3 ± 0.025)
RW	Radial Wire	(9.65 -0.25+0.38)	(9.65 ±0.25)			0.709 (18.00) min	Dia.: 0.031±0.004 (0.80 ± 0.10)	
AW	Axial Wire					0.906 (23.00) min		

⊗ Non-Magnetic Termination: ⊗								
Code	Term.	Capacitor Dimensions				Lead Dimensions		
		Length Lc	Width Wc	Thickness Tc	Overlap B	Length LL	Width WL	Thickness TL
P	Chip	0.380 -0.010+0.015 (9.65 - 0.25+0.38)	0.380 ±0.010 (9.65±0.25)	0.170 (4.32) max	0.024~0.059 (0.60~1.50)			
MN	Microstrip					0.728 (18.50) min	0.350 ± 0.020 (8.89±0.50)	0.008 ± 0.001 (0.20 ± 0.025)
AN	Axial Ribbon	0.380	0.380				0.315±0.010 (8.00±0.25)	
FN	Radial Ribbon	-0.010+0.015	±0.010	0.177 (4.50) max		0.354 (9.00) min	0.118 ± 0.010 (3.0 ± 0.25)	0.012 ± 0.001 (0.3 ± 0.025)
RN	Radial Wire	(9.65 -0.25+0.38)	(9.65 ±0.25)			0.709 (18.00) min	Dia.: 0.031 ± 0.004 (0.80 ± 0.10)	
BN	Axial Wire					0.906 (23.00) min		

Note: Non-Magnetic means no magnetic materials. All leads are attached with high temperature solder and parts are RoHS Compliant.



⚡ Electrical Specifications

Quality Factor (Q)	Greater than 10,000 at 1 MHz
Insulation Resistance (IR)	Test Voltage: 500V 10 ⁵ Megaohms min. @ +25°C rated WVDC 10 ⁴ Megaohms min. @ +125°C rated WVDC
Rated Voltage	See Rated Voltage Table
Dielectric Withstanding Voltage (WVDC)	250% of Rated Voltage of 5 seconds, Rated Voltage ≤ 500VDC 150% of Voltage for 5 seconds, 500VDC < Rated Voltage ≤ 1250 VDC 120% of Voltage for 5 seconds, Rated Voltage > 1250 VDC
Operating Temperature Range	-55°C to 200°C
Temperature Coefficient (TC)	C: -55°C to 125°C 0±30ppm/°C; >125°C to 200°C 0±60ppm/°C P: -55°C to 200°C +90±20ppm/°C
Capacitance Drift	±0.02% or ±0.02pF, whichever is greater
Piezoelectric Effects	None
Termination Type	See Termination Type Table

⚡ Environmental Specifications

	Specification	Test Parameters
Thermal Shock	DWV: The initial value IR: Shall not be less than 30% of the initial value. Capacitance Change:	MIL-STD-202, Method 107, Condition A. At the maximum rated temperature (-55°C and 200°C) stay 30 minutes, the time of removing shall not be more than 3 minutes. Perform five cycles.
Moisture Resistance	No more than 0.5% or 0.5pF, whichever is greater.	MIL-STD-202, Method 106
Humidity (Steady State)	DWV: The initial value IR: The initial value Capacitance Change: No more than 0.3% or 0.3pF, whichever is greater.	MIL-STD-202, Method 103, Condition A With 1.5Volts DC applied while subjected to an environment of 85°C with 85% relative humidity for 240 hours minimum.
Life	IR: Shall not be less than 30% of the initial value. Capacitance Change: No more than 2.0% or 0.5pF, whichever is greater.	MIL-STD-202, Method 108. For 2000 hours, at 200°C. 200% of Voltage for Capacitors, Rated Voltage ≤ 500VDC; 120% of Voltage for Capacitors, 500VDC < Rated Voltage ≤ 1250VDC; 100% for Voltage for Capacitors, Rated Voltage > 1250VDC
Terminal Strength	Force: 20lbs typical, 10lbs. min. Duration Time: 5 to 10 seconds	MIL-STD-202, Method 211A, Test Condition A. Applied a force and maintained for a period of 5 to 10 seconds. The force shall be in the direction of the axes of the terminations.

Capacitors are designed and manufactured to meet the requirements of MIL-PRF-55681 and MIL-PRF-123.




Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

3838C/P (0.380" x 0.380")

≡ Series Resonance vs. Capacitance

Series Resonance vs. Capacitance






Traditional High Q (>10,000) Low ESR
Multi-Layer Ceramic Capacitors

3838C/P (0.380" x 0.380")


≠ ESR vs. Frequency

ESR vs Frequency




≠ Q vs. Capacitance

Q vs Capacitance



≠ Current Rating vs. Capacitance

3838C/P Current Rating vs Capacitance



The current depends on voltage limited:

$$I = \frac{\sqrt{2}}{2} I_{peak} = \frac{\sqrt{2}}{2} \times \frac{V_{rated}}{X_C} = \sqrt{2\pi f C V_{rated}}$$

The current depends on power dissipation limited:


$$I = \sqrt{\frac{P_{dissipation}}{ESR}}$$

Note: If the thermal resistance of mounting surface is 12°C/W, then a power dissipation of 5W will result in the current limited. We can calculate the current limited.

≠ Custom Assemblies

Passive Plus offers Capacitor Assemblies for high power requirements. Typical assemblies are configured in series and/or parallel combinations, producing higher voltage/current handling capabilities, extended capacitance range and tighter tolerances.

To get started, simply send us either a mechanical drawing or circuit conditions and we can recommend a solution. All components are 100% up-screened for Partial Discharge and Sonoscanned. All assemblies include a 100hr Military burn in.




≠ Recommended Land Pattern Dimensions

When mounting the capacitor to substrate, it's important to carefully consider that the amount of solder (size of fillet) used has a direct effect upon the capacitor once it's mounted.

- 1) The greater the amount of solder, the greater the stress to the elements. This may cause the substrate to break or crack.
- 2) In the situation where two or more devices are mounted onto a common land, be sure to separate the device into exclusive pads by using soldering resist.


≠ Horizontal Mounting (mm)

A	B	C
7.1	3.0	10.2




≠ Vertical Mounting* (mm)

A	B	C
7.1	3.0	5.0



≠ Tape & Reel Specifications (mm)

Horizontal Orientation



Orientation	W	P0	P1	T	F	Qty/Min	Qty/reel	Tape Material
Horizontal	16.00	4.00	12.00	0.30	7.50	50	200	Plastic

A₀ B₀ K₀

- Determined by component size. Typical clearance between the cavity and the component is:
.05 (.002) min to .50 (.020) max for 8mm tape and .50 (.002) min to .65 (.026) max for 12mm tape.
- The component cannot rotate more than 20° within the determined cavity.



UHF/RF High Q Power Transmitter
Capacitors (NP0 TC)
Multi-Layer Ceramic Capacitors


6040C (0.600" x 0.400")

≠ **Product Features**

- High Q
- High RF Current/Voltage
- Ultra Stable Performance
- Capacitance Range:
1.0pF to 6800pF
- Working Voltage: 5000V
- Extended Voltage: 8000V


≠ **Typical Circuit Applications**

- Semiconductor Manufacturing
- High Energy Power Transfers
- Plasma Chambers
- Medical Equipment



Marking shown for illustration purposes only.
Actual marking may differ.

≠ **Part Numbering**



≠ **Capacitance Tolerance Codes**

Code	B	C	D	F	G	J	K
Tol.	±0.1pF	±0.25pF	±0.5pF	±1%	±2%	±5%	±10%

≠ **Voltage Codes**

Voltage	Code
1000V	102
2000V	202
3000V	302
5000V	502
8000V	802



UHF/RF High Q Power Transmitter
Capacitors (NP0 TC)
Multi-Layer Ceramic Capacitors

6040C (0.600" x 0.400")

≠ 6040C Capacitance Values


For special capacitances, tolerances and WVDC, please contact PPI.




Marking shown for illustration purposes only.
Actual marking may differ.

Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC	
			Std.	Ext.				Std.	Ext.				Std.	Ext.
1.0	1R0				39	390				1500	152			
1.2	1R2				47	470				1800	182	F,G, J,K	2000V	3000V
1.5	1R5				56	560	F,G, J,K	5000V	8000V	2200	222			
1.8	1R8				68	680				2700	272			
2.2	2R2				82	820				3300	332			
2.7	2R7	B,C, D	5000V	8000V	100	101				4700	472	F,G, J,K	1000V	2000V
3.3	3R3				120	121				5100	512			
3.9	3R9				150	151				5600	562			
4.7	4R7				180	181				6800	682			
5.6	5R6				220	221								
6.8	6R8				270	271	F,G, J,K	3000V	5000V					
8.2	8R2				330	331								
10	100				390	391								
12	120				470	471								
15	150				560	561								
18	180	F,G, J,K	5000V	8000V	680	681								
22	220				820	821								
27	270				1000	102	F,G, J,K	2000V	3000V					
33	330				1200	122								


≠ Termination Types and Codes




Chip Termination:
Codes: **W, L, P**




Microstrip Termination:
Codes: **MS, MN**



Axial Ribbon Termination:
Code: **AR, AN**



Radial Wire Termination:
Codes: **RW, RN**



Axial Wire Termination:
Codes: **AW, BN**

Termination Code	Magnetic Termination
W 	100% Sn Solder over Nickel Plating
L	90% Sn10%Pb Tin/Lead Solder over Nickel Plating
MS 	Silver-Plated Copper
AR 	
RW 	
AW 	

Termination Code	Non-Magnetic Terminations
P 	100% Sn Solder over Copper Plating
MN 	Silver-Plated Copper
AN 	
RN 	
BN 	

Note: "Non-Magnetic" means no magnetic materials.



≠ Terminations For Termination Types images, see previous page

Unit: inch (millimeter)

Magnetic Terminations								
		Capacitor Dimensions				Lead Dimensions		
Code	Term.	Length Lc	Width Wc	Thickness Tc	Overlap B	Length LL	Width WL	Thickness TL
W	Chip	0.614 -0.010+0.015 (15.6 -0.25+0.38)	0.433±0.010 (11.0±0.25)	0.154±0.008 (3.90±0.20) max	0.063 (1.60) max	-	-	-
MS	Microstrip					0.787 (20.0) min	0.350 ± 0.010 (8.89±0.25)	0.008±0.001 (0.20± 0.025)
AR	Axial Ribbon	0.614 -0.010+0.015	0.433±0.010 (11.0±0.25)	0.154±0.008 (3.90±0.20) max	-	0.787 (20.00) min	Dia.: 0.030±0.004 (0.80 ± 0.10)	
RW	Radial Wire	(15.6 -0.25+0.38)				0.984 (25.00) min		
AW	Axial Wire							

⊗ Non-Magnetic Terminations ⊗								
		Capacitor Dimensions				Lead Dimensions		
Code	Term.	Length Lc	Width Wc	Thickness Tc	Overlap B	Length LL	Width WL	Thickness TL
P	Chip	0.614 -0.010+0.015 (15.6 -0.25+0.38)	0.433±0.010 (11.0±0.25)	0.154±0.008 (3.90±0.20) max	0.063 (1.60) max	-	-	-
MN	Microstrip					0.787 (20.0) min	0.350 ± 0.010 (8.89±0.25)	0.008 ±0.001 (0.20 ± 0.025)
AN	Axial Ribbon	0.614 -0.010+0.015	0.433±0.010 (11.0±0.25)	0.154±0.008 (3.90±0.20) max	-	0.787 (20.00) min	Dia.: 0.031 ±0 .004 (0.80 ± 0.10)	
RN	Radial Wire	(15.6 -0.25+0.38)				0.984 (25.00) min		
BN	Axial Wire							

Note: Non-Magnetic means no magnetic materials. All leads are attached with high temperature solder and parts are RoHS Compliant.



⚡ Electrical Specifications


Quality Factor (Q)	No less than 1000pF, Q value more than 2000, Test Frequency 1MHz; More than 1000pF, Q value more than 2000, Test Frequency 1MHz
Insulation Resistance (IR)	Test Voltage: 500V 10 ⁵ Megaohms min. @ +25°C rated WVDC 10 ⁴ Megaohms min. @ +125°C rated WVDC
Rated Voltage	See Rated Voltage Table
Dielectric Withstanding Voltage (WVDC)	250% of Voltage of 5 seconds, Rated Voltage ≤ 500VDC 150% of Voltage for 5 seconds, 500VDC < Rated Voltage ≤ 1250 VDC 120% of Voltage for 5 seconds, Rated Voltage > 1250 VDC
Operating Temperature Range	-55°C to 175°C
Temperature Coefficient (TC)	-55°C to 125°C 0±30ppm/°C >125°C to 175°C 0±60ppm/°C
Capacitance Drift	±0.02% or ±0.02pF, whichever is greater
Piezoelectric Effects	None
Termination Type	See Termination Type Table

⚡ Environmental Specifications


	Specification	Test Parameters
Thermal Shock	DWV: The initial value IR: Shall not be less than 30% of the initial value. Capacitance Change:	MIL-STD-202, Method 107, Condition A. At the maximum rated temperature (-55°C and 175°C) stay 30 minutes, the time of removing shall not be more than 3 minutes. Perform five cycles.
Moisture Resistance	No more than 0.5% or 0.5pF, whichever is greater.	MIL-STD-202, Method 106
Humidity (Steady State)	DWV: The initial value IR: The initial value Capacitance Change: No more than 0.3% or 0.3pF, whichever is greater.	MIL-STD-202, Method 103, Condition A With 1.5Volts DC applied while subjected to an environment of 85°C with 85% relative humidity for 240 hours minimum.
Life	IR: Shall not be less than 30% of the initial value. Capacitance Change: No more than 2.0% or 0.5pF, whichever is greater.	MIL-STD-202, Method 108. For 2000 hours, at 125°C. 200% of Voltage for Capacitors, Rated Voltage ≤ 500VDC; 120% of Voltage for Capacitors, 500VDC < Rated Voltage ≤ 1250VDC; 100% for Voltage for Capacitors, Rated Voltage > 1250VDC
Terminal Strength	Force: 25lbs typical, 20lbs. min. Duration Time: 5 to 10 seconds	MIL-STD-202, Method 211A, Test Condition A. Applied a force and maintained for a period of 5 to 10 seconds. The force shall be in the direction of the axes of the terminations.

Capacitors are designed and manufactured to meet the requirements of MIL-PRF-55681 and MIL-PRF-123.


≠ ESR vs. Capacitance Measured @ 30MHz




≠ Self Resonant Frequency vs. Capacitance




≠ Strip Terminals Rated Current vs. Frequency



≠ Wire Terminals Rated Current vs. Frequency



≠ % Maximum Current vs. Ambient Temperature



≠ Custom Assemblies

Passive Plus offers Capacitor Assemblies for high power requirements. Typical assemblies are configured in series and/or parallel combinations, producing higher voltage/current handling capabilities, extended capacitance range and tighter tolerances.

To get started, simply send us either a mechanical drawing or circuit conditions and we can recommend a solution. All components are 100% up-screened for Partial Discharge and Sonoscanned. All assemblies include a 100hr Military burn in.



⚡ Recommended Land Pattern Dimensions


When mounting the capacitor to substrate, it's important to carefully consider that the amount of solder (size of fillet) used has a direct effect upon the capacitor once it's mounted.

- 1) The greater the amount of solder, the greater the stress to the elements. This may cause the substrate to break or crack.
- 2) In the situation where two or more devices are mounted onto a common land, be sure to separate the device into exclusive pads by using soldering resist.

⚡ Horizontal Mounting

A	B	C
13.00	3.30	11.30

Dimensions: mm





UHF/RF High Q Power Transmitter
Capacitors (NP0 TC)
Multi-Layer Ceramic Capacitors


7676C (0.760" x 0.760")

Product Features

- High Q
- High RF Current/Voltage
- Ultra Stable Performance
- Capacitance Range:
1.0pF to 20000pF
- Working Voltage: 5000V
- Extended Voltage: 8000V


Typical Circuit Applications

- Semiconductor Manufacturing
- High Energy Power Transfers
- Plasma Chambers
- Medical Equipment



Marking shown for illustration purposes only.
Actual marking may differ.

Part Numbering



Capacitance Tolerance Codes

Code	B	C	D	F	G	J	K
Tol.	±0.1pF	±0.25pF	±0.5pF	±1%	±2%	±5%	±10%

Voltage Codes

Voltage	Code
1000V	102
2000V	202
3000V	302
5000V	502
8000V	802



UHF/RF High Q Power Transmitter
Capacitors (NP0 TC)
Multi-Layer Ceramic Capacitors

7676C (0.760" x 0.760")

≠ 7676C Capacitance Values


Special capacitances, tolerances and WVDC are available. Please contact PPI.




Marking shown for illustration purposes only.
Actual marking may differ.

Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC		Cap. pF	Cap Code	Tol.	Rated WVDC	
			Std.	Ext.				Std.	Ext.				Std.	Ext.
1.0	1R0	B,C, D	5000V	8000V	33	330	F,G, J,K	5000V	8000V	1000	102	G,J, K	3000V	5000V
1.2	1R2				39	390				1200	122			
1.5	1R5				47	470				1500	152			
1.8	1R8				56	560				1800	182			
2.2	2R2				68	680				2200	222			
2.7	2R7				82	820				2700	272			
3.3	3R3				100	101				3300	332			
3.9	3R9				120	121				4700	472			
4.7	4R7				150	151				5100	512			
5.6	5R6				180	181				5600	562			
6.8	6R8	220	221	6800	682									
8.2	8R2	270	271	7500	752									
10	100	F,G, J,K	5000V	8000V	300	301	F,G, J,K	3000V	5000V	8200	822	G,J, K	1000V	2000V
12	120				390	391				10000	103			
15	150				470	471				12000	123			
18	180				560	561				15000	153			
22	220				680	681				18000	183			
27	270				820	821				20000	203			


≠ Termination Types and Codes




Chip Termination:
Codes: **W, L, P**




Microstrip Termination:
Codes: **MS, MN**



Axial Ribbon Termination:
Code: **AR, AN**



Radial Wire Termination:
Codes: **RW, RN**



Axial Wire Termination:
Codes: **AW, BN**

Termination Code	Magnetic Termination
W 	100% Sn Solder over Nickel Plating
L	90% Sn10%Pb Tin/Lead Solder over Nickel Plating
MS 	
AR 	Silver-Plated Copper
RW 	
AW 	

Termination Code	Non-Magnetic Terminations
P 	100% Sn Solder over Copper Plating
MN 	
AN 	Silver-Plated Copper
RN 	
BN 	

Note: "Non-Magnetic" means no magnetic materials.



≠ Termination Types For Termination Types images, see previous page

Unit: inch (millimeter)

Magnetic Terminations								
		Capacitor Dimensions				Lead Dimensions		
Code	Term.	Length Lc	Width Wc	Thickness Tc	Overlap B	Length LL	Width WL	Thickness TL
W	Chip					-	-	-
MS	Microstrip	0.760	0.760±0.010	0.154±0.008	0.063	0.787	0.591 ± 0.010	0.008±0.001
AR	Axial Ribbon	-0.010+0.015 (19.3 -0.25+0.38)	(19.3±0.25)	(3.90±0.20) max	(1.60) max	(20.0) min	(15.0±0.25)	(0.20± 0.025)
RW	Radial Wire					0.787 (20.00) min	Dia.: 0.030±0.004 (0.80 ± 0.10)	
AW	Axial Wire					1.181 (30.00) min		

⊗ Non-Magnetic Terminations ⊗								
		Capacitor Dimensions				Lead Dimensions		
Code	Term.	Length Lc	Width Wc	Thickness Tc	Overlap B	Length LL	Width WL	Thickness TL
P	Chip					-	-	-
MN	Microstrip	0.760	0.760±0.010	0.154±0.008	0.063	0.787	0.591 ± 0.010	0.008 ± 0.001
AN	Axial Ribbon	-0.010+0.015 (19.3 -0.25+0.38)	(19.3±0.25)	(3.90±0.20) max	(1.60) max	(20.0) min	(15.0±0.25)	(0.20 ± 0.025)
RN	Radial Wire					0.787 (20.00) min	Dia.: 0.031 ± 0.004 (0.80 ± 0.10)	
BN	Axial Wire					1.181 (30.00) min		

Note: Non-Magnetic means no magnetic materials. All leads are attached with high temperature solder and parts are RoHS Compliant.



≠ Electrical Specifications


Quality Factor (Q)	No less than 1000pF, Q value more than 2000, Test Frequency 1MHz; More than 1000pF, Q value more than 2000, Test Frequency 1MHz
Insulation Resistance (IR)	Test Voltage: 500V 10 ⁵ Megaohms min. @ +25°C rated WVDC 10 ⁴ Megaohms min. @ +125°C rated WVDC
Rated Voltage	See Rated Voltage Table
Dielectric Withstanding Voltage (WVDC)	250% of Voltage of 5 seconds, Rated Voltage ≤ 500VDC 150% of Voltage for 5 seconds, 500VDC < Rated Voltage ≤ 1250 VDC 120% of Voltage for 5 seconds, Rated Voltage > 1250 VDC
Operating Temperature Range	-55°C to 175°C
Temperature Coefficient (TC)	-55°C to 125°C 0±30ppm/°C >125°C to 175°C 0±60ppm/°C
Capacitance Drift	±0.02% or ±0.02pF, whichever is greater
Piezoelectric Effects	None
Termination Type	See Termination Type Table

≠ Environmental Specifications


	Specification	Test Parameters
Thermal Shock	DWV: The initial value IR: Shall not be less than 30% of the initial value. Capacitance Change:	MIL-STD-202, Method 107, Condition A. At the maximum rated temperature (-55°C and 175°C) stay 30 minutes, the time of removing shall not be more than 3 minutes. Perform five cycles.
Moisture Resistance	No more than 0.5% or 0.5pF, whichever is greater.	MIL-STD-202, Method 106
Humidity (Steady State)	DWV: The initial value IR: The initial value Capacitance Change: No more than 0.3% or 0.3pF, whichever is greater.	MIL-STD-202, Method 103, Condition A With 1.5Volts DC applied while subjected to an environment of 85°C with 85% relative humidity for 240 hours minimum.
Life	IR: Shall not be less than 30% of the initial value. Capacitance Change: No more than 2.0% or 0.5pF, whichever is greater.	MIL-STD-202, Method 108. For 2000 hours, at 125°C. 200% of Voltage for Capacitors, Rated Voltage ≤ 500VDC; 120% of Voltage for Capacitors, 500VDC < Rated Voltage ≤ 1250VDC; 100% for Voltage for Capacitors, Rated Voltage > 1250VDC
Terminal Strength	Force: 30lbs. min. Duration Time: 5 to 10 seconds	MIL-STD-202, Method 211A, Test Condition A. Applied a force and maintained for a period of 5 to 10 seconds. The force shall be in the direction of the axes of the terminations.

Capacitors are designed and manufactured to meet the requirements of MIL-PRF-55681 and MIL-PRF-123.


≠ ESR vs. Capacitance Measured @ 30MHz




≠ Self Resonant Frequency vs. Capacitance




≠ Strip Terminals Rated Current vs. Frequency



≠ Wire Terminals Rated Current vs. Frequency



≠ % Maximum Current vs. Ambient Temperature



≠ Custom Assemblies

Passive Plus offers Capacitor Assemblies for high power requirements. Typical assemblies are configured in series and/or parallel combinations, producing higher voltage/current handling capabilities, extended capacitance range and tighter tolerances.

To get started, simply send us either a mechanical drawing or circuit conditions and we can recommend a solution. All components are 100% up-screened for Partial Discharge and Sonoscanned. All assemblies include a 100hr Military burn in.



⚡ Recommended Land Pattern Dimensions


When mounting the capacitor to substrate, it's important to carefully consider that the amount of solder (size of fillet) used has a direct effect upon the capacitor once it's mounted.

- 1) The greater the amount of solder, the greater the stress to the elements. This may cause the substrate to break or crack.
- 2) In the situation where two or more devices are mounted onto a common land, be sure to separate the device into exclusive pads by using soldering resist.

⚡ Horizontal Mounting




A	B	C
16.00	3.30	19.60

Dimensions: mm





UHF/RF High Q Power Transmitter
Capacitors (NP0 TC)
Multi-Layer Ceramic Capacitors
Custom Capacitor Assemblies



*Marking shown for illustration purposes only.
Actual marking may differ.*

Please contact PPI (sales@passiveplus.com) to discuss custom assembly options.



UHF/RF High Q Power Transmitter
Capacitors (NP0 TC)
Multi-Layer Ceramic Capacitors

Custom Capacitor Assemblies

≠ Product Features

High Operating Voltage, High Operating Current, Extended Capacitance, Tighter Tolerances, High Reliability, High Q, Ultra-low ESR, Non-Magnetic


≠ Typical Applications Field

High Power RF, Medical Electronics, Broadcast, Semiconductor Manufacturing, High Magnetic Environments, Inductive Heating



Marking shown for illustration purposes only. Actual marking may differ.

≠ Part Numbering



Capacitor Size:

11P = 1111; 22P = 2225; 38P = 3838; 60P = 6040; 76P = 7676

Capacitance: For capacitor values requiring 3 significant digits,

e.g. 1222.5pF = 1222R5

e.g. P6S22P101F252X

Silver bracket assembly with six 2225C pieces in parallel, Capacitance is 100pF, Capacitance tolerance is $\pm 1\%$, WVDC is 2500 V and Laser marking.

e.g. S2S25C1222R5G203X

Silver bracket assembly with two 2225C pieces in series, Capacitance is 1222.5pF,

Capacitance tolerance is $\pm 2\%$, WVDC is 20,000V and Laser marking.

≠ Capacitance and Voltage

By Buyer's requirements using existing drawings, mechanical sketches, or we can help with capable modeling of assemblies thermal rise predictions.



UHF/RF High Q Power Transmitter
Capacitors (NP0 TC)
Multi-Layer Ceramic Capacitors


Custom Capacitor Assemblies

≠ Typical Assembly Configurations

≠ Parallel Assemblies

unit:inch (millimeter)

	1111C/P	22225C/P	3838C/P	6040C	7676C
Lead Material	Silver plated Copper or Silver				
Lead Thickness	.004 or .010 (0.1 or 0.25)			.010 or .020 (0.25 or 0.51)	
Lead Length (max.)	.50 (12.7)	.75 (19.8)		2.0 (50.8)	
Capacitor Spacer (typ.)	.050 or .078 (1.3 or 2)			.090 (2.3)	.050 or .157 (1.3 or 4)
Mounting Configuration	Horizontal / Vertical				



3838 Series/Parallel Combination




Marking shown for illustration purposes only. Actual marking may differ.

≠ Series Assemblies

unit:inch (millimeter)

	22225C/P	3838C/P	6040C	7676C
Lead Type	L Bracket			
Lead Material	Silver plated Copper or Silver			
Lead Thickness	.010 (0.25)		.010 or .020 (0.25 or 0.51)	
Lead Length (max.)	.75 (19.8)	1.0 (25.4)		
Capacitor Spacer (typ.)	.050 or .157 (1.3 or 4)			
Mounting Configuration	Horizontal			

- Epoxy Molding Available



Marking shown for illustration purposes only. Actual marking may differ.

Other Assemblies: By Buyer's requirement. Contact PPI.



Non-Magnetic

Custom & Engineering Design Kits

PPI
Passive Plus Inc.
RF & Microwave Components

DKD0505C05

0505C Series 0.1 — 2.0pF
Size: 0.055" x 0.055"
TC = NP0 WVDC = 150V
NON-MAGNETIC

Hi-Q Low ESR Capacitor Design Kit

PPI
Passive Plus Inc.
RF & Microwave Components

DKD1111C05

1111C Series 1.0 — 10pF
Size: 0.110" x 0.110"
TC = NP0 WVDC = 500V
NON-MAGNETIC

Hi-Q Low ESR Capacitor Design Kit

PPI
Passive Plus Inc.
RF & Microwave Components

DKD0505P05

0505P Series 0.1 — 2.0pF
Size: 0.055" x 0.055"
TC = P90 WVDC = 150V
NON-MAGNETIC

Hi-Q Low ESR Capacitor Design Kit

www.passiveplus.com

PPI
Passive Plus Inc.
RF & Microwave Components

DKD1111P05

1111P Series 1.0 — 10pF
Size: 0.110" x 0.110"
TC = P90 WVDC = 500V
NON-MAGNETIC

Hi-Q Low ESR Capacitor Design Kit

www.passiveplus.com



0505 & 1111 case size kits
are also available in
Magnetic Terminations

According to the customer's demand, PPI can provide many kinds of tool kits for engineers to design and debug the circuit. All of our products satisfy the requirement of RoHS instruction.

PPI also offers kits for Non-Magnetic MRI applications. Engineering design kits are also available in multiple sizes as well. All kits are RoHS Compliant.

Standard Values updated in 2022.



Kit Number	Value Range	Values
DKD0505C05 DKD0505P05	0.1 - 2.0pF	0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0, 1.2, 1.5, 1.6, 1.8, 2.0pF
DKD0505C06 DKD0505P06	1 - 10pF	1.0, 1.2, 1.5, 1.8, 2.0, 2.2, 2.4, 2.7, 3.0, 3.3, 3.9, 4.7, 5.6, 6.8, 8.2, 10pF
DKD0505C07 DKD0505P07	10 - 100pF	10, 12, 15, 18, 20, 22, 24, 27, 30, 33, 39, 47, 56, 68, 82, 100pF
DKD0505C08	100 - 1000pF	100, 120, 150, 180, 200, 220, 240, 270, 300, 330, 390, 470, 560, 680, 820, 1000pF
DKD1111C05 DKD1111P05	1.0 - 10pF	1.0, 1.2, 1.5, 1.8, 2.0, 2.2, 2.4, 2.7, 3.0, 3.3, 3.9, 4.7, 5.6, 6.8, 8.2, 10pF
DKD1111C06 DKD1111P06	10 - 100pF	10, 12, 15, 18, 20, 22, 24, 27, 30, 33, 39, 47, 56, 68, 82, 100pF
DKD1111C07 DKD1111P07	100 - 1000pF	100, 120, 150, 180, 200, 220, 240, 270, 300, 330, 390, 470, 560, 680, 820, 1000pF
DKD1111C08 DKD1111P08	1000 - 10000pF	1000, 1100, 1200, 1500, 1800, 2000, 2200, 2700, 3000, 3300, 3900, 4700, 5100, 5600, 10000pF

Custom Kits

According to the customer's demand, PPI can provide many kinds of tool kits for engineers to design and debug the circuit. All our products satisfy the requirement of RoHS instruction.

Passive Plus will develop a custom kit using the engineer's specific requirements for the engineer's projects (case size, temperature coefficient, value range, tolerances, voltages, and quantities per value). Once these requirements are determined, PPI will then provide customer with a price. Please contact PPI directly to start this process.

All kits are RoHS Compliant.






Custom & Engineering Design Kits

Custom Kits



≠ Non Magnetic Capacitor Tape & Reel Specifications

Case Size	Orientation	Measurement Unit	W	P0	P1	T	F	Minimum Qty per Reel	Std Qty per Reel	Tape Material
0505CP	H	in.	0.315	0.157	0.157	0.009	0.138	500	3000	Plastic
		mm	8.00	4.00	4.00	0.22	3.50			
	V	in.	0.472	0.157	0.157	0.012	0.217	500	2000	
		mm	12.00	4.00	4.00	0.30	5.50			
1111CP	H	in.	0.315	0.157	0.157	0.009	0.138	500	2000	
		mm	8.00	4.00	4.00	0.22	3.50			
	V	in.	0.315	0.157	0.157	0.009	0.138	500	1500	
		mm	8.00	4.00	4.00	0.22	3.50			
	V	in.	0.472	0.157	0.157	0.016	0.217	500	1500	
		mm	12.00	4.00	4.00	0.40	5.50			
2225CP	H	in.	0.630	0.157	0.472	0.012	0.295	500	500	Plastic
		mm	16.00	4.00	12.00	0.30	7.50			
	V	in.	0.630	0.157	0.315	0.020	0.295	500	500	
mm	16.00	4.00	8.00	0.50	7.50					
3838CP	H	in.	0.630	0.157	0.630	0.012	0.295	50	200	
		mm	16.00	4.00	16.00	0.30	7.50			




$A_0B_0K_0$

- Determined by component size. Typical clearance between the cavity and the component is:
.50 (.002) min to .65 (.026) max for 12mm tape.
- The component cannot rotate more than 20° within the determined cavity.



Non-Magnetic Trimmer Capacitors





Variable Capacitors PTFE Trimmers

Part Attributes

- High Voltage
- Medium Size
- Wide Capacitance Range
- Lower Q

Product Applications

- L – C Filters
- Radio Transmitters & Receivers
- Quartz Oscillators Insulation Resistance
- Coils for NMR – Systems
- Impedance Matching



Product Specifications

• Capacitance Range	2.0pF – 100pF
• Q-Factor	2000 @ 100 MHz
• DC Working Voltage	Up to 7.5kV
• DC Withstanding Voltage	Up to 15kV
• Operating Temperature Range	-65°C to +125°C
• TCC (ppm/°C)	0 ± 50 to 65 ± 30 (model dependent)
• Insulation Resistance	>10 Mohm @ 500VDC
• Vibration	60g, 10-2000Hz
• Shock	100g, 6msec.
• Resolution	High Resolution
• Non-Magnetic	For MRI/NMR
• Custom Designs Available	
• PPI SERIES	PPI-63





Variable Capacitors Air Plate Trimmers

Part Attributes





- Wide Capacitance Range
- Highest Q
- Higher Voltage
- Large Size
- Open Construction

Product Applications

- L – C Filters
- Radio Transmitters & Receivers
- Quartz Oscillators Insulation Resistance
- Coils for NMR – Systems
- Low Noise Amplifiers

Product Specifications

• Capacitance Range	1pF – 146pF (select models up to 200pF)
• Q-Factor	>1500 @ 200 MHz/800 @ 1MHz
• DC Working Voltage	3.25kV
• DC Withstanding Voltage	6.5kV
• Operating Temperature Range	-65°C to +125°C
• TCC (ppm/°C)	30 ± 20 to 90 ± 40 (model dependent)
• Insulation Resistance	>10 Mohm @ 500VDC
• Vibration	60g, 10-2000Hz
• Shock	100g, 6msec.
• Resolution	180°Resolution
• Non-Magnetic	For MRI/NMR
• Custom Designs Available	
• PPI SERIES	PPI-10





Variable Capacitors Sapphire Trimmers

Part Attributes

- Smallest Size
- Finer Tuning/Multi-Turn
- High Q
- Lower Voltage
- Lower Capacitance Range



Product Applications

- L – C Filters
- Radio Transmitters & Receivers
- Quartz Oscillators Insulation Resistance
- Coils for NMR – Systems
- Low Noise Amplifiers



Product Specifications

• Capacitance Range	1.0pF – 18.5pF
• Q-Factor	>5000 @ 200 MHz
• DC Working Voltage	500V
• DC Withstanding Voltage	1kV
• Operating Temperature Range	-65°C to +125°C
• TCC (ppm/°C)	0 ± 75 to 350 ± 75 (model dependent)
• Insulation Resistance	>10 Mohm @ 500VDC
• Vibration	60g, 10-2000Hz
• Shock	100g, 6msec.
• Resolution	High Resolution
• Non-Magnetic	For MRI/NMR
• Custom Designs Available	
• PPI SERIES	PPI-66





Variable Capacitors Air Tubular Trimmers

Part Attributes

- Finer Tuning/ Multi-Turn
- High Q
- Medium Size
- Lower Voltage
- Medium Capacitance Range


Product Applications

- L – C Filters
- Radio Transmitters & Receivers
- Quartz Oscillators Insulation Resistance
- Coils for NMR – Systems
- Impedance Matching




Product Specifications


• Capacitance Range	0.3pF – 30pF
• Q-Factor	>5000 @ 200 MHz
• DC Working Voltage	1.75kV
• DC Withstanding Voltage	3.5kV
• Operating Temperature Range	-65°C to +125°C
• TCC (ppm/°C)	0 ± 50 to 65 ± 30 (model dependent)
• Insulation Resistance	>10 Mohm @ 500VDC
• Vibration	60g, 10-2000Hz
• Shock	100g, 6msec.
• Resolution	High Resolution
• Non-Magnetic	For MRI/NMR
• Custom Designs Available	
• PPI SERIES	PPI-60



Q-Factor vs. Frequency



Capacitance vs. Self-Resonant Frequency





Product Features

- Four Dielectrics:
 - Standard PTFE
 - Polypropylene
 - Polyimide
 - Polycarbonate
 - Four Different Sizes:
 - 5mm, 7.5mm, 9.5mm, 16mm
 - SMD and lead-through-hole mounting
 - Top, bottom and Side Mount models
 - Wide capacitance ranges
 - Low cost
 - Linear capacitance change vs. rotation
- $Q = 200 @ 1 \text{ MHz}$
 - $\text{PPM}/^\circ\text{C}: +150 \pm 250$
 - Compact size



Product Applications

Typical Applications:

- Antennas • Transmitters
- RF Equipment • Instruments

Modifications & Variations:

- Special capacitance ranges • Special terminal sizes & shapes •
- Extended Adjust shafts • High temperature versions for PTFE • Silver and/or Gold Plating

For requests for options such as special adjustments, pin configurations, dielectrics, etc., please contact PPI directly.



Production Qualification

FilmTrim Capacitors are in accordance with DIN IEC 418-1 and 4-former DIN 44261 part 3.

Testing methods for manufacturing quality are in accordance with MIL-STD-105D and IEC410 (former DIN44260).

Solderability or heat resistance for the FilmTrim Capacitors comply with DIN IEC 68-2-20 part 2, Test Ta and Tb.

Each FilmTrim Capacitor is tested for minimum and maximum capacitance value and is also subjected to full test voltage.






Product Features

Series	Size (mm)	Heights (mm)		Dielectric	Qmin	Capacitance Range		Voltage Rating (VDC)	Test Voltage (VDC)
		From	To			Min	Max		
XL	5.0	5.0	6.0	PTFE	1500	0.9pF	18pF	150	300
ZL	5.0	5.0	6.3	Polyimide	300	1.0pF	32pF	150	300
XA	7.5	10.2	11.4	PTFE	1500	1.3pF	45pF	200	300
XB	7.5	10.2	11.4	PTFE	1500	1.3pF	45pF	200	300
XE	7.5	10.2	11.4	PTFE High Temp	1500	1.3pF	45pF	200	300
XE NM	7.5	10.2	11.4	PTFE High Temp	1500	1.3pF	45pF	200	300
XR	7.5	10.2	11.4	PTFE High Temp	1500	1.3pF	45pF	200	300
YA	7.5	10.2	10.2	Polypropylene	1000	1.3pF	36pF	200	300
YB	7.5	10.2	10.2	Polypropylene	1000	1.3pF	27pF	200	300
ZA	7.5	10.2	10.2	Polycarbonate	200	2.5pF	40pF	200	300
ZB	7.5	10.2	10.2	Polycarbonate	200	2.5pF	40pF	200	300
XC	9.5	10.2	12.0	PTFE	1500	2.0pF	150pF	200	300
XD	9.5	10.2	12.0	PTFE	1500	2.0pF	150pF	200	300
XF	9.5	10.2	12.4	PTFE High Temp	1500	2.2pF	90pF	200	300
XF NM	9.5	10.2	12.4	PTFE High Temp	1500	2.2pF	90pF	200	300
XT	9.5	10.2	12.4	PTFE High Temp	1500	2.2pF	90pF	200	300
YC	9.5	10.2	10.2	Polypropylene	1000	2.0pF	60pF	200	300
YD	9.5	10.2	10.2	Polypropylene	1000	2.0pF	60pF	200	300
ZC	9.5	10.2	12.0	Polycarbonate	500	7.0pF	180pF	200	300
ZD	9.5	10.2	12.0	Polycarbonate	500	7.0pF	180pF	200	300
ZN	16.0	13.8	16.8	Polycarbonate #1	200	8.0pF	300pF	150	300
ZN	16.0	16.8	16.8	Polycarbonate #2	100	23pF	600pF	150	300
ZP	16.0	13.8	16.8	Polycarbonate #1	200	8.0pF	300pF	150	300
ZP	16.0	16.8	16.8	Polycarbonate #2	100	23pF	600pF	150	300

≠ **Part Numbering** *See charts below for details*



≠ **Dielectrics**

Dielectrics	
Code	Description
X	PTFE (Polytetrafluoroethylene)
Y	PP (Polypropylene)
Z	PC (Polycarbonate) or PI (Polyimide)

≠ **Style**

Style	
Code	Description
A	7.5mm Top/Bottom Adjust
B	7.5mm Side Adjust
C	9.5mm Top/Bottom Adjust
D	9.5mm Side Adjust
E*	7.5mm Top/Bottom Adjust
F*	9.5mm Top/Bottom Adjust
L	5mm Top Adjust
N	16mm Top Adjust
P	16mm Side Adjust
R*	7.5mm Side Adjust
T*	9.5mm Side Adjust

≠ **Capacitance**

Capacitance Code
1R6 = 1.6pF
400 = 40pF
301 = 300pF


≠ **Special Options**

Special Options (Top Adjust Models)	
Code	Description
00	Standard
02	7.5mm, 2 leads
03	9.5mm, 3 lead special
04	9.5mm, 2 leads

** Extended Temperature range: -40 to +125°C
For other modifications such as high temperature base material or special lead plating, contact PPI.*

Electrical Specifications

Dielectrics	<ul style="list-style-type: none"> High Temperature PTFE Polyimide (PI)
Voltage Rating	150 VDC
Dielectric Withstanding Voltage	300 VDC
Contact Resistance	$\leq 0.010\text{m}\Omega$
Insulation Resistance	$\geq 10.000\text{M}\Omega$
Rotation Torque	$C_{\text{max}} < 20\text{pF}$ 0.10...1.5Ncm $C_{\text{max}} > 20\text{pF}$ 0.15...2.5Ncm



All dimensions are in/mm.

General Specifications

Dielectric	Capacitance (pF)		Q min (1MHz)	TCC (ppm/°C)	Operating Temperature (°C)	H max in/mm	Color Code	Model Number
	min	max						
PTFE High Temp	1.2	4.0	1500	0±350	-40 to +125	0.20/5.0	Brown	PPXL4R000
	1.8	10		0±300		0.23/5.8	Black	PPXL10000
	2.0	15		0±300		0.24/6.0	White	PPXL15000
	2.3	18		0±300		0.24/6.0	Green	PPXL18000
PI	1.2	5.0	150	0±350	-40 to +85	0.20/5.0	Brown	PPZL5R000
	1.4	10		0±350		0.20/5.0	Black	PPZL10000
	2.0	15		0±250		0.23/5.8	White	PPZL15000
	2.7	20		0±250		0.23/5.8	Green	PPZL20000
	3.6	32		0±250		0.25/6.3	None	PPZL32000






Electrical Specifications

Dielectrics

- High Temperature PTFE
- Standard PTFE
- Polypropylene (PP)
- Polycarbonate (PC)

Voltage Rating	200V High Temp PTFE 100V all other Dielectrics
Dielectric Withstanding Voltage	300V High Temp PTFE 200V all other Dielectrics
Contact Resistance	≤ 0.010mΩ
Insulation Resistance	≥10,000MΩ
Rotation Torque	C _{max} <35pF 0.10...1.5Ncm C _{max} >35pF 0.15...2.5Ncm



All dimensions are in/mm.

General Specifications

Dielectric	Capacitance (pF)		Q min (1MHz)	TCC (ppm/°C)	Operating Temperature (°C)	H max in/mm	Color Code	Model Number		
	min	max						Top/Bottom 3 Lead	Top/Bottom 2 Lead	Side Adjust
PTFE	1.6	5.0	1500	0±350	-40 to +85	0.40/10.2	Clear	PPXA5R000	PPXA5R002	PPXB5R000
	2.0	9.0		0±350		0.40/10.2	Yellow	PPXA9R000	PPXA9R002	PPXB9R000
	2.0	18		0±300		0.40/10.2	Green	PPXA18000	PPXA18002	PPXB18000
	3.9	27		0±300		0.40/10.2	Red	PPXA27000	PPXA27002	PPXB27000
	4.5	36		0±300		0.45/11.4	Violet	PPXA36000	PPXA36002	PPXB36000
	5.0	45		0±300		0.45/11.4	Orange	PPXA45000	PPXA45002	PPXB45000
PTFE High Temp	1.5	5.0	1500	0±250	-40 to +125	0.40/10.2	Clear	PPXE5R000	PPXE5R002	PPXR5R000
	1.8	9.0		0±250		0.40/10.2	Yellow	PPXE9R000	PPXE9R002	PPXR9R000
	2.6	18		0±250		0.40/10.2	Green	PPXE18000	PPXE18002	PPXR18000
	3.5	27		0±250		0.40/10.2	Red	PPXE27000	PPXE27002	PPXR27000
	4.5	36		0±250		0.45/11.4	Violet	PPXE36000	PPXE36002	PPXR36000
	5.0	45		0±250		0.45/11.4	Orange	PPXE45000	PPXE45002	PPXR45000
PP	1.6	5.0	1000	0±300	-40 to +70	0.40/10.2	Clear	PPYA5R000	PPYA5R002	PPYB5R000
	2.0	10		0±300		0.40/10.2	Yellow	PPYA10000	PPYA10002	PPYB10000
	2.0	15		0±400		0.40/10.2	Blue	PPYA15000	PPYA15002	PPYB15000
	2.2	22		0±400		0.40/10.2	Green	PPYA22000	PPYA22002	PPYB22000
	2.3	27		0±350		0.40/10.2	Red	PPYA27000	PPYA27002	PPYB27000
	3.0	36		0±350		0.40/10.2	Violet	PPYA36000	PPYA36002	
PC	2.5	30	200	100±300	-40 to +85	0.40/10.2	Red	PPZA30000	PPZA30002	PPZB30000
	4.0	40		100±300		0.40/10.2	Violet	PPZA40000	PPZA40002	PPZB40000


*Gold plated metal parts are standard on PPXE and PPXR models above.





Electrical Specifications

Dielectrics	<ul style="list-style-type: none"> • High Temperature PTFE • Standard PTFE • Polypropylene (PP) • Polycarbonate (PC)
Voltage Rating	200V High Temp PTFE 100V all other Dielectrics
Dielectric Withstanding Voltage	300V High Temp PTFE 200V all other Dielectrics
Contact Resistance	≤ 0.010mΩ
Insulation Resistance	≥10,000MΩ
Rotation Torque	0.15....3.5Ncm



All dimensions are in/mm.


≠ General Specifications

Dielectric	Capacitance (pF)		Q min (1MHz)	TCC (ppm/°C)	Operating Temperature (°C)	H max in/mm	Color Code	Model Number			
	min	max						Top/Bottom 3 Lead	Top/Bottom 3 Lead Special	Top/Bottom 2 Lead	Side Adjust
PTFE	2.0	13		0±400		0.40/10.2	Blue	PPXC13000	PPXC13003	PPXC13004	PPXD13000
	3.0	26		0±350		0.40/10.2	Green	PPXC26000	PPXC26003	PPXC26004	PPXD26000
	3.5	38		0±300		0.40/10.2	Clear	PPXC38000	PPXC38003	PPXC38004	PPXD38000
	6.0	60	1500	0±300	-40 to +85	0.45/11.4	Yellow	PPXC60000	PPXC60003	PPXC60004	PPXD60000
	7.0	75		0±300		0.45/11.4	Red	PPXC75000	PPXC75003	PPXC75004	PPXD75000
	8.0	90		0±300		0.49/12.0	Violet	PPXC90000	PPXC90003	PPXC90004	PPXD90000
	10	150		0±300		0.49/12.0	Orange	PPXC15100	PPXC15103	PPXC15104	
PTFE High Temp	2.5	15		0±250		0.40/10.2	Red	PPXF15000	PPXF15003	PPXF15004	PPXT15000
	3.0	25		0±250		0.40/10.2	Clear	PPXF25000	PPXF25003	PPXF25004	PPXT25000
	4.0	40	1500	0±250	-40 to +125	0.40/10.2	Yellow	PPXF40000	PPXF40003	PPXF40004	PPXT40000
	5.5	60		0±250		0.45/11.4	Blue	PPXF60000	PPXF60003	PPXF60004	PPXT60000
	6.0	75		0±250		0.45/11.4	Violet	PPXF75000	PPXF75003	PPXF75004	PPXT75000
	8.0	90		0±250		0.49/12.4	Orange	PPXF90000	PPXF90003	PPXF90004	PPXT90000
PP	2.0	15		0±400		0.40/10.2	Blue	PPYC15000	PPYC15003	PPYC15004	PPYD15000
	3.0	20	1000	0±400	-40 to +70	0.40/10.2	Green	PPYC20000	PPYC20003	PPYC20004	PPYD20000
	3.5	40		0±350		0.40/10.2	Clear	PPYC40000	PPYC40003	PPYC40004	PPYD40000
	4.5	65		0±350		0.40/10.2	Yellow	PPYC65000	PPYC65003	PPYC65004	PPYD65000
PC	8.0	80		0±200		0.40/10.2	Red	PPZC80000	PPZC80003	PPZC80004	PPZD80000
	9.0	100		0±400		0.45/11.4	Violet	PPZC10100	PPZC10103	PPZC10104	PPZD10100
	9.0	120	200	0±350	-40 to +85	0.45/11.4	Orange	PPZC12100	PPZC12103	PPZC12104	PPZD12100
	10	150		0±350		0.47/12.0	Orange	PPZC15100	PPZC15103	PPZC15104	PPZD15100
	12	180		0±350		0.47/12.0	Orange	PPZC18100	PPZC18103	PPZC18104	PPZD18100




Electrical Specifications

Dielectrics	<ul style="list-style-type: none"> • Polypropylene (PP) • Polycarbonate (PC)
Voltage Rating	150 VDC
Dielectric Withstanding Voltage	300 VDC
Contact Resistance	≤ 0.010mΩ
Insulation Resistance	≥ 10,000MΩ
Rotation Torque	0.15....3.5Ncm



All dimensions are in/mm.



All dimensions are in/mm.

General Specifications

Dielectric	Capacitance (pF)		Q min (1MHz)	TCC (ppm/°C)	Operating Temperature (°C)	H max in/mm	Color Code	Model Number	
	min	max						Top Adjust	Side Adjust
PC	9	200	200	0±300	-40 to +85	0.54/13.8	Orange	PPZN20100	PPZP20100
	18	300	200	0±300				PPZN30100	PPZP30100
PI	25	600	100	0±350	-40 to +85	0.66/16.8	None	PPZN60100	PPZP60100

≠ Specifications Notes

- 1 Parts are 100% tested for capacitance range and dielectric withstanding voltage.
- 2 Capacitance range specified is that which is guaranteed and is measured at 1 MHz at room temperature.
- 3 Q factor is measured at maximum rated capacitance and at room temperature.
- 4 Dielectric strength is measured at maximum rated capacitance and room temperature, with test voltage (as listed for each model) applied for 60 seconds.
- 5 Insulation resistance is measured at maximum rated capacitance and room temperature and at rated voltage, unless otherwise specified.
- 6 Temperature coefficient of capacitance (TCC) is measured at 1 MHz over the operating temperature range, with capacitor set at maximum rated capacitance.
- 7 Axial load during tuning should not exceed 200 grams force. At maximum axial load, capacitance change is no more than 15%.
- 8 Capacitors should not be operated outside of rated capacitance range and working voltage.

≠ Soldering FilmTrim Capacitors

Dip soldering:

260°C ± 10°C for 7 seconds maximum.

Hand Soldering

(for lead-through-hole models):

Tip temperature 350°C ± 10°C for 3 to 4 seconds



≠ Cleaning FilmTrim Capacitors


- 1 Water soluble fluxes and detergents with a water flush after soldering of the boards can be used for all parts.

- 2 Do not immerse FilmTrim models in chlorinated or fluorinated hydrocarbon solvents as this would adversely affect the plastic dielectrics and base materials. Some customers have successfully used X models in scrubbers or sprayers where only bottom of the printed circuit boards is exposed to solvents.

If the process requires immersion in solvents for cleaning boards, the FilmTrim capacitors should be hand soldered to board after the boards have been cleaned.



Thin Film Products







Standard Chip Resistors – PR Series

Product Features

- Wire-bondable Thin Film Resistors
- Operating frequencies from DC to 500 MHz
- Can be used in Non-Magnetic Applications




Product Specifications

Resistance Range	0.5Ω to 35MΩ
Resistance Tolerance	±0.01% to ±20%, value dependent

Part Numbering

Example shown: Standard Resistor, TaN resistive element, alumina substrate, case size 0.020" × 0.020" × 0.010", PdAu bonding pad, bottom side bare, resistance 1000 Ω ± 5%, 150 ppm TCR, regular trim, 100 mW max power handling.



*Flip Chip – wire bondable or solderable

Resistive Materials

Material	Passivation	Sheet Resistivity (Ω/ Sq)	Abs. Tolerance	Ratio Tolerance
Tantalum Nitride (TaN)	Self Passivating Ta ₂ O ₅	5 to 270	From ±0.01%	From ±0.01%
NiChrome (NiCr)	SiO ₂	5 to 250	From ±0.01%	From ±0.01%

The standard dimensional tolerance for length and width is ± 2 mils. The standard dimensional tolerance for thickness is ± 1 mil.

All parts are supplied in waffle packs. Other packaging may be available. Contact PPI for additional packaging options.



Standard Chip Resistors – PR Series

Substrate Materials

Material	Thickness	Surface Finish	Dielectric Constant (@ 1MHz)	Coefficient of Thermal Expansion (x 10 ⁶ /°C)	Thermal Conductivity (W/m*K)	Code
Alumina (Al ₂ O ₃)	0.005" - 0.010"	2μ" - 3μ"	9.9	7 (25°C to < 300°C)	26.9	35
Aluminum Nitride (AlN)	0.005" - 0.010"	6μ" - 8μ"	8.0 - 9.1	4.6 - 5.7 (25°C to < 1000°C)	170	28
Beryllium Oxide (BeO)	0.005" - 0.010"	< 5μ"	6.76	9 (25°C to < 1000°C)	285	25
Silicon (Si) (with 12kÅ SiO ₂)	0.005" - 0.010"	Chemical Polish	N/A (SiO ₂ K=1.38)	2.49 - 4.44 (25°C to < 1000°C)	149 (SiO ₂ 1.38)	22
Quartz (Fused Silica)	0.005" - 0.010"	60/40 Optical Polish	3.826	0.55 (25°C to < 300°C)	1.38	20

Resistance Tolerance Codes

Tolerance	B	D	F	G	H	J	K	L	M	Q	S
Code	± 0.1%	± 0.5%	± 1%	± 2%	± 3%	± 5%	± 10%	± 15%	± 20%	± 0.05%	± 0.01%

Terminations

Metallization		Code
Top Side	Bottom Side	
Pd / Au	—	A
Flip Chip (Ti/Pt/Au)		R
Pd/Au	Ta/Pd/Au	D

Power Handling Codes

Watts	Code	Watts	Code
50 mW	C	750 mW	J
75 mW	D	1.0 W	K
100 mW	E	1.4 W	U
125 mW	I	2.0 W	L
150 mW	F	2.8 W	Y
200 mW	O	3.0 W	N
250 mW	G	4.0 W	P
350 mW	M	5.0 W	Q
400 mW	R	6.0 W	2
500 mW	H	10 W	S

Temperature Coefficient of Resistance

Material	±150 ppm/°C	±100 ppm/°C	±50 ppm/°C	±25 ppm/°C	±10 ppm/°C	±5 ppm/°C
Tantalum Nitride (TaN)	Q	V	W	X	Y	Z
	Standard	Yes	---	---	---	---
NiChrome (NiCr)	---	---	Yes	Standard	Yes	Yes



Standard Chip Resistors – PR Series

Power Handling & Standard Resistance Ranges by Material and Case Size

Case Size mils (inches)	Power Handling					Resistance Range						
	Alumina (C-35)	Silicon (C-22)	AlN (C-28)	BeO (C-25)	Quartz (C-20)	Min (Ω)	Max (Ω) Alumina (C-35)	Max (Ω) Silicon (C-22)	Max (Ω) AlN (C-28)	Max (Ω) BeO (C-25)	Max (Ω) Quartz (C-20)	
12 x 9 (0.012 x 0.009)	50 mW	50 mW	200 mW	400 mW	10 mW	1-3	25K	150K	25K	25K	150K	
14 x 12 (0.014 x 0.012)	100 mW	100 mW	400 mW	750 mW	20 mW	1-3	40K	200K	40K	40K	200K	
20 x 10 (0.020 x 0.010)	100 mW	100 mW	400 mW	750 mW	20 mW	1-3	60K	250K	60K	60K	250K	
15 x 15 (0.015 x 0.015)	100 mW	100 mW	400 mW	750 mW	20 mW	1-2	70K	500K	70K	70K	500K	
20 x 20 (0.020 x 0.020)	250 mW	250 mW	1.0 W	2.0 W	50 mW	1-2	125K	750K	125K	125K	750K	
30 x 20 (0.030 x 0.020)	250 mW	250 mW	1.0 W	2.0 W	50 mW	1-2	200K	1M	200K	200K	1M	
40 x 20 (0.040 x 0.020)	250 mW	250 mW	1.0 W	2.0 W	50 mW	1-2	250K	1.5M	250K	250K	1.5M	
30 x 30 (0.030 x 0.030)	250 mW	250 mW	1.0 W	2.0 W	50 mW	1-2	275K	2M	275K	275K	2M	
35 x 35 (0.035 x 0.035)	250 mW	250 mW	1.0 W	2.0 W	50 mW	1-2	300K	3M	300K	300K	3M	
40 x 40 (0.040 x 0.040)	350 mW	350 mW	1.4 W	2.8 W	70 mW	1-2	500K	5M	500K	500K	5M	
50 x 25 (0.050 x 0.025)	350 mW	350 mW	1.4 W	2.8 W	70 mW	1-2	300K	3M	300K	300K	3M	
60 x 30 (0.060 x 0.030)	500 mW	500 mW	2.0 W	4.0 W	100 mW	1-2	500K	6M	500K	500K	6M	
50 x 50 (0.050 x 0.050)	500 mW	500 mW	2.0 W	4.0 W	100 mW	1-2	700K	7M	700K	700K	7M	
60 x 60 (0.060 x 0.060)	500 mW	500 mW	2.0 W	4.0 W	100 mW	1-2	2M	15M	2M	2M	15M	
80 x 50 (0.080 x 0.050)	500 mW	500 mW	2.0 W	4.0 W	100 mW	1-2	2M	20M	2M	2M	20M	
100 x 50 (0.100 x 0.050)	500 mW	500 mW	2.0 W	4.0 W	100 mW	1-2	2.5M	25M	2.5M	2.5M	25M	
120 x 60 (0.120 x 0.060)	750 mW	750 mW	3.0 W	6.0 W	125 mW	1-2	3M	30M	3M	3M	30M	
100 x 100 (0.100 x 0.100)	750 mW	750 mW	3.0 W	6.0 W	125 mW	1-2	3.5M	35M	3.5M	3.5M	35M	

Typical PPI commercial testing includes 100% visual inspection, 100% electrical testing with short time overload, and TCR sampling.

Our parts meet or exceed additional MIL-PRF-55342 and MIL-STD-202 requirements.




Standard Chip Resistors – PR Series

General Properties

Operating Temperature	-55°C to +150°C
Storage Temperature	-65°C to +150°C
Operating Frequency	DC to 500 MHz
Voltage Rating	100V maximum
Power Derating (See Chart at Right)	Full power up to 70°C Derated linearly to zero power at 150°C

Power Derating Curve



Testing

Testing Performed	Specification / Standard
Visual Inspection	MIL-PRF-55342 MIL-STD-883
Mechanical Inspection	MIL-PRF-55342
DC Resistance	MIL-PRF-55342 MIL-STD-202
Resistance Temperature Characteristics (TCR)	MIL-PRF-55342
Short Time Overload	MIL-PRF-55342
High Temperature Exposure	MIL-PRF-55342
Thermal Shock	MIL-PRF-55342 MIL-STD-202
Resistance to Bonding Exposure	MIL-PRF-55342
Wire Bonding Integrity	MIL-PRF-55342
Life Test	MIL-PRF-55342 MIL-STD-202

Performance Specifications

Higher power ratings, additional sizes, and custom resistors available. Please contact sales@passiveplus.com.

Packaging

ESD waffle packs are standard. Film rings and gel pack packaging are available upon request.




Back Contact Resistors – PR Series

Product Features

- Wire-bondable Thin Film Resistors
- Built to the customer’s specifications.
- Operating frequencies from DC to 500 MHz.
- Provides engineers with space saving option.
- One wire bond is required to the top side of the chip, increasing reliability, with the bottom connection made by eutectic or conductive epoxy.
- Custom dual configuration.
- Can be used in Non-Magnetic Applications




30x30 220kΩ
Fine Line
Back Contact Resistor



Product Specifications

Resistance Range	5 Ω to 25MΩ
Resistance Tolerance	±0.01% to ±20%, value dependent
Resistive Material	Tantalum Nitride (TaN)

Part Numbering



Resistive Materials

Material	Passivation	Sheet Resistivity (Ω/ Sq)	Abs. Tolerance	Ratio Tolerance
Tantalum Nitride (TaN)	Self Passivating Ta ₂ O ₅	5 to 270	From ±0.01%	From ±0.01%

The standard dimensional tolerance for length and width is ± 2 mils.
The standard dimensional tolerance for thickness is ± 1 mil.

All parts are supplied in waffle packs. Other packaging may be available. Contact PPI for additional packaging options.



Back Contact Resistors – PR Series

Substrate Materials

Material	Thickness	Surface Finish	Dielectric Constant (@ 1MHz)	Coefficient of Thermal Expansion (x 10 ⁶ / °C)	Thermal Conductivity (W/m*K)	Code
Silicon (Si) (with 12kÅ SiO ₂)	0.005" - 0.010"	Chemical Polish	N/A (SiO ₂ K=1.38)	2.49 - 4.44 (25°C to < 1000°C)	149 (SiO ₂ 1.38)	22

Resistance Tolerance Codes

Tolerance	B	D	F	G	H	J	K	L	M	Q	S
Code	± 0.1%	± 0.5%	± 1%	± 2%	± 3%	± 5%	± 10%	± 15%	± 20%	± 0.05%	± 0.01%

* Limit of ± 50mΩs

Terminations

Metallization		Code
Top Side	Bottom Side	
TaN/Pd/Au	Au	W

Power Handling Codes

Watts	Code	Watts	Code
50 mW	C	250 Mw	G
75 mW	D	350 mW	M
100 mW	E	400 mW	R
125 Mw	I	500 mW	H
150 mW	F	750 mW	J
200 mW	O	1.0 W	K

Temperature Coefficient of Resistance

Material	±150 ppm/°C	±100 ppm/°C	±50 ppm/°C	±25 ppm/°C	±10 ppm/°C	±5 ppm/°C
Tantalum Nitride (TaN)	Q	V	W	X	Y	Z
	Standard	Yes	---	---	---	---
NiChrome (NiCr)	---	---	Yes	Standard	Yes	Yes



Back Contact Resistors – PR Series

Power Handling & Standard Resistance Ranges by Material and Case Size

Power Handling		Resistance Range	
Case Size mils (inches)	Silicon (C-22)	Min (Ω)	Max (Ω) Silicon (C-22)
12 x 9 (0.012 x 0.009)	50 mW	1-3	150K
14 x 12 (0.014 x 0.012)	100 mW	1-3	200K
20 x 10 (0.020 x 0.010)	100 mW	1-3	250K
15 x 15 (0.015 x 0.015)	100 mW	1-2	500K
20 x 20 (0.020 x 0.020)	250 mW	1-2	750K
30 x 20 (0.030 x 0.020)	250 mW	1-2	1M
40 x 20 (0.040 x 0.020)	250 mW	1-2	1.5M
30 x 30 (0.030 x 0.030)	250 mW	1-2	2M
35 x 35 (0.035 x 0.035)	250 mW	1-2	3M
40 x 40 (0.040 x 0.040)	350 mW	1-2	5M
50 x 25 (0.050 x 0.025)	350 mW	1-2	3M
60 x 30 (0.060 x 0.030)	500 mW	1-2	6M
50 x 50 (0.050 x 0.050)	500 mW	1-2	7M
60 x 60 (0.060 x 0.060)	500 mW	1-2	15M
80 x 50 (0.080 x 0.050)	500 mW	1-2	20M
100 x 50 (0.100 x 0.050)	500 mW	1-2	25M
120 x 60 (0.120 x 0.060)	750 mW	1-2	30M
100 x 100 (0.100 x 0.100)	750 mW	1-2	35M

Typical PPI commercial testing includes 100% visual inspection, 100% electrical testing with short time overload, and TCR sampling.

Our parts meet or exceed additional MIL-PRF-55342 and MIL-STD-202 requirements.






Back Contact Resistors – PR Series

General Properties

Operating Temperature	-55°C to +150°C
Storage Temperature	-65°C to +150°C
Operating Frequency	DC to 500 MHz
Voltage Rating	100V maximum
Power Derating (See Chart at Right)	Full power up to 70°C Derated linearly to zero power at 150°C

Power Derating Curve



Testing

Testing Performed	Specification / Standard
Visual Inspection	MIL-PRF-55342 MIL-STD-883
Mechanical Inspection	MIL-PRF-55342
DC Resistance	MIL-PRF-55342 MIL-STD-202
Resistance Temperature Characteristics (TCR)	MIL-PRF-55342
Short Time Overload	MIL-PRF-55342
High Temperature Exposure	MIL-PRF-55342
Thermal Shock	MIL-PRF-55342 MIL-STD-202
Resistance to Bonding Exposure	MIL-PRF-55342
Wire Bonding Integrity	MIL-PRF-55342
Life Test	MIL-PRF-55342 MIL-STD-202

Performance Specifications

Higher power ratings, additional sizes, and custom resistors available. Please contact sales@passiveplus.com.

Packaging

ESD waffle packs are standard. Film rings and gel pack packaging are available upon request.



Standard Edge Wrapped Chip Resistors – PR Series


Product Features

- Half wrap style chips have solid gold back contiguous with one pad, therefore eliminating one wirebond
- Full wrap style chips have both pads continue to the back side, allowing elimination of all wirebonds
- Can be used in Non-Magnetic Applications

Product Specifications


Resistance Range 1 Ω to 3.5MΩ

Resistance Tolerance ±0.01% to ±20%, value dependent




20x10 392Ω
Full Wrap Resistor

Half Wrap




Full Wrap



Part Numbering

Example shown below: Standard Resistor, TaN resistive element, AlN substrate, case size 0.040" × 0.020" × 0.010", dual edge wrap, resistance 200Ω ± 2%, 150 ppm TCR, 1.0 W max power handling.



Resistive Materials

Material	Passivation	Sheet Resistivity (Ω/ Sq)	Abs. Tolerance	Ratio Tolerance
Tantalum Nitride (TaN)	Self Passivating Ta ₂ O ₅	5 to 270	From ±0.01%	From ±0.01%
NiChrome (NiCr)	SiO ₂	5 to 250	From ±0.01%	From ±0.01%

The standard dimensional tolerance for length and width is ± 2 mils.
The standard dimensional tolerance for thickness is ± 1 mil.

All parts are supplied in waffle packs. Other packaging may be available. Contact PPI for additional packaging options.



Standard Edge Wrapped Chip Resistors – PR Series

Substrate Materials

Material	Thickness	Surface Finish	Dielectric Constant (@ 1MHz)	Coefficient of Thermal Expansion (x 10 ⁶ /°C)	Thermal Conductivity (W/m*K)	Code
Alumina (Al ₂ O ₃)	0.005" - 0.010"	2μ" - 3μ"	9.9	7 (25°C to < 300°C)	26.9	35
Aluminum Nitride (AlN)	0.005" - 0.010"	6μ" - 8μ"	8.0 - 9.1	4.6 - 5.7 (25°C to < 1000°C)	170	28
Beryllium Oxide (BeO)	0.005" - 0.010"	< 5μ"	6.76	9 (25°C to < 1000°C)	285	25

Resistance Tolerance Codes

Tolerance	B	D	F	G	H	J	K	L	M	Q	S
Code	± 0.1%	± 0.5%	± 1%	± 2%	± 3%	± 5%	± 10%	± 15%	± 20%	± 0.05%	± 0.01%

* Limit of ± 50mΩs

Terminations

Description	Code	Application	Metallization
1 Side Wrap	H	Epoxy or Au/Sn	Ta/Pd/Au
1 Side Wrap	M	Epoxy, Au/Sn or Sn Solder	TiW/Ni/Au
1 Side Wrap	S	Sn Solder Ball	TiW/Ni/Au - solder dipped
2 Side Wrap	J	Epoxy or Au/Sn	Ta/Pd/Au
2 Side Wrap	N	Epoxy, Au/Sn or Sn Solder	TiW/Ni/Au
2 Side Wrap	T	Sn Solder Ball	TiW/Ni/Au - solder dipped

Power Handling Codes

Watts	Code	Watts	Code
50 mW	C	750 mW	J
75 mW	D	1.0 W	K
100 mW	E	1.4 W	U
125 mW	I	2.0 W	L
150 mW	F	2.8 W	Y
200 mW	O	3.0 W	N
250 mW	G	4.0 W	P
350 mW	M	5.0 W	Q
400 mW	R	6.0 W	2
500 mW	H	10 W	S

Temperature Coefficient of Resistance

Material	±150 ppm/°C	±100 ppm/°C	±50 ppm/°C	±25 ppm/°C	±10 ppm/°C	±5 ppm/°C
Tantalum Nitride (TaN)	Q	V	W	X	Y	Z
	Standard	Yes	---	---	---	---
NiChrome (NiCr)	---	---	Yes	Standard	Yes	Yes



Standard Edge Wrapped Chip Resistors – PR Series

Power Handling & Standard Resistance Ranges by Material and Case Size

Case Size mils (inches)	Power Handling					Resistance Range					
	Alumina (C-35)	Silicon (C-22)	AlN (C-28)	BeO (C-25)	Quartz (C-20)	Min (Ω)	Max (Ω) Alumina (C-35)	Max (Ω) Silicon (C-22)	Max (Ω) AlN (C-28)	Max (Ω) BeO (C-25)	Max (Ω) Quartz (C-20)
12 x 9 (0.012 x 0.009)	50 mW	50 mW	200 mW	400 mW	10 mW	1-3	25K	150K	25K	25K	150K
14 x 12 (0.014 x 0.012)	100 mW	100 mW	400 mW	750 mW	20 mW	1-3	40K	200K	40K	40K	200K
20 x 10 (0.020 x 0.010)	100 mW	100 mW	400 mW	750 mW	20 mW	1-3	60K	250K	60K	60K	250K
15 x 15 (0.015 x 0.015)	100 mW	100 mW	400 mW	750 mW	20 mW	1-2	70K	500K	70K	70K	500K
20 x 20 (0.020 x 0.020)	250 mW	250 mW	1.0 W	2.0 W	50 mW	1-2	125K	750K	125K	125K	750K
30 x 20 (0.030 x 0.020)	250 mW	250 mW	1.0 W	2.0 W	50 mW	1-2	200K	1M	200K	200K	1M
40 x 20 (0.040 x 0.020)	250 mW	250 mW	1.0 W	2.0 W	50 mW	1-2	250K	1.5M	250K	250K	1.5M
30 x 30 (0.030 x 0.030)	250 mW	250 mW	1.0 W	2.0 W	50 mW	1-2	275K	2M	275K	275K	2M
35 x 35 (0.035 x 0.035)	250 mW	250 mW	1.0 W	2.0 W	50 mW	1-2	300K	3M	300K	300K	3M
40 x 40 (0.040 x 0.040)	350 mW	350 mW	1.4 W	2.8 W	70 mW	1-2	500K	5M	500K	500K	5M
50 x 25 (0.050 x 0.025)	350 mW	350 mW	1.4 W	2.8 W	70 mW	1-2	300K	3M	300K	300K	3M
60 x 30 (0.060 x 0.030)	500 mW	500 mW	2.0 W	4.0 W	100 mW	1-2	500K	6M	500K	500K	6M
50 x 50 (0.050 x 0.050)	500 mW	500 mW	2.0 W	4.0 W	100 mW	1-2	700K	7M	700K	700K	7M
60 x 60 (0.060 x 0.060)	500 mW	500 mW	2.0 W	4.0 W	100 mW	1-2	2M	15M	2M	2M	15M
80 x 50 (0.080 x 0.050)	500 mW	500 mW	2.0 W	4.0 W	100 mW	1-2	2M	20M	2M	2M	20M
100 x 50 (0.100 x 0.050)	500 mW	500 mW	2.0 W	4.0 W	100 mW	1-2	2.5M	25M	2.5M	2.5M	25M
120 x 60 (0.120 x 0.060)	750 mW	750 mW	3.0 W	6.0 W	125 mW	1-2	3M	30M	3M	3M	30M
100 x 100 (0.100 x 0.100)	750 mW	750 mW	3.0 W	6.0 W	125 mW	1-2	3.5M	35M	3.5M	3.5M	35M

Typical PPI commercial testing includes 100% visual inspection, 100% electrical testing with short time overload, and TCR sampling.


Our parts meet or exceed additional MIL-PRF-55342 and MIL-STD-202 requirements.



Standard Edge Wrapped Chip Resistors – PR Series

General Properties

Operating Temperature	-55°C to +150°C
Storage Temperature	-65°C to +150°C
Operating Frequency	DC to 500 MHz
Voltage Rating	100V maximum
Power Derating (See Chart at Right)	Full power up to 70°C Derated linearly to zero power at 150°C



Testing

Testing Performed	Specification / Standard
Visual Inspection	MIL-PRF-55342 MIL-STD-883
Mechanical Inspection	MIL-PRF-55342
DC Resistance	MIL-PRF-55342 MIL-STD-202
Resistance Temperature Characteristics (TCR)	MIL-PRF-55342
Short Time Overload	MIL-PRF-55342
High Temperature Exposure	MIL-PRF-55342
Thermal Shock	MIL-PRF-55342 MIL-STD-202
Resistance to Bonding Exposure	MIL-PRF-55342
Wire Bonding Integrity	MIL-PRF-55342
Life Test	MIL-PRF-55342 MIL-STD-202

Performance Specifications

Higher power ratings, additional sizes, and custom resistors available. Please contact sales@passiveplus.com.

Packaging

ESD waffle packs are standard. Film rings and gel pack packaging are available upon request.



Microwave Chip Resistors – PM Series

Product Features

- Special microwave laser-trimming to ensure a tight tolerance at high frequencies
- Compatible with flip-chip configurations
- Operating frequencies up to 60 GHz; higher frequencies are available
- Can be used in Non-Magnetic Applications




Product Specifications

Resistance Range 2 Ω to 5kΩ


Resistance Tolerance ±0.01% to ±20%, value dependent

VSWR	DC to 10 GHz	10 to 20 GHz	20 to 60 GHz
	1.2:1	1.3:1	1.5:1



Part Numbering

Example shown: Microwave Resistor, TaN resistive element, alumina substrate, case size 0.020" × 0.020" × 0.010", PdAu bonding pad, bottom side bare, resistance 1000 Ω ± 5%, 150 ppm TCR, microwave trim, 100 mW max power handling.



Resistive Materials

Code	Material	Passivation	Sheet Resistivity (Ω/ Sq)	Abs. Tolerance	Ratio Tolerance
T	Tantalum Nitride (TaN)	Self Passivating Ta ₂ O ₅	5 to 270	From ±0.01%	From ±0.01%
N	NiChrome (NiCr)	SiO ₂	5 to 250	From ±0.01%	From ±0.01%

The standard dimensional tolerance for length and width is ± 2 mils. The standard dimensional tolerance for thickness is ± 1 mil.

All parts are supplied in waffle packs. Other packaging may be available. Contact PPI for additional packaging options.



Microwave Chip Resistors – PM Series

Substrate Materials

Material	Thickness	Surface Finish	Dielectric Constant (@ 1MHz)	Coefficient of Thermal Expansion (x 10 ⁶ /°C)	Thermal Conductivity (W/m*K)	Code
Alumina (Al ₂ O ₃)	0.005" - 0.010"	2μ" - 3μ"	9.9	⁷ (25°C to < 300°C)	26.9	35
Aluminum Nitride (AlN)	0.005" - 0.010"	6μ" - 8μ"	8.0 - 9.1	^{4.6 - 5.7} (25°C to < 1000°C)	170	28
Beryllium Oxide (BeO)	0.005" - 0.010"	< 5μ"	6.76	⁹ (25°C to < 1000°C)	285	25
Quartz (Fused Silica)	0.005" - 0.010"	60/40 Optical Polish	3.826	^{0.55} (25°C to < 300°C)	1.38	20

Resistance Tolerance Codes

Tolerance	B	D	F	G	H	J	K	L	M	Q	S
Code	± 0.1%	± 0.5%	± 1%	± 2%	± 3%	± 5%	± 10%	± 15%	± 20%	± 0.05%	± 0.01%

Terminations

Metallization		Code
Top Side	Bottom Side	
Pd / Au	—	A
Flip Chip (Ti/Pt/Au)		R
Pd/Au	Ta/Pd/Au	D

Temperature Coefficient of Resistance

Material	±150 ppm/°C	±100 ppm/°C	±50 ppm/°C	±25 ppm/°C	±10 ppm/°C	±5 ppm/°C
Tantalum Nitride (TaN)	Q	V	W	X	Y	Z
	Standard	Yes	---	---	---	---
NiChrome (NiCr)	---	---	Yes	Standard	Yes	Yes

Power Handling Codes

Watts	Code	Watts	Code	Watts	Code
10 mW	A	350 mW	M	4.0 W	P
20 mW	B	400 mW	R	5.0 W	Q
50 mW	C	500 mW	H	6.0 W	Z
75 mW	D	750 mW	J	10 W	S
100 mW	E	1.0 W	K	15 W	T
125 mW	I	1.4 W	U	20 W	V
150 mW	F	2.0 W	L	25 W	W
200 mW	O	2.8 W	Y	30 W	Z
250 mW	G	3.0 W	N	50 W	X
				40 W	1



Microwave Chip Resistors – PM Series

Power Handling & Standard Resistance Ranges by Material and Case Size

Standard Power Handling							High Power Resistor Range				
Case Size mils (inches)	Alumina (C35)	AlN (C-28)	BeO (C-25)	Quartz (C-20)	Min (Ω)	Max (Ω)	Min (Ω)	Max (Ω)	Max (Ω) Alumina (C-35)	Max (Ω) AlN (C-28)	Max (Ω) BeO (C-25)
12 x 9 (0.012 x 0.009)	50 mW	200 mW	400 mW	10 mW	4	500	---	---	---	---	---
14 x 12 (0.014 x 0.012)	100 mW	400 mW	750 mW	20 mW	3	750	---	---	---	---	---
20 x 10 (0.020 x 0.010)	100 mW	400 mW	750 mW	20 mW	3	1000	2	1000	250 mW	1.0 W	2.0 W
15 x 15 (0.015 x 0.015)	100 mW	400 mW	750 mW	20 mW	4	1000	2	1000	250 mW	1.0 W	2.0 W
20 x 20 (0.020 x 0.020)	250 mW	1.0 W	2.0 W	50 mW	2	1250	2	1000	500 mW	2.0 W	4.0 W
30 x 20 (0.030 x 0.020)	250 mW	1.0 W	2.0 W	50 mW	2	2500	2	1000	500 mW	2.0 W	4.0 W
40 x 20 (0.040 x 0.020)	250 mW	1.0 W	2.0 W	50 mW	2	3750	2	1000	750 mW	3.0 W	6.0 W
30 x 30 (0.030 x 0.030)	250 mW	1.0 W	2.0 W	50 mW	2	2500	2	1000	750 mW	2.0 W	6.0 W
35 x 35 (0.035 x 0.035)	250 mW	1.0 W	2.0 W	50 mW	2	3000	2	1000	1.0 W	4.0 W	6.0 W
40 x 40 (0.040 x 0.040)	350 mW	1.4 W	2.8 W	70 mW	2	3750	2	1000	1.0 W	4.0 W	6.0 W
50 x 25 (0.050 x 0.025)	350 mW	1.4 W	2.8 W	70 mW	3	5000	2	1000	1.0 W	4.0 W	6.0 W
60 x 30 (0.060 x 0.030)	500 mW	2.0 W	4.0 W	100 mW	3	5000	2	1000	1.4 W	5.0 W	10.0 W
50 x 50 (0.050 x 0.050)	500 mW	2.0 W	4.0 W	100 mW	2	5000	2	1000	1.4 W	5.0 W	10.0 W
60 x 60 (0.060 x 0.060)	500 mW	2.0 W	4.0 W	100 mW	2	5000	2	1000	1.4 W	5.0 W	10.0 W
80 x 50 (0.080 x 0.050)	500 mW	2.0 W	4.0 W	100 mW	2	5000	2	1000	2.8 W	10.0 W	15.0 W
100 x 50 (0.100 x 0.050)	500 mW	2.0 W	4.0 W	100 mW	2	5000	2	1000	2.8 W	10.0 W	15.0 W
120 x 60 (0.120 x 0.060)	750 mW	3.0 W	6.0 W	125 mW	2	5000	2	1000	2.8 W	10.0 W	15.0 W
100 x 100 (0.100 x 0.100)	750 mW	3.0 W	6.0 W	125 mW	2	5000	2	1000	2.8 W	10.0 W	15.0 W

Typical PPI commercial testing includes 100% visual inspection, 100% electrical testing with short time overload, and TCR sampling.


Our parts meet or exceed additional MIL-PRF-55342 and MIL-STD-202 requirements.



Microwave Chip Resistors – PM Series

General Properties

Operating Temperature	-55°C to +150°C
Storage Temperature	-65°C to +150°C
Operating Frequency	DC to 60 GHz
Voltage Rating	100V maximum
Power Derating (See Chart at Right)	Full power up to 70°C Derated linearly to zero power at 150°C



Testing

Testing Performed	Specification / Standard
Visual Inspection	MIL-PRF-55342 MIL-STD-883
Mechanical Inspection	MIL-PRF-55342
DC Resistance	MIL-PRF-55342 MIL-STD-202
Resistance Temperature Characteristics (TCR)	MIL-PRF-55342
Short Time Overload	MIL-PRF-55342
High Temperature Exposure	MIL-PRF-55342
Thermal Shock	MIL-PRF-55342 MIL-STD-202
Resistance to Bonding Exposure	MIL-PRF-55342
Wire Bonding Integrity	MIL-PRF-55342
Life Test	MIL-PRF-55342 MIL-STD-202

Performance Specifications

Higher power ratings, additional sizes, and custom resistors available. Please contact sales@passiveplus.com.

Packaging


ESD waffle packs are standard. Film rings and gel pack packaging are available upon request.



Microwave Edge Wrapped Chip Resistors

Product Features

- Edge Wrap similar in construction to our standard surface mount wrap resistors, with half wrap and full wrap styles available.
- The addition of a microwave design allows for operation at frequencies up to 60 GHz.
- Can be used in Non-Magnetic Applications




Product Specifications


Resistance Range 2 Ω to 5kΩ

Resistance Tolerance ±0.5% to ±20%, value dependent

Half Wrap




Full Wrap



Part Numbering

Example shown below: Microwave Resistor, TaN resistive element, AlN substrate, case size 0.040" × 0.020" × 0.010", dual edge wrap, resistance 200 Ω ± 2%, 150 ppm TCR, 1.0 W max power handling.



Resistive Materials

Code	Material	Passivation	Sheet Resistivity (Ω/ Sq)	Abs. Tolerance	Ratio Tolerance
T	Tantalum Nitride (TaN)	Self Passivating Ta ₂ O ₅	5 to 270	From ±0.01%	From ±0.01%
N	NiChrome (NiCr)	SiO ₂	5 to 250	From ±0.01%	From ±0.01%

The standard dimensional tolerance for length and width is ± 2 mils. The standard dimensional tolerance for thickness is ± 1 mil.

All parts are supplied in waffle packs. Other packaging may be available. Contact PPI for additional packaging options.



Microwave Edge Wrapped Chip Resistors

Substrate Materials

Material	Thickness	Surface Finish	Dielectric Constant (@ 1MHz)	Coefficient of Thermal Expansion (x 10 ⁶ /°C)	Thermal Conductivity (W/m*K)	Code
Alumina (Al ₂ O ₃)	0.005" - 0.010"	2μ" - 3μ"	9.9	⁷ (25°C to < 300°C)	26.9	35
Aluminum Nitride (AlN)	0.005" - 0.010"	6μ" - 8μ"	8.0 - 9.1	^{4.6 - 5.7} (25°C to < 1000°C)	170	28
Beryllium Oxide (BeO)	0.005" - 0.010"	< 5μ"	6.76	⁹ (25°C to < 1000°C)	285	25

Resistance Tolerance Codes

Tolerance	B	D	F	G	H	J	K	L	M	Q	S
Code	± 0.1%	± 0.5%	± 1%	± 2%	± 3%	± 5%	± 10%	± 15%	± 20%	± 0.05%	± 0.01%

Terminations

Metallization	Application	Code
1 Side Wrap	Epoxy or Au/Sn	H
1 Side Wrap	Epoxy, Au/Sn, or Sn Solder	M
1 Side Wrap	Sn Solder Ball	S
2 Side Wrap	Epoxy or Au/Sn	J
2 Side Wrap	Epoxy, Au/Sn, or Sn Solder	N
2 Side Wrap	Sn Solder Ball	T

Temperature Coefficient of Resistance

Material	±150 ppm/°C	±100 ppm/°C	±50 ppm/°C	±25 ppm/°C	±10 ppm/°C	±5 ppm/°C
Tantalum Nitride (TaN)	Q	V	W	X	Y	Z
	Standard	Yes	---	---	---	---
NiChrome (NiCr)	---	---	Yes	Standard	Yes	Yes

Power Handling Codes

Watts	Code	Watts	Code	Watts	Code
10 mW	A	350 mW	M	4.0 W	P
20 mW	B	400 mW	R	5.0 W	Q
50 mW	C	500 mW	H	6.0 W	Z
75 mW	D	750 mW	J	10 W	S
100 mW	E	1.0 W	K	15 W	T
125 mW	I	1.4 W	U	20 W	V
150 mW	F	2.0 W	L	25 W	W
200 mW	O	2.8 W	Y	30 W	Z
250 mW	G	3.0 W	N	50 W	X
				40 W	1



Microwave Edge Wrapped Chip Resistors

Power Handling & Standard Resistance Ranges by Material and Case Size

Standard Power Handling							High Power Resistor Range				
Case Size mils (inches)	Alumina (C35)	AlN (C-28)	BeO (C-25)	Quartz (C-20)	Min (Ω)	Max (Ω)	Min (Ω)	Max (Ω)	Max (Ω) Alumina (C-35)	Max (Ω) AlN (C-28)	Max (Ω) BeO (C-25)
12 x 9 (0.012 x 0.009)	50 mW	200 mW	400 mW	10 mW	4	500	---	---	---	---	---
14 x 12 (0.014 x 0.012)	100 mW	400 mW	750 mW	20 mW	3	750	---	---	---	---	---
20 x 10 (0.020 x 0.010)	100 mW	400 mW	750 mW	20 mW	3	1000	2	1000	250 mW	1.0 W	2.0 W
15 x 15 (0.015 x 0.015)	100 mW	400 mW	750 mW	20 mW	4	1000	2	1000	250 mW	1.0 W	2.0 W
20 x 20 (0.020 x 0.020)	250 mW	1.0 W	2.0 W	50 mW	2	1250	2	1000	500 mW	2.0 W	4.0 W
30 x 20 (0.030 x 0.020)	250 mW	1.0 W	2.0 W	50 mW	2	2500	2	1000	500 mW	2.0 W	4.0 W
40 x 20 (0.040 x 0.020)	250 mW	1.0 W	2.0 W	50 mW	2	3750	2	1000	750 mW	3.0 W	6.0 W
30 x 30 (0.030 x 0.030)	250 mW	1.0 W	2.0 W	50 mW	2	2500	2	1000	750 mW	2.0 W	6.0 W
35 x 35 (0.035 x 0.035)	250 mW	1.0 W	2.0 W	50 mW	2	3000	2	1000	1.0 W	4.0 W	6.0 W
40 x 40 (0.040 x 0.040)	350 mW	1.4 W	2.8 W	70 mW	2	3750	2	1000	1.0 W	4.0 W	6.0 W
50 x 25 (0.050 x 0.025)	350 mW	1.4 W	2.8 W	70 mW	3	5000	2	1000	1.0 W	4.0 W	6.0 W
60 x 30 (0.060 x 0.030)	500 mW	2.0 W	4.0 W	100 mW	3	5000	2	1000	1.4 W	5.0 W	10.0 W
50 x 50 (0.050 x 0.050)	500 mW	2.0 W	4.0 W	100 mW	2	5000	2	1000	1.4 W	5.0 W	10.0 W
60 x 60 (0.060 x 0.060)	500 mW	2.0 W	4.0 W	100 mW	2	5000	2	1000	1.4 W	5.0 W	10.0 W
80 x 50 (0.080 x 0.050)	500 mW	2.0 W	4.0 W	100 mW	2	5000	2	1000	2.8 W	10.0 W	15.0 W
100 x 50 (0.100 x 0.050)	500 mW	2.0 W	4.0 W	100 mW	2	5000	2	1000	2.8 W	10.0 W	15.0 W
120 x 60 (0.120 x 0.060)	750 mW	3.0 W	6.0 W	125 mW	2	5000	2	1000	2.8 W	10.0 W	15.0 W
100 x 100 (0.100 x 0.100)	750 mW	3.0 W	6.0 W	125 mW	2	5000	2	1000	2.8 W	10.0 W	15.0 W

Typical PPI commercial testing includes 100% visual inspection, 100% electrical testing with short time overload, and TCR sampling.


Our parts meet or exceed additional MIL-PRF-55342 and MIL-STD-202 requirements.



Microwave Edge Wrapped Chip Resistors

General Properties

Operating Temperature	-55°C to +150°C
Storage Temperature	-65°C to +150°C
Operating Frequency	DC to 60 GHz
Voltage Rating	100V maximum
Power Derating (See Chart at Right)	Full power up to 70°C Derated linearly to zero power at 150°C



Testing

Testing Performed	Specification / Standard
Visual Inspection	MIL-PRF-55342 MIL-STD-883
Mechanical Inspection	MIL-PRF-55342
DC Resistance	MIL-PRF-55342 MIL-STD-202
Resistance Temperature Characteristics (TCR)	MIL-PRF-55342
Short Time Overload	MIL-PRF-55342
High Temperature Exposure	MIL-PRF-55342
Thermal Shock	MIL-PRF-55342 MIL-STD-202
Resistance to Bonding Exposure	MIL-PRF-55342
Wire Bonding Integrity	MIL-PRF-55342
Life Test	MIL-PRF-55342 MIL-STD-202

Performance Specifications

Higher power ratings, additional sizes, and custom resistors available. Please contact sales@passiveplus.com.

Packaging


ESD waffle packs are standard. Film rings and gel pack packaging are available upon request.



Dual Chip Resistors – PD Series



Product Features

- Two resistors on a single chip area.
- Available styles are common or isolated node.
- The nature of this design lends itself to tightly matched TCR and electrical tolerance, with resistance ratios within 0.01% possible (value dependent).
- Can be used in Non-Magnetic Applications




Product Specifications

Resistance Range	2Ω - 1MΩ per resistor (Silicon or Quartz) 2Ω - 160kΩ per resistor (Al ₂ O ₃ , BeO, or AlN)
Resistance Tolerance	±0.01% to ±20% value dependent
Standard Size	30 mil x 30 mil x 10 mil 0.03" x 0.03" x 0.01"




Common Node Configuration



Isolated Node Configuration

Part Numbering



Resistive Style

Code	Style
D	Dual Resistors
I	Isolated Resistors

Resistive Materials

Material	Passivation	Sheet Resistivity (Ω/ Sq)	Abs. Tolerance	Ratio Tolerance
Tantalum Nitride (TaN)	Self Passivating Ta ₂ O ₅	5 to 270	From ±0.01%	From ±0.01%
NiChrome (NiCr)	SiO ₂	5 to 250	From ±0.01%	From ±0.01%

All parts are supplied in waffle packs. Other packaging may be available. Contact PPI for additional packaging options.



Dual Chip Resistors – PD Series

Substrate Materials

Material	Thickness	Surface Finish	Dielectric Constant (@ 1MHz)	Coefficient of Thermal Expansion (x 10 ⁶ /°C)	Thermal Conductivity (W/m ² *K)	Code	Power per Resistor
Alumina (Al ₂ O ₃)	0.005" - 0.010"	2μ" - 3μ"	9.9	⁷ (25°C to < 300°C)	26.9	35	125 mW
Aluminum Nitride (AlN)	0.005" - 0.010"	6μ" - 8μ"	8.0 - 9.1	^{4.6 - 5.7} (25°C to < 1000°C)	170	28	500 mW
Beryllium Oxide (BeO)	0.005" - 0.010"	< 5μ"	6.76	⁹ (25°C to < 1000°C)	285	25	1 W
Silicon (Si) (with 12kÅ SiO ₂)	0.005" - 0.010"	Chemical Polish	N/A (SiO ₂ K=1.38)	^{2.49 - 4.44} (25°C to < 1000°C)	149 (SiO ₂ 1.38)	22	125 mW
Quartz (Fused Silica)	0.005" - 0.010"	60/40 Optical Polish	3.826	^{0.55} (25°C to < 300°C)	1.38	20	25 mW

Resistance Tolerance Codes

Tolerance	B	D	F	G	H	J	K	L	M	Q	S
Code	± 0.1%	± 0.5%	± 1%	± 2%	± 3%	± 5%	± 10%	± 15%	± 20%	± 0.05%	± 0.01%

Terminations

Metallization		Code
Top Side	Bottom Side	
Pd / Au	—	A
Pd / Au	Ta/Pd/Au	D
Pd / Au	Au Sputtered	K

Temperature Coefficient of Resistance

Material	±150 ppm/°C	±100 ppm/°C	±50 ppm/°C	±25 ppm/°C	±10 ppm/°C	±5 ppm/°C
Tantalum Nitride (TaN)	Q	V	W	X	Y	Z
	Standard	Yes	---	---	---	---
NiChrome (NiCr)	---	---	Yes	Standard	Yes	Yes

Power Handling Range by Material

Case Size mils (inches)	Alumina (C35)	Silicon (C-22)	AlN (C-28)	BeO (C-25)	Quartz (C-20)
30 x 30 (0.030 x 0.030)	125 mW	125 mW	500 mW	1.0 W	25 mW

Resistance Ratio Codes


Tolerance To Other Resistors	Code
±0.01%	G
±0.05%	H
±0.10%	J
±0.25%	K
±0.50%	M
±1.00%	N
No Ratio	R



Dual Chip Resistors – PD Series

General Properties

Operating Temperature	-55°C to +150°C
Storage Temperature	-65°C to +150°C
Operating Frequency	DC to 500 MHz
Voltage Rating	100V maximum
Power Derating (See Chart at Right)	Full power up to 70°C Derated linearly to zero power at 150°C



Testing

Testing Performed	Specification / Standard
Visual Inspection	MIL-PRF-55342 MIL-STD-883
Mechanical Inspection	MIL-PRF-55342
DC Resistance	MIL-PRF-55342 MIL-STD-202
Resistance Temperature Characteristics (TCR)	MIL-PRF-55342
Short Time Overload	MIL-PRF-55342
High Temperature Exposure	MIL-PRF-55342
Thermal Shock	MIL-PRF-55342 MIL-STD-202
Resistance to Bonding Exposure	MIL-PRF-55342
Wire Bonding Integrity	MIL-PRF-55342
Life Test	MIL-PRF-55342 MIL-STD-202

Performance Specifications

Higher power ratings, additional sizes, and custom resistors available. Please contact sales@passiveplus.com.

Packaging


ESD waffle packs are standard. Film rings and gel pack packaging are available upon request.



Standard Resistor Array – PS, PB, PI Series



Product Features

- Configured in 3 to 12 resistor combinations with all resistors at the same value and tolerance.
- Custom arrays can be designed to engineer’s specifications.
- Can be used in Non-Magnetic Applications





Product Specifications



Resistance Range	5Ω to 100 kΩ per resistor (Alumina) 5Ω to 1 MΩ per resistor (Silicon)
Resistive Material	Tantalum Nitride
Ratio Tolerance	To 0.01% value dependent



Isolated




Common



Series

Part Numbering



Resistive Style

Code	Style
I	Isolated Array
B	Common-Bus Array
S	Series Array

Resistive Materials

Material	Code	Passivation	Sheet Resistivity (Ω/ Sq)	Abs. Tolerance	Ratio Tolerance
Tantalum Nitride (TaN)	T	Self Passivating Ta ₂ O ₅	5 to 270	From ±0.01%	From ±0.01%



Standard Resistor Array – PS, PB, PI Series

Substrate Materials

Recommended Substrates	Code
99.6% Alumina (Al ₂ O ₃)	35
Silicon (SiO ₂)	20

Terminations

Metallization		Code
Top Side	Bottom Side	
Pd / Au	—	A
Pd / Au	Ta/Pd/Au	D
Pd / Au	Au Sputtered	K

Resistance Tolerance Codes

Tolerance	B	D	F	G	H	J	K	L	M	Q	S
Code	± 0.1%	± 0.5%	± 1%	± 2%	± 3%	± 5%	± 10%	± 15%	± 20%	± 0.05%	± 0.01%

Temperature Coefficient of Resistance

Material	±150 ppm/°C	±100 ppm/°C
Tantalum Nitride (TaN)	Q	V
	Standard	Yes

Power Handling

Resistors	3	4	5	6	7	8	9	10	11	12
Length (mils)	40 (0.04")	50 (0.05")	60 (0.06")	70 (0.07")	80 (0.08")	90 (0.09")	100 (0.10")	110 (0.11")	120 (0.12")	130 (0.13")
Width	60 mils (0.06") standard									
Thickness	10 mils (0.01") standard									
Power	50 mW/ Resistor standard									

Packaging

Code	Style
W	Waffle Pack (Standard)
G	Gel Pack

All parts are supplied in waffle packs. Other packaging may be available. Contact PPI for additional packaging options.




Standard Resistor Array – PS, PB, PI Series

General Properties

Operating Temperature	-55°C to +150°C
Storage Temperature	-65°C to +150°C
Operating Frequency	DC to 500 MHz
Voltage Rating	100V maximum
Power Derating (See Chart at Right)	Full power up to 70°C Derated linearly to zero power at 150°C

Power Derating Curve



Testing

Testing Performed	Specification / Standard
Visual Inspection	MIL-PRF-55342 MIL-STD-883
Mechanical Inspection	MIL-PRF-55342
DC Resistance	MIL-PRF-55342 MIL-STD-202
Resistance Temperature Characteristics (TCR)	MIL-PRF-55342
Short Time Overload	MIL-PRF-55342
High Temperature Exposure	MIL-PRF-55342
Thermal Shock	MIL-PRF-55342 MIL-STD-202
Resistance to Bonding Exposure	MIL-PRF-55342
Wire Bonding Integrity	MIL-PRF-55342
Life Test	MIL-PRF-55342 MIL-STD-202

Performance Specifications

Higher power ratings, additional sizes, and custom resistors available. Please contact sales@passiveplus.com.

Packaging


ESD waffle packs are standard. Film rings and gel pack packaging are available upon request.



Network Resistor Array – PN Series


Product Features

- Multiple resistances in a single, space saving chip.
- Single chip geometry offers excellent TCR tracking and resistance ratio tracking.
- PPI offers chips with 12 or 20 resistive elements as standard.
- Other configurations are available upon request.
- Can be used in Non-Magnetic Applications



Product Specifications


Resistive Material	Tantalum Nitride
Ratio Tolerance	To 0.01% value dependent



12 Resistor Configuration

20 Resistor Configuration

Part Numbering



Resistor Style

Code	Style
N	Network Array

Resistive Materials

Code	Material	Passivation	Sheet Resistivity (Ω/ Sq)	Abs. Tolerance	Ratio Tolerance
T	Tantalum Nitride (TaN)	Self Passivating Ta ₂ O ₅	5 to 270	From ±0.01%	From ±0.01%



Network Resistor Array – PN Series

Substrate Materials

Code	Material	Thickness	Surface Finish	Dielectric Constant (@ 1MHz)	Coefficient of Thermal Expansion (x 10 ⁶ /°C)	Thermal Conductivity (W/m*K)
35	Alumina (Al ₂ O ₃)	0.005" - 0.010"	2μ" - 3μ"	9.9	7 (25°C to < 300°C)	26.9
22	Silicon (Si) (with 12kÅ SiO ₂)	0.005" - 0.010"	Chemical Polish	N/A (SiO ₂ K=1.38)	2.49 - 4.44 (25°C to < 1000°C)	149 (SiO ₂ 1.38)

Terminations

Code	Metallization	
	Top Side	Bottom Side
A	Pd / Au	—
D	Pd / Au	Ta/Pd/Au
K	Pd/ Au	Au Sputtered

Resistance Range

Code	Size	Substrate Metallization	Resistance Range	Resistance Distribution
12	30x30 (0.030"x0.030")	Silicon	80Ω to 240kΩ	R ₁ to R ₇ = R _t /8
		Alumina	80Ω to 50kΩ	R ₈ to R ₁₂ = R _t /40
20	38x38 (0.038"x0.038")	Silicon	550Ω to 500kΩ	R ₁ to R ₁₀ = R _t /110
		Alumina	550Ω to 50kΩ	R ₁₁ to R ₂₀ = R _t /11

Resistance Tolerance Codes

Code	J	K	M
Tolerance	± 5%	± 10%	± 20%

Temperature Coefficient of Resistance

Code	TC	Material
Q*	±150 ppm/°C	Tantalum Nitride
V	±100 ppm/°C	(TaN)

*Standard

Power Handling

Code	Rating
C	250mW

Packaging

Code	Style
W	Waffle Pack (Standard)
G	Gel Pack

All parts are supplied in waffle packs. Other packaging may be available. Contact PPI for additional packaging options.




Network Resistor Array – PN Series

General Properties

Operating Temperature	-55°C to +150°C
Storage Temperature	-65°C to +150°C
Operating Frequency	DC to 500 MHz
Voltage Rating	100V maximum
Power Derating (See Chart at Right)	Full power up to 70°C Derated linearly to zero power at 150°C

Power Derating Curve



Testing

Testing Performed	Specification / Standard
Visual Inspection	MIL-PRF-55342 MIL-STD-883
Mechanical Inspection	MIL-PRF-55342
DC Resistance	MIL-PRF-55342 MIL-STD-202
Resistance Temperature Characteristics (TCR)	MIL-PRF-55342
Short Time Overload	MIL-PRF-55342
High Temperature Exposure	MIL-PRF-55342
Thermal Shock	MIL-PRF-55342 MIL-STD-202
Resistance to Bonding Exposure	MIL-PRF-55342
Wire Bonding Integrity	MIL-PRF-55342
Life Test	MIL-PRF-55342 MIL-STD-202




Performance Specifications

Higher power ratings, additional sizes, and custom resistors available. Please contact sales@passiveplus.com.




Product Features


- Reduces amplitude or power of a signal by a known value. This is achieved with very little distortion of the signal, maintaining accuracy up to 40 GHz.
- Attenuators are available with or without center Taps
- Single wraps of the ground pad to a full gold backside available
- Additional Attenuator configurations, including balanced attenuators, are available as custom parts
- Can be used in Non-Magnetic Applications



Attenuator Top Contact




Attenuator, Single Pad Wrap



Attenuator, 3-Sided Wrap



Part Numbering



Resistive Metallizations

Code	Material	Passivation	Sheet Resistivity (Ω/Sq)	Abs. Tolerance	Ratio Tolerance
T	Tantalum Nitride (TaN)	Self Passivating Ta ₂ O ₅	5 to 270	From ±0.01%	From ±0.01%



Attenuator Type

Code	Description
S	T-Pattern



Attenuators – PAT Series

 **Materials**

(LxWxT) Dimensions (mils)	Power (W)			Value	
	Al ₂ O ₃	AlN	BeO	Min	Max
CODE	35	28	25		
50x50x10	250mW	1W	2W	0.5dB	24.5dB
80x60x15	250mW	1W	2W	0.5dB	24.5dB
150x120x25	2W	8W	16W	0.5dB	24.5dB

 **Bond Pad Metallizations**

Metallization	Code
Top Only	A
Single Wrap, Full GRD Plane	M
Flip Chip	R
3-sided Wrap	X

 **Attenuation Tolerance**

Tolerance	Code
±0.1dB (-0.5 to -6.0dB)	F
±0.2dB (-6.5 to -24.5dB)	G

 **Temperature Coefficient of Resistance**

TCR	Availability	Code
±150ppm	Standard	Q
±100ppm	Optional	V

 **Power Handling**

Power	Code
250mW	G
1.0W	K
2.0W	L
8.0W	R
16.0W	Y

Power Ratings assume proper heat sinking is used.

 **Packaging**

Code	Style
W	Waffle Pack (Standard)
G	Gel Pack

All parts are supplied in waffle packs. Other packaging may be available. Contact PPI for additional packaging options.




Attenuators – PAT Series



General Properties

Operating Temperature	-55°C to +150°C
Storage Temperature	-65°C to +150°C
Operating Frequency	DC to 40 GHz
Voltage Rating	100V maximum
Power Derating (See Chart at Right)	Full power up to 70°C Derated linearly to zero power at 150°C

Power Derating Curve



Testing

Testing Performed	Specification / Standard
Visual Inspection	MIL-PRF-55342 MIL-STD-883
Mechanical Inspection	MIL-PRF-55342
DC Resistance	MIL-PRF-55342 MIL-STD-202
Resistance Temperature Characteristics (TCR)	MIL-PRF-55342
Short Time Overload	MIL-PRF-55342
High Temperature Exposure	MIL-PRF-55342
Thermal Shock	MIL-PRF-55342 MIL-STD-202
Resistance to Bonding Exposure	MIL-PRF-55342
Wire Bonding Integrity	MIL-PRF-55342
Life Test	MIL-PRF-55342 MIL-STD-202



Performance Specifications

Higher power ratings, additional sizes, and custom resistors available. Please contact sales@passiveplus.com.



Packaging

ESD waffle packs are standard. Gel pack packaging also available. Film rings are available upon request for Top Contact Attenuators only. Please contact PPI for availability.


Thermal Conductors – PTC Series

λ Product Features

With the increase in heat dissipation from microelectronics devices and the reduction in overall form factors, thermal management becomes a more and more important element of electronic product design.

PPI's Thermal conductors are a passive heat exchanger that transfers the heat generated by an electronic device to a thermal ground plane or any specific thermal point where it gets dissipated away from the device.

Our thermal conductors are available in a variety of sizes including standard EIA case sizes and are constructed using Aluminum Nitride (AlN) or Beryllium Oxide (BeO).



λ Product Features

- High Thermal Conductivity
- Low Thermal Resistance
- Low Capacitance
- One piece construction
- RoHS Compliant
- EIA case sizes
- More efficient thermal management

λ Applications


- GaN Power Amplifiers
- High RF Power Amplifiers
- Filters
- Synthesizers
- Switch Mode Power Supplies
- Pin & Laser Diodes

λ Functional Applications

- Between active device & adjacent ground planes
- Specific contact pad to case
- Contact pad to contact pad
- Direct component contact to via pad or trace
- Edges fully metallized

λ Part Numbering

Example shown below: Thermal Conductor, AlN, 1005, thickness (40 mils), Platinum/Gold (Pt/Au), Waffle Pack





Thermal Conductors – PTC Series

λ Parts Characterizations

Case Size	Length (L) mils / (mm)	Width (W) mils / (mm)	Thickness (T) mils / (mm)	Terminal (t)	Thermal Resistance (°C/W)		Thermal Conductivity (mW/°C)	
					AlN	BeO	AlN	BeO
0302	30 ± 2 (.770 ± .051)	20 ± 2 (.510 ± .0510)	20 (.020 ± .002)	10 -0.25	19	12	53	81
0402	40 ± 2 (1.020 ± .051)	20 ± 2 (.510 ± .0510)	20 (.020 ± .002)	10 -0.25	25	16	40	61
0505	50 ± 2 (1.270 ± .051)	50 ± 2 (1.270 ± .051)	25 (.025 ± .002)	15 -0.38	10	7	100	153
0603	60 ± 2 (1.52 ± .051)	30 ± 2 (.760 ± .051)	25 (.025 ± .002)	15 -0.38	20	13	50	76
0805	80 ± 2 (2.030 ± .051)	50 ± 2 1.270 ± .051)	40 (.040 ± .002)	20 -0.51	10	7	100	153
1005	100 ± 2 (2.54 ± .051)	50 ± 2 (1.27 ± .051)	40 (.040 ± .002)	20 -0.51	13	8	77	122
1020	100 ± 2 (2.540 ± .051)	200 ± 2 (5.080 ± .051)	40 (.040 ± .002)	20 -0.51	3	2	320	508
1111	110 ± 2 (2.790 ± .051)	110 ± 2 (2.790 ± .051)	40 (.040 ± .002)	20 -0.51	7	4	153	240
2010	195 ± 10 (4.950 ± .254)	195 ± 10 (2.410 ± .254)	60 (.060 ± .002)	30 -0.77	10	6	100	159
2525	240 ± 10 (6.100 ± .254)	250 ± 10 (6.350 ± .254)	60 (.060 ± .002)	40 -1.02	4	3	240	380
3725	370 ± 10 (9.400 ± .254)	245 ± 10 (6.220 ± .254)	60 (.060 ± .002)	50 -1.27	6	4	160	254
3737	365 ± 10 (9.270 ± .254)	375 ± 10 (9.530 ± .254)	60 (.060 ± .002)	50 -1.27	4	3	240	380

λ Materials

	AlN	BeO
CODE	28	25

λ Metallizations

Termination Code	Termination Materials
N*	Platinum/Gold (Pt/Au)
X	Platinum/Silver (Pt/Ag)

*Recommended

λ Packaging

Code	Style
W	Waffle Pack (Standard)
G	Gel Pack

All parts are supplied in waffle packs. Other packaging may be available. Contact PPI for additional packaging options.





Thermal Conductors – PTC Series

λ General Properties

Operating Temperature	-55°C to +150°C
Storage Temperature	-65°C to +150°C
Insulation Resistance	10 ¹² Ω min at 25°C



λ Testing

Testing Performed	Specification / Standard
Visual Inspection	MIL-PRF-55342 MIL-STD-883
Mechanical Inspection	MIL-PRF-55342
DC Resistance	MIL-PRF-55342 MIL-STD-202
Resistance Temperature Characteristics (TCR)	MIL-PRF-55342
Short Time Overload	MIL-PRF-55342
High Temperature Exposure	MIL-PRF-55342
Thermal Shock	MIL-PRF-55342 MIL-STD-202
Resistance to Bonding Exposure	MIL-PRF-55342
Wire Bonding Integrity	MIL-PRF-55342
Life Test	MIL-PRF-55342 MIL-STD-202


λ Performance Specifications

Higher power ratings, additional sizes, and custom resistors available. Please contact sales@passiveplus.com.



Spiral Inductors

PPI Spiral Inductors consist of a thin film gold spiral patterned on a substrate for use in a wide variety of uses, including storing electrical energy in the form of magnetic energy, in frequencies from DC to RF.



50x50 Spiral Inductor

An optional polyimide coating over the coil is available for increased resistance to scratches or shorts. Non-conductive epoxy is recommended as a mounting method, backside metallization is also available. A second corner pad is provided for easy wire-bonding from the center pad for edge-contact mounting.

Product Features

- High Thermal Conductivity
- Low Thermal Resistance
- Low Capacitance
- Less Resistive & Capacitive losses
- RoHS Compliant
- EIA case sizes
- More efficient thermal management


Applications

- Microwave Circuit Resonant elements
- Electrical Power & Electronic Devices

Functional Applications

- Choking, Blocking, Attenuating, or filtering/smoothing high frequency noise
- Storing & transferring energy in power converters
- Creates tuned oscillators or LC “tank” circuits
- Impedance matching

Part Numbering




Other inductance values, DC resistance values, substrates, geometries, metallizations, and custom inductors are available.



Parts Characterizations

Case Size (Mils)	Inductances	# of Turns	DC Resistance	Q (@ 200MHz)	Q (@ 500MHz)
25 x 25	1.2 nH	1.5	0.6Ω	3	7
25 x 25	2.0 nH	2.0	0.9Ω	3	8
25 x 25	3.0 nH	2.5	1.2Ω	4	9
30 x 30	4.4 nH	3.0	1.5Ω	4	10
30 x 30	6.0 nH	3.5	1.9Ω	4	11
30 x 30	7.9 nH	4.0	2.3Ω	4	11
40 x 40	10 nH	4.5	2.7Ω	5	12
40 x 40	13 nH	5.0	3.2Ω	5	12
40 x 40	16 nH	5.5	3.7Ω	5	13
40 x 40	19 nH	6.0	4.2Ω	6	13
40 x 40	23 nH	6.5	4.7Ω	6	14
50 x 50	28 nH	7.0	5.3Ω	7	14



50x50 Spiral Inductor



Substrates

Code	Substrate
20	Quartz
35	99.6% Alumina (Al ₂ O ₃)



Metallizations

Metallization		Code	Note
Top Side	Bottom Side		
Ta/Pd/Au	—	A	Wirebondable
Ta/Pd/Au	Ta/Pd/Au	D	Wirebond or Epoxy

Other metallizations available. Please contact PPI.



Inductance Codes

Inductance (nH)
Digits 1-4 are significant figures
The "R" is used as a decimal point.
e.g. 28R0 = 28nH, 1R50 = 1.5nH

Inductance values are computed in free air, using a magnetic permeability for free air of $\mu = 4.0 \times 10^{-7}$. DC resistance is based on a gold metallization.



Protective Coating

Code	Polyimide Coating
B	Without Coating
P	With Polyimide Coating



Packaging

Code	Style
W	Waffle Pack (Standard)
G	Gel Pack

All parts are supplied in waffle packs. Other packaging may be available. Contact PPI for additional packaging options.




Thin Film Products

Spiral Inductors

General Properties

Operating Temperature	-55°C to +150°C
Storage Temperature	-65°C to +150°C
Operating Frequency	DC to 500 MHz
Insulation Resistance	10 ¹² Ω · min at 25°C




50x50 Spiral Inductor

Testing

Testing Performed	Specification / Standard
Visual Inspection	MIL-PRF-55342 MIL-STD-883
Mechanical Inspection	MIL-PRF-55342
DC Resistance	MIL-PRF-55342 MIL-STD-202
High Temperature Exposure	MIL-PRF-55342
Thermal Shock	MIL-PRF-55342 MIL-STD-202
Resistance to Bonding Exposure	MIL-PRF-55342
Wire Bonding Integrity	MIL-PRF-55342
Life Test	MIL-PRF-55342 MIL-STD-202


Performance Specifications

Additional sizes and custom inductors available. Please contact sales@passiveplus.com.






Single Layer Capacitors




≠ Product Features

PPI offers Standard Edge to Edge SLC with tight tolerances to the required size, shape and value. Thicknesses of up to 25+ mils are available utilizing temperature-stable low-loss materials and special terminations to improve the all solder process. Chip size, shape and electrical properties may be determined from the dielectric material.



- Capacitance: 0.04 to 10,000pF
- Square or rectangle, length or width .005" and up

≠ Part Numbering



≠ Substrates

Substrates can be supplied as follows:

- **Bare**
- **Metallized:**
 - Gold over Platinum, Palladium, or Nickel
 - Silver over Platinum
 - Custom schemes and patterns to Customer specifications

Thickness Range 3 mils +

Length and Width Up to 4" depending on material

≠ Standard Electrode Metallizations

Gold (D4) This metallization consists of a minimum of 70 micro-inches of Gold over Platinum or Nickel which is ideal for all wirebonding methodologies.

Silver (S7) This metallization consists of 20 micro-inches of Silver over Platinum which is ideal for all solder applications whenever the use of Gold is unacceptable.




≠ Metallization Codes

Code	Description
D4	Ti/Pt/Au Titanium/Platinum/Gold (70 μin Gold)
S7	Ti/Pt/Ag Titanium/Platinum/Silver (20 μin Silver)
K2	Ta/Pd/Au Tantalum/Palladium/Gold (75 μin Gold)
L3	Ta/Pd/Au Tantalum/Palladium/Gold (100 μin Gold)

Contact PPI for available metallizations.

≠ Capacitance Codes

Value	Code
<10pF	1R0 = 1.0pF
>10pF	101 = 100pF



≠ Capacitance Tolerance & Dimensional Tolerances Codes

Class I Dielectrics: AS1 - KS2			
Tolerance	Code	Tolerance	Code
± .50pF	D	± 20%	M
± .25pF	C	± 15%	L
± .10pF	B	± 10%	K
± .05pF	A	± 5%	J
± .01pF	P	± 3%	H
		± 2%	G

Class II Dielectrics: MS1 - ZS4			
Tolerance	Code	Tolerance	Code
-10% thru +40%	Y	± 20%	M
-20% thru +80%	Z	± 15%	L
0% thru +100%	V	± 10%	K
Guaranteed Min. Value	GMV	± 5%	J

Material	L or W Dimension	Tolerance
AS1 - ZS1	< 20 mils	±15%
	≥ 20 mils	±10%

Material	L or W Dimension	Tolerance
ZS4 - ZS6	≤ 15 mils	± 2 mils
	> 15 mils; ≤ 30 mils	± 3 mils
	> 30 mils	± 5 mils

≠ Rated Voltage Codes

Code	Voltage	Dielectric Thickness
2	50V	4 mils
3	100V	6 mils

≠ Packaging

PPI SLCs are available in Waffle Packs (Standard).
Other packaging options may be available.
Please contact PPI.

**≠ Dielectric Materials – Class I**

Dielectrics below consist of material exhibiting very low losses, extremely low or closely controlled temperature coefficients, negligible voltage and frequency coefficients, negligible aging effects and high insulation and dielectric breakdown.

Type	IR Min @ 25°C	Temperature Coefficient (-25 to 125°C)	Dissipation Factor (@ 10GHz)	Dielectric Constant (K)	Material
AS1	10 ¹²	Negligible	0.0001	3.8	Quartz
AS2	10 ¹²	Negligible	0.0001	3.9	Si
AS3	10 ¹²	Negligible	0.0001	6.6	BeO
AS6	10 ¹²	P120 ± 25ppm	0.0001	8.7	AlN
AS7	10 ¹²	P180 ± 50ppm	0.0006	9.6	Alumina 96
AS8	10 ¹²	P180 ± 50ppm	0.0006	9.8	Alumina 99.6
BS2	10 ¹²	NP0 ± 30ppm	0.0001	12.6	Titanate
CS1	10 ¹²	0 ± 30ppm	0.001	20	Titanate
ES1	10 ¹²	0 ± 30ppm	0.002	40	Titanate
FS1	10 ¹²	0 ± 30ppm	0.005	50	Titanate
IS1	10 ¹⁵	0 ± 30ppm	0.005	84	Titanate
KS3	10 ⁶	N1500 ± 500ppm	0.0025	160	Titanate

**± Dielectric Materials – Class II**

Dielectrics below are characterized by high dielectric constants, increased losses and higher temperature coefficients. These properties are inherent with this class of material but the high dielectric constants permit the use of smaller size to achieve low series inductance and meet dimensional requirements. Capacitors made with these materials are often used for coupling of microstrip line circuits where a small chip is necessary. Used as a bypass capacitor, the small size provides low series inductance and dielectric losses are typically of little concern.

Type	IR (MEG-OHMs) 100VDC @ 25°C	Temperature Coefficient (-55 to 125°C)	Dissipation Factor (@ 1 MHz)	Aging (%) HR/Decade	Dielectric Constant (K)
MS1	10 ⁵	5 to -10	0.010	2.0	300
PS1	10 ⁴	± 10%	0.025	3.0	700
SS3	10 ⁵	3 to -10	0.015	3.5	2,200
US1	10 ⁵	0 to -35	0.020	3.0	4,000
US3	10 ⁵	3.0	0.025	3.0	5,000
RS2	10 ⁴	± 10%	0.025	3.0	1250
ZS1	10 ⁵	0 to -80	0.025	3.0	11,000
ZS4	Contact PPI	15 to -15	0.035	3.0	25,000
ZS6	Contact PPI	15 to -15	0.035	3.0	35,000
US3	10 ⁵	± 15%	0.030	3.0	4500



± Capacitance, Case Size & Dielectric Availability - Class I Dielectrics

Cap (pF)	Size mils (mm)																	
	10x10		12x12		15x15		20x20		25x25		30x30		35x35		40x40		50x50	
	(.254 x .254)		(.305 x .305)		(.381 x .381)		(.508 x .508)		(.635 x .635)		(.762 x .762)		(.889 x .889)		(1.016 x 1.016)		(1.270 x 1.270)	
	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness
0.04	AS7	5	AS7	6	AS7	10												
0.06	AS7	4	AS7	5	AS7	8	AS2	5	AS2	10								
0.08	ES1	10	AS7	4	AS7	6	AS7	10	AS2	7	AS2	9						
0.1	ES1	8	ES1	11	AS7	5	AS7	9	AS2	5	AS2	7	AS2	10				
0.2	ES1	5	ES1	7	ES1	10	AS7	4	AS7	7	AS7	10	AS2	5	AS2	7	AS2	10
0.3	IS1	6	ES1	4	ES1	6	ES1	11	AS7	4	AS7	7	AS7	9	AS2	5	AS2	7
0.4	IS1	5	IS1	7	ES1	5	ES1	9	ES1	15	AS7	5	AS7	7	AS7	9	AS2	5
0.5	IS1	4	IS1	5	ES1	4	ES1	7	ES1	11	AS7	5	AS7	5	AS7	7	AS2	4
0.6	KS2	6	IS1	5	IS1	7	ES1	6	ES1	10	ES1	15	AS7	4	AS7	6	AS7	9
0.8	MS1	8	KS2	6	IS1	5	ES1	5	ES1	7	ES1	10	ES1	15	AS7	4	AS7	7
1.0	MS1	7	KS2	5	IS1	4	IS1	7	ES1	6	ES1	8	ES1	10	AS7	4	AS7	5
1.2	MS1	6	KS2	4	IS1	4	IS1	6	ES1	5	ES1	7	ES1	9	AS7	3	AS7	5
1.5	MS1	5	MS1	7	KS2	5	IS1	5	ES1	4	ES1	6	ES1	7	ES1	10	AS7	4
1.8	MS1	4	MS1	5	KS2	4	IS1	4	IS1	6	ES1	5	ES1	6	ES1	8	ES1	11
2.0	MS1	4	MS1	5	KS2	4	KS2	7	IS1	6	ES1	4	ES1	5	ES1	7	ES1	11
2.2	RS1	4	MS1	5	KS2	4	KS2	6	IS1	5	IS1	7	ES1	5	ES1	7	ES1	10
2.7	RS1	8	MS1	4	MS1	6	KS2	5	IS1	4	IS1	6	ES1	4	ES1	5	ES1	8
3.3	RS1	7	RS1	10	MS1	5	KS2	4	KS2	6	IS1	5	IS1	7	ES1	4	ES1	7
3.9	RS1	6	RS1	9	MS1	4	MS1	7	KS2	5	IS1	4	IS1	6	IS1	8	ES1	6
4.7	RS1	5	RS1	7	RS1	11	MS1	6	KS2	4	KS2	6	IS1	5	IS1	6	ES1	5
5.6	RS1	4	RS1	6	RS1	10	MS1	5	MS1	7	KS2	5	IS1	4	IS1	5	ES1	4
6.8	RS1	4	RS1	5	RS1	8	MS1	4	MS1	6	KS2	5	KS2	6	IS1	4	IS1	7
8.2	SS3	6	RS1	4	RS1	7	MS1	4	MS1	5	KS2	4	KS2	5	KS2	7	KS2	10
10	SS3	5	RS1	4	RS1	5	RS1	9	MS1	4	MS1	6	KS2	4	KS2	5	KS2	8
12	SS3	4	SS3	6	RS1	5	RS1	8	RS1	11	MS1	5	MS1	7	KS2	4	KS2	7
15	US1	6	SS3	5	RS1	4	RS1	6	RS1	10	MS1	4	MS1	6	MS1	7	KS2	6
18	US1	5	SS3	4	SS3	6	RS1	5	RS1	8	RS1	11	MS1	4	MS1	6	KS2	5
20	US1	5	SS3	4	SS3	6	RS1	5	RS1	8	RS1	11	MS1	4	MS1	5	KS2	4
22	US1	4	US1	6	SS3	5	RS1	4	RS1	7	RS1	9	MS1	4	MS1	5	KS2	4





Shaded cells indicate Class II Dielectrics



≠ Capacitance, Case Size & Dielectric Availability – Class II Dielectrics

Cap (pF)	Size mils (mm)																	
	10x10 (.254 x .254)		12x12 (.305 x .305)		15x15 (.381 x .381)		20x20 (.508 x .508)		25x25 (.635 x .635)		30x30 (.762 x .762)		35x35 (.889 x .889)		40x40 (1.016 x 1.016)		50x50 (1.270 x 1.270)	
	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness												
27	US1	4	US1	5	SS3	4	RS1	4	RS1	6	RS1	8	MS1	3	MS1	4	MS1	6
33	VS1	4	US1	4	US1	6	SS3	6	RS1	5	RS1	6	RS1	11	MS1	4	MS1	5
39	ZS1	6	US1	4	US1	5	SS3	5	RS1	4	RS1	5	RS1	7	RS1	10	MS1	4
47	ZS1	5	ZS1	7	US1	5	SS3	4	SS3	6	RS1	5	RS1	6	RS1	8	MS1	4
56	ZS1	4	ZS1	6	VS1	5	US1	7	SS3	5	RS1	4	RS1	5	RS1	7	RS1	10
68	ZS1	4	ZS1	5	VS1	4	US1	6	SS3	5	SS3	6	RS1	4	RS1	6	RS1	9
82	ZS4	7	ZS1	4	ZS1	7	VS1	6	SS3	4	SS3	5	SS3	7	SS3	10	RS1	7
100	ZS4	6	ZS4	8	ZS1	6	VS1	5	US1	6	SS3	5	SS3	6	SS3	8	RS1	6
120	ZS4	5	ZS4	7	ZS1	5	ZS1	8	VS1	6	SS3	4	SS3	5	SS3	7	RS1	5
150	ZS4	4	ZS4	5	ZS1	4	ZS1	7	VS1	5	VS1	7	SS3	4	SS3	5	RS1	4
180	ZS6	4	ZS4	5	ZS4	7	ZS1	6	VS1	4	VS1	6	VS1	8	US1	8	SS3	7
200	ZS6	4	ZS4	4	ZS4	6	ZS1	5	ZS1	8	VS1	5	VS1	7	US1	7	SS3	6
220	ZS6	4	ZS6	5	ZS4	6	ZS1	4	ZS1	7	VS1	5	VS1	6	US1	6	SS3	6
270			ZS6	4	ZS4	5	ZS4	8	ZS1	6	VS1	4	VS1	5	US1	5	SS3	5
330					ZS4	4	ZS4	7	ZS1	5	ZS1	7	VS1	4	US1	4	US1	7
390					ZS6	4	ZS4	6	ZS1	4	ZS1	6	ZS1	7	ZS1	10	US1	6
470					ZS6	4	ZS4	5	ZS4	7	ZS1	5	ZS1	6	ZS1	8	US1	5
560							ZS4	4	ZS4	6	ZS1	4	ZS1	5	ZS1	7	US1	4
680							ZS6	5	ZS4	5	ZS4	8	ZS1	5	ZS1	6	VS1	4
820							ZS6	4	ZS6	6	ZS4	6	ZS1	4	ZS1	5	ZS1	7
1000									ZS6	5	ZS4	5	ZS4	7	ZS1	4	ZS1	6
1200									ZS6	4	ZS4	4	ZS4	6	ZS4	7	ZS1	5
1500											ZS6	5	ZS4	5	ZS4	6	ZS1	4
1800											ZS6	4	ZS6	6	ZS4	5	ZS4	8
2200													ZS6	5	ZS4	4	ZS4	6
2700													ZS6	4	ZS6	5	ZS4	5
3300																	ZS6	6

⊕ Typical Temperature Characteristics






≠ Product Features


Border Caps have the topside electrode withdrawn from the edges in order to increase the distance between electrodes and dramatically decrease the possibilities of shorting when epoxy die-mounting. This style is also widely used for optical recognition-based assembly.



Increased margin sizes and special terminations are available for high power LC filter applications. Border Caps can be customized to any sized square or rectangle. Contact PPI for more information.



≠ Part Numbering



≠ Thicknesses (mils)

Length & Width	L or W Tolerance	Margin Nominal	Thickness
≤ .010	± .002	0.001	± .0015
.011 - .029	± .002	0.002	
≥ .030	± .003	0.002	

All dimensions given are inches

≠ Metallization Codes

Code	Description
D4	Ti/Pt/Au Titanium/Platinum/Gold (70 μin Gold)
S7	Ti/Pt/Ag Titanium/Platinum/Silver (20 μin Silver)
K2	Ta/Pd/Au Tantalum/Palladium/Gold (75 μin Gold)
L3	Ta/Pd/Au Tantalum/Palladium/Gold (100 μin Gold)

Contact PPI for available metallizations.



≠ Substrates

Substrates can be supplied as follows:

- **Bare**
- **Metallized:**
 - Gold over Platinum, Palladium, or Nickel
 - Silver over Platinum
 - Custom schemes and patterns to Customer specifications

Thickness Range 3 mils +

Length and Width Up to 4” depending on material

≠ Standard Electrode Metallizations

Gold (D4) This metallization consists of a minimum of 70 micro-inches of Gold over Platinum or Nickel which is ideal for all wirebonding methodologies.

Silver (S7) This metallization consists of 20 micro-inches of Silver over Platinum which is ideal for all solder applications whenever the use of Gold is unacceptable.

≠ Capacitance Tolerance Codes

Class I Dielectrics: AS1 - KS2			
Tolerance	Code	Tolerance	Code
± .50pF	D	± 20%	M
± .25pF	C	± 15%	L
± .10pF	B	± 10%	K
± .05pF	A	± 5%	J
± .01pF	P	± 3%	H
		± 2%	G

Class II Dielectrics: MS1 – ZS6			
Tolerance	Code	Tolerance	Code
-10% thru +40%	Y	± 20%	M
-20% thru +80%	Z	± 15%	L
0% thru +100%	V	± 10%	K
Guaranteed Min. Value	GMV	± 5%	J

≠ Capacitance Codes

Value	Code
<10pF	1R0 = 1.0pF
>10pF	101 = 100pF

≠ Rated Voltage Codes

Code	Voltage	Dielectric Thickness
2	50V	4 mils
3	100V	6 mils

≠ Packaging

PPI SLCs are available in Waffle Packs (Standard). Other packaging options may be available. Please contact PPI.

≠ Dielectric Materials – Class I

Dielectrics below consist of material exhibiting very low losses, extremely low or closely controlled temperature coefficients, negligible voltage and frequency coefficients, negligible aging effects and high insulation and dielectric breakdown.

Type	IR Min @ 25°C	Temperature Coefficient (-25 to 125°C)	Dissipation Factor (@ 10GHz)	Dielectric Constant (K)	Material
AS1	10 ¹²	Negligible	0.0001	3.8	Quartz
AS2	10 ¹²	Negligible	0.0001	3.9	Si
AS3	10 ¹²	Negligible	0.0001	6.6	BeO
AS6	10 ¹²	P120 ± 25ppm	0.0001	8.7	AlN
AS7	10 ¹²	P180 ± 50ppm	0.0006	9.6	Alumina 96
AS8	10 ¹²	P180 ± 50ppm	0.0006	9.8	Alumina 99.6
BS2	10 ¹²	NP0 ± 30ppm	0.0001	12.6	Titanate
CS1	10 ¹²	0 ± 30ppm	0.001	20	Titanate
ES1	10 ¹²	0 ± 30ppm	0.002	40	Titanate
FS1	10 ¹²	0 ± 30ppm	0.005	50	Titanate
IS1	10 ¹⁵	0 ± 30ppm	0.005	84	Titanate
KS3	10 ⁶	N1500 ± 500ppm	0.0025	160	Titanate

± Dielectric Materials – Class II

Dielectrics below are characterized by high dielectric constants, increased losses and higher temperature coefficients. These properties are inherent with this class of material but the high dielectric constants permit the use of smaller size to achieve low series inductance and meet dimensional requirements. Capacitors made with these materials are often used for coupling of microstrip line circuits where a small chip is necessary. Used as a bypass capacitor, the small size provides low series inductance and dielectric losses are typically of little concern.

Type	IR (MEG-OHMs) 100VDC @ 25°C	Temperature Coefficient (-55 to 125°C)	Dissipation Factor (@ 1 MHz)	Aging (%) HR/Decade	Dielectric Constant (K)
MS1	10 ⁵	5 to -10	0.010	2.0	300
PS1	10 ⁴	± 10%	0.025	3.0	700
SS3	10 ⁵	3 to -10	0.015	3.5	2,200
US1	10 ⁵	0 to -35	0.020	3.0	4,000
US3	10 ⁵	3.0	0.025	3.0	5,000
RS2	10 ⁴	± 10%	0.025	3.0	1250
ZS1	10 ⁵	0 to -80	0.025	3.0	11,000
ZS4	Contact PPI	15 to -15	0.035	3.0	25,000
ZS6	Contact PPI	15 to -15	0.035	3.0	35,000
US3	10 ⁵	± 15%	0.030	3.0	4500



≠ Capacitance, Case Size & Dielectric Availability - Class I Dielectrics

Cap (pF)	Size mils (mm)																	
	10x10 (.254 x .254)		12x12 (.305 x .305)		15x15 (.381 x .381)		20x20 (.508 x .508)		25x25 (.635 x .635)		30x30 (.762 x .762)		35x35 (.889 x .889)		40x40 (1.016 x 1.016)		50x50 (1.270 x 1.270)	
	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness												
0.04	AS7	4	AS7	4	AS7	5	AS1	5										
0.06	ES1	10	AS7	4	AS7	6	AS1	5	AS1	8	AS1	10						
0.08	ES1	7	ES1	10	AS7	5	AS7	10	AS1	6	AS1	8	AS1	11				
0.1	ES1	6	ES1	9	AS7	4	AS7	7	AS1	5	AS1	7	AS1	10				
0.2	IS1	4	ES1	4	ES1	5	AS7	4	AS7	5	AS7	7	AS1	4	AS1	5	AS1	10
0.3	KS2	6	IS1	5	ES1	4	ES1	8	AS7	4	AS7	5	AS7	7	AS1	4	AS1	6
0.4	KS2	4	IS1	4	IS1	6	ES1	6	ES1	10	AS7	4	AS7	5	AS7	7	AS1	5
0.5	MS1	5	KS2	4	IS1	5	ES1	4	ES1	7	ES1	10	AS7	4	AS7	6	AS7	10
0.6	MS1	5	KS2	5	IS1	4	ES1	4	ES1	6	ES1	10	AS7	4	AS7	5	AS7	7
0.8	MS1	5	MS1	5	KS2	5	IS1	6	ES1	5	ES1	7	ES1	10	AS7	4	AS7	6
1.0	MS1	4	MS1	5	KS2	4	IS1	5	ES1	4	ES1	6	ES1	8	ES1	10	AS7	5
1.2	RS1	6	MS1	5	MS1	7	IS1	4	IS1	7	ES1	5	ES1	7	ES1	10	AS7	4
1.5	RS1	7	MS1	4	MS1	6	KS2	6	IS1	6	IS1	8	ES1	6	ES1	7	ES1	15
1.8	RS1	6	MS1	4	MS1	5	KS2	5	IS1	5	IS1	7	ES1	5	ES1	7	ES1	10
2.0	RS1	6	RS1	8	MS1	4	KS2	5	IS1	5	IS1	6	ES1	4	ES1	6	ES1	10
2.2	RS1	5	RS1	7	MS1	4	MS1	7	KS2	7	IS1	6	ES1	4	ES1	5	ES1	10
2.7	RS1	5	RS1	6	MS1	4	MS1	6	KS2	6	IS1	6	IS1	8	ES1	5	ES1	8
3.3	SS3	6	RS1	6	RS1	8	MS1	5	KS2	5	IS1	4	IS1	6	IS1	7	ES1	6
3.9	SS3	5	RS1	5	RS1	7	MS1	4	KS2	4	KS2	6	IS1	5	IS1	6	ES1	5
4.7	SS3	5	RS1	5	RS1	7	MS1	4	MS1	6	KS2	5	IS1	4	IS1	5	IS1	8
5.6	SS3	5	SS3	6	RS1	5	MS1	4	MS1	5	KS2	4	KS2	6	IS1	5	IS1	7
6.8	US1	5	SS3	6	RS1	5	RS1	8	MS1	5	MS1	7	KS2	5	KS2	7	IS1	6
8.2	US1	4	SS3	5	RS1	4	RS1	7	MS1	4	MS1	6	KS2	4	KS2	5	IS1	5
10	US1	5	SS3	4	SS3	6	RS1	6	MS1	4	MS1	5	MS1	6	KS2	5	IS1	4
12	US1	5	US1	6	SS3	5	RS1	5	RS1	8	MS1	4	MS1	6	KS2	4	KS2	6
15	US1	4	US1	5	SS3	5	RS1	5	RS1	7	MS1	4	MS1	5	MS1	6	KS2	5
18	VS1	4	VS1	6	US1	7	SS3	7	RS1	5	RS1	9	MS1	4	MS1	5	KS2	4
20	ZS1	5	VS1	5	US1	6	SS3	6	RS1	5	RS1	8	MS1	4	MS1	5	KS2	4

Class I Dielectrics





Shaded cells indicate Class II Dielectrics



± Capacitance, Case Size & Dielectric Availability – Class II Dielectrics

Cap (pF)	Size mils (mm)																	
	10x10		12x12		15x15		20x20		25x25		30x30		35x35		40x40		50x50	
	(.254 x .254)		(.305 x .305)		(.381 x .381)		(.508 x .508)		(.635 x .635)		(.762 x .762)		(.889 x .889)		(1.016 x 1.016)		(1.270 x 1.270)	
	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness
22	ZS1	7	VS1	4	US1	5	SS3	6	RS1	5	RS1	7	RS1	10	MS1	4	MS1	6
27	ZS1	6	VS1	4	VS1	5	SS3	5	RS1	4	RS1	6	RS1	8	MS1	4	MS1	5
33	ZS1	5	ZS1	6	VS1	4	SS3	4	SS3	6	RS1	5	RS1	7	RS1	9	MS1	5
39	ZS1	4	ZS1	5	VS1	4	US1	6	SS3	6	RS1	4	RS1	6	RS1	8	MS1	4
47	ZS4	8	ZS1	5	ZS1	6	US1	5	SS3	5	SS3	7	RS1	5	RS1	7	RS1	11
56	ZS4	6	ZS1	4	ZS1	5	VS1	5	SS3	4	SS3	6	RS1	4	RS1	6	RS1	9
68	ZS4	5	ZS4	8	ZS1	5	VS1	4	US1	6	SS3	5	RS1	4	RS1	5	RS1	7
82	ZS6	6	ZS4	6	ZS1	4	VS1	4	US1	5	SS3	4	SS3	6	RS1	4	RS1	6
100	ZS6	5	ZS4	6	ZS1	4	ZS1	6	VS1	5	US1	6	SS3	5	SS3	7	RS1	5
120			ZS4	5	ZS4	6	ZS1	5	VS1	4	VS1	6	SS3	4	SS3	5	RS1	4
150			ZS4	6	ZS4	6	ZS1	4	ZS1	7	VS1	5	VS1	7	SS3	4	SS3	7
180			ZS6	5	ZS4	5	ZS1	4	ZS1	6	VS1	4	VS1	6	SS3	4	SS3	6
200					ZS6	5	ZS1	4	ZS1	6	VS1	4	VS1	5	US1	6	SS3	5
220					ZS6	5	ZS4	8	ZS1	5	VS1	4	VS1	5	US1	5	SS3	5
270					ZS6	5	ZS4	6	ZS1	4	ZS1	7	VS1	4	VS1	6	SS3	4
330							ZS4	5	ZS1	4	ZS1	5	ZS1	7	VS1	5	US1	6
390							ZS4	5	ZS4	6	ZS1	5	ZS1	6	VS1	4	US1	5
470							ZS4	4	ZS4	6	ZS1	4	ZS1	5	ZS1	7	VS1	5
560							ZS6	5	ZS6	6	ZS1	4	ZS1	5	ZS1	6	VS1	4
680									ZS6	6	ZS4	6	ZS1	4	ZS1	5	ZS1	8
820									ZS6	5	ZS4	5	ZS4	8	ZS1	4	ZS1	7
1000											ZS6	6	ZS4	6	ZS4	8	ZS1	6
1200											ZS6	5	ZS4	5	ZS4	7	ZS1	5
1500													ZS6	6	ZS4	5	ZS1	4
1800													ZS6	5	ZS6	6	ZS4	7
2200															ZS6	5	ZS4	6
2700															ZS6	5	ZS4	5
3300																	ZS6	5

⊕ Typical Temperature Characteristics




≠ Product Features

A single full electrode is provided on one side of the capacitor and split electrodes on the other side. This is a three-terminal capacitor which can be used as a two capacitor with a common electrode or as serially connected capacitors so that connections may be made on one side of the chip only (surface mount). This design is often used in microstrip coupling to eliminate lead inductance and raise the self resonant frequency.




≠ Product Characteristics

- Capacitance: 0.06 picofarads and up
- Chip shape: Twin pads with gap
- Gap widths: 5, 10, 15, 20 mil or custom



Standard dimensional tolerance for length and width is $\pm 15\%$ up to 20 mils. For dimensions greater than 20 mils, standard tolerance is $\pm 10\%$. In cases where dimension cannot be exceeded, insert "M" to signify a maximum dimension. The thickness tolerance is ± 1.5 mils.

≠ Part Numbering





⚡ Substrates

Substrates can be supplied as follows:

- **Bare**
- **Metallized:**
 - Gold over Platinum, Palladium, or Nickel
 - Silver over Platinum
 - Custom schemes and patterns to Customer specifications

Thickness Range 3 mils +

⚡ Standard Electrode Metallizations

Gold (D4) This metallization consists of a minimum of 70 micro-inches of Gold over Platinum or Nickel which is ideal for all wirebonding methodologies.

Silver (S7) This metallization consists of 20 micro-inches of Silver over Platinum which is ideal for all solder applications whenever the use of Gold is unacceptable.

⚡ Capacitance Tolerance Codes

Class I Dielectrics: AS1 - KS2

Tolerance	Code
± 20%	M
± 15%	L
± 10%	K
± 5%	J

Class II Dielectrics: MS1 – ZS6

Tolerance	Code	Tolerance	Code
-10% thru +40%	Y	± 20%	M
-20% thru +80%	Z	± 15%	L
0% thru +100%	V	± 10%	K
Guaranteed Min. Value	GMV		

⚡ Metallization Codes

Code	Description
D4	Ti/Pt/Au Titanium/Platinum/Gold (70 μin Gold)
S7	Ti/Pt/Ag Titanium/Platinum/Silver (20 μin Silver)
K2	Ta/Pd/Au Tantalum/Palladium/Gold (75 μin Gold)
L3	Ta/Pd/Au Tantalum/Palladium/Gold (100 μin Gold)

Contact PPI for available metallizations.

⚡ Capacitance Codes

Value	Code
<10pF	1R0 = 1.0pF
>10pF	101 = 100pF

⚡ Rated Voltage Codes

Code	Voltage	Dielectric Thickness
2	50V	4 mils
3	100V	6 mils

⚡ Packaging

PPI SLCs are available in Waffle Packs (Standard). Other packaging options may be available. Please contact PPI.

Twin Caps are available in a wide range of size configurations, dielectric and termination materials to fit your application. Please contact PPI for designs not listed in this catalog.

≠ Dielectric Materials – Class I

Dielectrics below consist of material exhibiting very low losses, extremely low or closely controlled temperature coefficients, negligible voltage and frequency coefficients, negligible aging effects and high insulation and dielectric breakdown.

Type	IR Min @ 25°C	Temperature Coefficient (-25 to 125°C)	Dissipation Factor (@ 10GHz)	Dielectric Constant (K)	Material
AS1	10 ¹²	Negligible	0.0001	3.8	Quartz
AS2	10 ¹²	Negligible	0.0001	3.9	Si
AS3	10 ¹²	Negligible	0.0001	6.6	BeO
AS6	10 ¹²	P120 ± 25ppm	0.0001	8.7	AlN
AS7	10 ¹²	P180 ± 50ppm	0.0006	9.6	Alumina 96
AS8	10 ¹²	P180 ± 50ppm	0.0006	9.8	Alumina 99.6
BS2	10 ¹²	NP0 ± 30ppm	0.0001	12.6	Titanate
CS1	10 ¹²	0 ± 30ppm	0.001	20	Titanate
ES1	10 ¹²	0 ± 30ppm	0.002	40	Titanate
FS1	10 ¹²	0 ± 30ppm	0.005	50	Titanate
IS1	10 ¹⁵	0 ± 30ppm	0.005	84	Titanate
KS3	10 ⁶	N1500 ± 500ppm	0.0025	160	Titanate

⚡ Dielectric Materials – Class II

Dielectrics below are characterized by high dielectric constants, increased losses and higher temperature coefficients. These properties are inherent with this class of material but the high dielectric constants permit the use of smaller size to achieve low series inductance and meet dimensional requirements. Capacitors made with these materials are often used for coupling of microstrip line circuits where a small chip is necessary. Used as a bypass capacitor, the small size provides low series inductance and dielectric losses are typically of little concern.

Type	IR (MEG-OHMs) 100VDC @ 25°C	Temperature Coefficient (-55 to 125°C)	Dissipation Factor (@ 1 MHz)	Aging (%) HR/Decade	Dielectric Constant (K)
MS1	10 ⁵	5 to -10	0.010	2.0	300
PS1	10 ⁴	± 10%	0.025	3.0	700
SS3	10 ⁵	3 to -10	0.015	3.5	2,200
US1	10 ⁵	0 to -35	0.020	3.0	4,000
US3	10 ⁵	3.0	0.025	3.0	5,000
RS2	10 ⁴	± 10%	0.025	3.0	1250
ZS1	10 ⁵	0 to -80	0.025	3.0	11,000
ZS4	Contact PPI	15 to -15	0.035	3.0	25,000
ZS6	Contact PPI	15 to -15	0.035	3.0	35,000
US3	10 ⁵	± 15%	0.030	3.0	4500



± Capacitance, Case Size & Dielectric Availability

Capacitance (pF)	Case Size							
	Mils (mm)							
	20x10 (.508 x .254)		40x20 (1.016 x .508)		60x30 (1.524 x .762)		80x40 (2.032 x 1.016)	
	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness
	Class I Dielectrics							
0.06	ES1	6	AS7	6	AS1	6	AS1	8
0.08	ES1	4	AS7	4	AS1	4	AS1	7
0.1	IS1	7	ES1	15	AS7	8	AS1	5
0.2	KS3	6	ES1	7	AS7	4	AS7	7
0.3	MS1	8	ES1	5	ES1	10	AS7	4
0.4	MS1	6	IS1	7	ES1	8	ES1	15
0.5	MS1	5	IS1	6	ES1	7	ES1	10
0.6	MS1	4	IS1	5	ES1	6	ES1	9
0.8	PS1	11	KS3	6	IS1	4	ES1	7
1	PS1	9	KS3	5	IS1	7	ES1	6
1.2	PS1	7	KS3	4	IS1	6	ES1	5
1.5	PS1	6	MS1	7	IS1	5	IS1	8
1.8	PS1	5	MS1	6	IS1	4	IS1	6
2	PS1	4	MS1	5	IS1	4	IS1	6
2.2	PS1	4	MS1	5	KS3	6	IS1	5
2.7	SS3	7	MS1	4	KS3	5	IS1	4
3.3	SS3	6	PS1	11	KS3	4	KS3	6
3.9	SS3	5	PS1	9	MS1	7	KS3	5
4.7	SS3	4	PS1	8	MS1	5	KS3	4
5.6	US1	6	PS1	6	MS1	5	MS1	7
6.8	US1	5	PS1	5	MS1	4	MS1	6
8.2	US3	5	PS1	4	PS1	11	MS1	5
10	US3	4	SS3	7	PS1	9	MS1	4
12	ZS1	8	SS3	6	PS1	7	PS1	11





Capacitance, Case Size & Dielectric Availability chart continues on the next page.



≠ Capacitance, Case Size & Dielectric Availability - continued

15	ZS1	6	SS3	5	PS1	6	PS1	9
18	ZS1	5	SS3	4	PS1	5	PS1	8
20	ZS1	5	US1	7	PS1	4	PS1	7
22	ZS1	4	US1	6	PS1	4	PS1	6
27	ZS4	8	US1	5	SS3	7	PS1	5
33	ZS4	6	US3	5	SS3	6	SS3	9
39	ZS4	5	US3	4	SS3	5	SS3	8
47	US3	6	ZS1	8	SS3	4	SS3	6
56	US3	5	ZS1	7	US1	6	SS3	5
68	US3	4	ZS1	5	US1	5	US1	8
82			ZS1	4	US3	5	US3	8
100			ZS4	8	US3	4	US3	7
120			ZS4	7	ZS1	8	US3	6
150			ZS4	5	ZS1	6	US3	5
180			ZS4	5	ZS1	5	ZS1	8
200			ZS6	6	ZS1	5	ZS1	7
220			ZS6	5	ZS4	9	ZS1	7
270			ZS6	4	ZS4	8	ZS1	6
330					ZS4	6	ZS1	5
390					ZS4	5	ZS4	9
470					ZS6	6	ZS4	7
560					ZS6	5	ZS4	6
680					ZS6	4	ZS4	5
820							ZS6	6
1000							ZS6	5
1200							ZS6	4
Class II Dielectrics								

⊕ Typical Temperature Characteristics




≠ Product Features

Array Caps are used where arrays of capacitors are needed, usually for decoupling or bypass of GaAs integrated circuits. Standard arrays can contain up to 10 capacitors starting at 0.04pF. Typical overall dimensions range start at 20x10 mils. Array Caps can be fully customized to meet Customer's application requirements.




Array Caps are available with (B) or without borders (A) surrounding the edges to help prevent epoxy shorts and aid optical recognition systems.


≠ Dimensions and Electrode Configuration



Standard border is 2 mils and the gap is between 4 – 6 mils depending on the capacitance required.



≠ Part Numbering





≠ Substrates

Substrates can be supplied as follows:

- **Bare**
- **Metallized:**
 - Gold over Platinum, Palladium, or Nickel
 - Silver over Platinum
 - Custom schemes and patterns to Customer specifications

Thickness Range 3 mils +

≠ Standard Electrode Metallizations

Gold (D4) This metallization consists of a minimum of 70 micro-inches of Gold over Platinum or Nickel which is ideal for all wirebonding methodologies.

Silver (S7) This metallization consists of 20 micro-inches of Silver over Platinum which is ideal for all solder applications whenever the use of Gold is unacceptable.

≠ Metallization Codes

Code	Description
D4	Ti/Pt/Au Titanium/Platinum/Gold (70 µin Gold)
S7	Ti/Pt/Ag Titanium/Platinum/Silver (20 µin Silver)
K2	Ta/Pd/Au Tantalum/Palladium/Gold (75 µin Gold)
L3	Ta/Pd/Au Tantalum/Palladium/Gold (100 µin Gold)

Contact PPI for available metallizations.

≠ Capacitance Tolerance Codes

Class I Dielectrics: AS1 - KS2	
Tolerance	Code
± 20%	M
± 15%	L
± 10%	K

Class II Dielectrics: MS1 - ZS4			
Tolerance	Code	Tolerance	Code
-10% thru +40%	Y	± 20%	M
-20% thru +80%	Z	± 15%	L
0% thru +100%	V	± 10%	K
Guaranteed Min. Value	GMV		

≠ Capacitance Codes

Value	Code
<10pF	1R0 = 1.0pF
>10pF	101 = 100pF

≠ Rated Voltage Codes

Code	Voltage	Dielectric Thickness
2	50V	4 mils
3	100V	6 mils

≠ Packaging

PPI SLCs are available in Waffle Packs (Standard). Other packaging options may be available. Please contact PPI.

≠ Dielectric Materials – Class I

Dielectrics below consist of material exhibiting very low losses, extremely low or closely controlled temperature coefficients, negligible voltage and frequency coefficients, negligible aging effects and high insulation and dielectric breakdown.

Type	IR Min @ 25°C	Temperature Coefficient (-25 to 125°C)	Dissipation Factor (@ 10GHz)	Dielectric Constant (K)	Material
AS1	10 ¹²	Negligible	0.0001	3.8	Quartz
AS2	10 ¹²	Negligible	0.0001	3.9	Si
AS3	10 ¹²	Negligible	0.0001	6.6	BeO
AS6	10 ¹²	P120 ± 25ppm	0.0001	8.7	AlN
AS7	10 ¹²	P180 ± 50ppm	0.0006	9.6	Alumina 96
AS8	10 ¹²	P180 ± 50ppm	0.0006	9.8	Alumina 99.6
BS2	10 ¹²	NP0 ± 30ppm	0.0001	12.6	Titanate
CS1	10 ¹²	0 ± 30ppm	0.001	20	Titanate
ES1	10 ¹²	0 ± 30ppm	0.002	40	Titanate
FS1	10 ¹²	0 ± 30ppm	0.005	50	Titanate
IS1	10 ¹⁵	0 ± 30ppm	0.005	84	Titanate
KS3	10 ⁶	N1500 ± 500ppm	0.0025	160	Titanate

⚡ Dielectric Materials – Class II

Dielectrics below are characterized by high dielectric constants, increased losses and higher temperature coefficients. These properties are inherent with this class of material but the high dielectric constants permit the use of smaller size to achieve low series inductance and meet dimensional requirements. Capacitors made with these materials are often used for coupling of microstrip line circuits where a small chip is necessary. Used as a bypass capacitor, the small size provides low series inductance and dielectric losses are typically of little concern.

Type	IR (MEG-OHMs) 100VDC @ 25°C	Temperature Coefficient (-55 to 125°C)	Dissipation Factor (@ 1 MHz)	Aging (%) HR/Decade	Dielectric Constant (K)
MS1	10 ⁵	5 to -10	0.010	2.0	300
PS1	10 ⁴	± 10%	0.025	3.0	700
SS3	10 ⁵	3 to -10	0.015	3.5	2,200
US1	10 ⁵	0 to -35	0.020	3.0	4,000
US3	10 ⁵	3.0	0.025	3.0	5,000
RS2	10 ⁴	± 10%	0.025	3.0	1250
ZS1	10 ⁵	0 to -80	0.025	3.0	11,000
ZS4	<i>Contact PPI</i>	15 to -15	0.035	3.0	25,000
ZS6	<i>Contact PPI</i>	15 to -15	0.035	3.0	35,000
US3	10 ⁵	± 15%	0.030	3.0	4500



≠ Capacitance, Case Size & Dielectric Availability - Class I Dielectrics

Cap (pF)	Size mils (mm)																	
	10x10		12x12		15x15		20x20		25x25		30x30		35x35		40x40		50x50	
	(.254 x .254)		(.305 x .305)		(.381 x .381)		(.508 x .508)		(.635 x .635)		(.762 x .762)		(.889 x .889)		(1.016 x 1.016)		(1.270 x 1.270)	
	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness
0.04	AS7	5	AS7	6	AS7	10												
0.06	AS7	4	AS7	5	AS7	8	AS2	5	AS2	10								
0.08	ES1	10	AS7	4	AS7	6	AS7	10	AS2	7	AS2	9						
0.1	ES1	8	ES1	11	AS7	5	AS7	9	AS2	5	AS2	7	AS2	10				
0.2	ES1	5	ES1	7	ES1	10	AS7	4	AS7	7	AS7	10	AS2	5	AS2	7	AS2	10
0.3	IS1	6	ES1	4	ES1	6	ES1	11	AS7	4	AS7	7	AS7	9	AS2	5	AS2	7
0.4	IS1	5	IS1	7	ES1	5	ES1	9	ES1	15	AS7	5	AS7	7	AS7	9	AS2	5
0.5	IS1	4	IS1	5	ES1	4	ES1	7	ES1	11	AS7	5	AS7	5	AS7	7	AS2	4
0.6	KS2	6	IS1	5	IS1	7	ES1	6	ES1	10	ES1	15	AS7	4	AS7	6	AS7	9
0.8	MS1	8	KS2	6	IS1	5	ES1	5	ES1	7	ES1	10	ES1	15	AS7	4	AS7	7
1.0	MS1	7	KS2	5	IS1	4	IS1	7	ES1	6	ES1	8	ES1	10	AS7	4	AS7	5
1.2	MS1	6	KS2	4	IS1	4	IS1	6	ES1	5	ES1	7	ES1	9	AS7	3	AS7	5
1.5	MS1	5	MS1	7	KS2	5	IS1	5	ES1	4	ES1	6	ES1	7	ES1	10	AS7	4
1.8	MS1	4	MS1	5	KS2	4	IS1	4	IS1	6	ES1	5	ES1	6	ES1	8	ES1	11
2.0	MS1	4	MS1	5	KS2	4	KS2	7	IS1	6	ES1	4	ES1	5	ES1	7	ES1	11
2.2	RS1	4	MS1	5	KS2	4	KS2	6	IS1	5	IS1	7	ES1	5	ES1	7	ES1	10
2.7	RS1	8	MS1	4	MS1	6	KS2	5	IS1	4	IS1	6	ES1	4	ES1	5	ES1	8
3.3	RS1	7	RS1	10	MS1	5	KS2	4	KS2	6	IS1	5	IS1	7	ES1	4	ES1	7
3.9	RS1	6	RS1	9	MS1	4	MS1	7	KS2	5	IS1	4	IS1	6	IS1	8	ES1	6
4.7	RS1	5	RS1	7	RS1	11	MS1	6	KS2	4	KS2	6	IS1	5	IS1	6	ES1	5
5.6	RS1	4	RS1	6	RS1	10	MS1	5	MS1	7	KS2	5	IS1	4	IS1	5	ES1	4
6.8	RS1	4	RS1	5	RS1	8	MS1	4	MS1	6	KS2	5	KS2	6	IS1	4	IS1	7
8.2	SS3	6	RS1	4	RS1	7	MS1	4	MS1	5	KS2	4	KS2	5	KS2	7	KS2	10
10	SS3	5	RS1	4	RS1	5	RS1	9	MS1	4	MS1	6	KS2	4	KS2	5	KS2	8
12	SS3	4	SS3	6	RS1	5	RS1	8	RS1	11	MS1	5	MS1	7	KS2	4	KS2	7
15	US1	6	SS3	5	RS1	4	RS1	6	RS1	10	MS1	4	MS1	6	MS1	7	KS2	6
18	US1	5	SS3	4	SS3	6	RS1	5	RS1	8	RS1	11	MS1	4	MS1	6	KS2	5
20	US1	5	SS3	4	SS3	6	RS1	5	RS1	8	RS1	11	MS1	4	MS1	5	KS2	4
22	US1	4	US1	6	SS3	5	RS1	4	RS1	7	RS1	9	MS1	4	MS1	5	KS2	4

Shaded cells indicate Class II Dielectrics









≠ Capacitance, Case Size & Dielectric Availability – Class II Dielectrics

Cap (pF)	Size mils (mm)																	
	10x10 (.254 x .254)		12x12 (.305 x .305)		15x15 (.381 x .381)		20x20 (.508 x .508)		25x25 (.635 x .635)		30x30 (.762 x .762)		35x35 (.889 x .889)		40x40 (1.016 x 1.016)		50x50 (1.270 x 1.270)	
	Dielectric	Thickness	Dielectric	Thickness	Dielectric	Thickness												
27	US1	4	US1	5	SS3	4	RS1	4	RS1	6	RS1	8	MS1	3	MS1	4	MS1	6
33	VS1	4	US1	4	US1	6	SS3	6	RS1	5	RS1	6	RS1	11	MS1	4	MS1	5
39	ZS1	6	US1	4	US1	5	SS3	5	RS1	4	RS1	5	RS1	7	RS1	10	MS1	4
47	ZS1	5	ZS1	7	US1	5	SS3	4	SS3	6	RS1	5	RS1	6	RS1	8	MS1	4
56	ZS1	4	ZS1	6	VS1	5	US1	7	SS3	5	RS1	4	RS1	5	RS1	7	RS1	10
68	ZS1	4	ZS1	5	VS1	4	US1	6	SS3	5	SS3	6	RS1	4	RS1	6	RS1	9
82	ZS4	7	ZS1	4	ZS1	7	VS1	6	SS3	4	SS3	5	SS3	7	SS3	10	RS1	7
100	ZS4	6	ZS4	8	ZS1	6	VS1	5	US1	6	SS3	5	SS3	6	SS3	8	RS1	6
120	ZS4	5	ZS4	7	ZS1	5	ZS1	8	VS1	6	SS3	4	SS3	5	SS3	7	RS1	5
150	ZS4	4	ZS4	5	ZS1	4	ZS1	7	VS1	5	VS1	7	SS3	4	SS3	5	RS1	4
180	ZS6	4	ZS4	5	ZS4	7	ZS1	6	VS1	4	VS1	6	VS1	8	US1	8	SS3	7
200	ZS6	4	ZS4	4	ZS4	6	ZS1	5	ZS1	8	VS1	5	VS1	7	US1	7	SS3	6
220	ZS6	4	ZS6	5	ZS4	6	ZS1	4	ZS1	7	VS1	5	VS1	6	US1	6	SS3	6
270			ZS6	4	ZS4	5	ZS4	8	ZS1	6	VS1	4	VS1	5	US1	5	SS3	5
330					ZS4	4	ZS4	7	ZS1	5	ZS1	7	VS1	4	US1	4	US1	7
390					ZS6	4	ZS4	6	ZS1	4	ZS1	6	ZS1	7	ZS1	10	US1	6
470					ZS6	4	ZS4	5	ZS4	7	ZS1	5	ZS1	6	ZS1	8	US1	5
560							ZS4	4	ZS4	6	ZS1	4	ZS1	5	ZS1	7	US1	4
680							ZS6	5	ZS4	5	ZS4	8	ZS1	5	ZS1	6	VS1	4
820							ZS6	4	ZS6	6	ZS4	6	ZS1	4	ZS1	5	ZS1	7
1000									ZS6	5	ZS4	5	ZS4	7	ZS1	4	ZS1	6
1200									ZS6	4	ZS4	4	ZS4	6	ZS4	7	ZS1	5
1500											ZS6	5	ZS4	5	ZS4	6	ZS1	4
1800											ZS6	4	ZS6	6	ZS4	5	ZS4	8
2200													ZS6	5	ZS4	4	ZS4	6
2700													ZS6	4	ZS6	5	ZS4	5
3300																	ZS6	6

⚡ Typical Temperature Characteristics





Headquarters: New York, USA