

TSA72

- 50GHz SOLUTIONS
- SUPER LOW LOSS
- HIGH SHIELDING
- KINK RESISTANT
- EASY-TIGHT COUPLING



TESTeLINK RF Cables



Professional High Frequency RF Test Cables.
2.4mm, 2.92mm(K), and 3.5mm Interfaces.

Key Features;

- Quick Finger Tight Coupling
- Kink Resistant Cable Construction
- Super Low Attn <1.04db/ft @ 50GHz
- Low VSWR < 1.20:1 (Max ≤ 1.40:1)
- RF Leakage ≤-100dB to 18GHz
- High Power 55W @ 50GHz

Configuration Chart

TSA72-D1D1-S18

TSA72-YYZZ-YYY

YYZZ = Connector Options
 2.4mm Male (50GHz) = C1
 2.4mm Female (50GHz) = CF
 2.92mm Male (40GHz) = D1
 2.92mm Female (40GHz) = DF
 3.5mm Male (32GHz) = E1
 3.5mm Female (32GHz) = EF

YYY = Length Options
 FYY = Length in Feet(F06 = 6ft)
 SYY = Length in Inches(S18 = 18")
 YMY = Length in Meters(2M5 = 2.5m)
 CYY = Length in Centimeters(C30 = 30cm)